



Simco

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Simco** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Simco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
13010198	SIMCO ionization with air knife - Transvector Vortec - Air Knife - Transvector active length 2465.2 mm (96 ") Air connection G 1/4 " mounted on SIMCO anti-static bar type MEB active length 2438.4 mm total length 2505.0 mm incl. 3 m HS cable Country of origin: NL stat. Item no .: 85437090 Net weight: 2.3 kg
12070044	SIMCO power supply type A 2A7 S 230 V / 50 Hz / 7 kV 4 x device connection 7kV max. 12 m (from HS cable including rod length) 1 x high voltage display 1 x power switch with display Tests CE, UL / CSA Protection class IP 54 Country of origin: NL stat. Item no .: 85437090 Net weight: 3.1 kg
A 2A3 S	SIMCO power supply type A 2A3 S 230 V / 50 Hz / 3 kV 4 x device connection 3 kV max. 12 m from HV cable including rod length 1 x high voltage display 1 x power switch with display Tests CE, Protection class IP 54 Without Schuko plug Country of origin: NL stat. Item no .: 85437090 Net weight: 2.8 kg
0207000040	
0209000000	
06.59.20.2000	
09.30.07.6100	
09.32.80.0010	
0928800210	

0932800160	
0932800190	
0974707000	
0974707100	
0974709000	
15.45.00.0160	
17809.	
25-R-1000	
39.30.00.0200	
4002371	
400916301	
4012304	
4012306	
4012474	
4015591	
4015703	
4050661	
4105292	
antistatic for ÅÑİ 60Đ +60kV DC	
DES20424	
EP-SH-N 2115mm x 2245mm	
EP-SH-N 2133mm x 2263mm	
EP-Sh-N eff. 2115 mm/total 2245 mm w	
HD-R Charging Bar	
MEB	
MEB eff. 2286 mm/total 2356 mm	
SIMCO-NETZTEIL TYP LB 2A4 D	
STBAR HD-C 2250x 2325MM OAL	
THUNDERION 2.0	
TT-P-645C	
VCM-30	
02.07.00.0040	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
SIMCO CM5-30-N	SIMCO charging generator Operating voltage: 100-240V / 50-60Hz Number of outputs: 4 Output Voltage: 0-30KV Polarity: Negative Output current: 5.0mA max Incl. Power cord 2.5m IEC 320 I/O plug Sub-D 25 pin without cable Country of origin: NL

09.74.70.9081	Supercharging system CM5 60 N for 100/240V, 50/60Hz Output voltage adjustable from 0 - 60 kV negative, current limited remote control connection for voltage, power and on/off including field bus 69.72.70.4800
09.74.70.9181	Supercharging system CM5 60 P for 100/240V, 50/60Hz Output voltage adjustable from 0 - 60 kV positive, current limited remote control connection for voltage, power and on/off including field bus 69.72.70.4800
45.09.00.1035	Emitter ThunderIon 2.0
75.10.99.000	
75.10.99.0020	
45.10.90.3920	
45.09.00.1035	
45.09.00.1030	
Typ A 2A7 S	12070044 230V / 50Hz / 7kV 4 x device connection 7kV max. 12 m (above HS cable incl. rod length) 1 * High Voltage Indicator 1 x power switch with indicator Tests CE, UL/CSA Degree of protection IP 54
Typ FMX-004	15010026 including case and 9 V battery Measuring distance 25 mm Setting via 2 LED light marks on the object to be measured Measuring ranges Electrostatic field Measuring range Low +/- 1.5kV High +/-30.0 kV Ion balance measurement, with the built-in ion adapter Measuring range Low +/- 300 V High +/- 2.0 kV LCD display -- bar graph + / - Digital -- battery -- display 4 digits The measuring device for the commissioning engineer - maintenance. including calibration and calibration certificate
ion FMX-004	
1531011710 Static Neutrolising Busbar	
09.74.70.7000	Charging system CM5 30 N for 100/240V, 50/60Hz Output voltage adjustable from 0 - 30 kV negative, current limited Remote control connection for voltage, current and On off
09.74.70.9081	CM5 60 N charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 60 kV negative, current limited Remote control connection for voltage, current and On off including fieldbus 69.72.70.4800
09.74.70.9181	CM5 60 P charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 60 kV positive, current limited Remote control connection for voltage, current and On off including fieldbus 69.72.70.4800
09.74.70.7000	CM5 30 N charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 30 kV negative, current limited Remote control connection for voltage, current and On off
02.07.00.0040	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
02.07.00.0040	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
08.05.25.7000	A2A7S f¼r 230 V, 50 Hz, 7 kV
15.09.01.0875	anti-static bar ThunderIon IQ 2.0 effective length: 875 mm, dead length: 1070 mm
15.09.01.0625	anti-static bar ThunderIon IQ 2.0 effective length: 625 mm, dead length: 820 mm

00985074000	CMM mini static device
05.07.20.0010	Top Gun III ion spray gun with power supply for 230V, 50Hz, air filter 0.01 micron and 3 m cable/hose, Airflow control valve
4004261	(PRICE/EA) AEROSTAT GUARDIAN 3-FAN OVERHEAD IONIZER, 230V, 50 HZ CE-EU
Mcm30	CHARGER
4008832	VISION CONTROLLER 120-240VAC 50/60HZ 22W
4001995	HOOD
12010707	
1511000100	
Ch30-N	CHARGER 2.5A 115VAC 50/60HZ 30KV 5MA 6MA SCC MAX
4003337	CHARGER
R50-Blue-Bar-20.5in	STATIC NEUTRALIZING BAR 20.5IN OVERALL LENGTH
Hd-C Charging Bar 2200/2275 Mm. + 14 M Cable	
14-21570	
R51-Blue-Bar-27in	STATIC NEUTRALIZING BAR 5800VAC 50/60HZ
As-10	
4010442	POWER SUPPLY, LINEAR, 7KV, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:7KV, POWER RATING:20VA, INPUT VOLTAGE VAC:120V, LENGTH:6.4
08.05.10.7000	
Type Cm5 60 N	High voltage generator type CM5 60 N 100-240V, 50/60Hz Output voltage 60 kV DC
4005105	AIR IONIZER, IONIZING AIR GUN, APPROVAL BODIES:CE / UL, FEATURES:OSHA COMPLIANT, OPERATES ON COMPRESSED AIR OR NITROGEN, STATIC DISSIPATIVE GUN AND 7
4011281	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, CE-EU
4006599	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 14-FOOT CABLE/HOSE ASSEMBLY, N.A.
13200037	
R50-Blue-Bar-20in	NEUTRALIZER BAR 8KV BAR 20IN W/CORD
94-156250	PC BOARD ASSEMBLY ADC/GAIN MEMORY
12070135	
Hd-R 1313/1388	
11020308	
4012557	CONTROL
23040001	
64-08.0525.7000	
	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 5 CABLE/HOSE

4012199	ASSEMBLY, OPTICAL SENSOR, N.A.
08.34.62.5480	
13040005	
4004175	BLOWER STATIC ELIMINATION 2AMP 120VAC 50/60HZ
4010018	NEUTRALIZER BAR 8KV BAR 29IN W/CORD
Simco-Netzteil Typ Lb 2a4 D	
23040002	
4011009	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 4-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, NAM
4002549	IONIZED AIR BLOWER MODEL AS30 2AMP 120VAC 50/60HZ
4088022	STBAR R50 1710X1795MM OAL WITH 7 FOOT HV CABLE
03.20.06.1003	
08.05.25.7900 - A2a7bhr	
4010608	POWER SUPPLY DC HIGH VOLTAGE .6AMP 120VAC 50/60HZ
12010766 Typ P-Sh-N	
Cm5 30n	
4012250	CENTURION SINGLE-FAN DC IONIZING AIR BLOWER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:90CFM, DEPTH:3.375, WIDTH:8, HEIGHT:9.375, SUPPLY VOLTAGE VAC:120
4011549	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
Electrode For A6c7s	
A2a7s 230v 50hz 7 Kv	
4012210	ORION IONIZING AIR NOZZLE, 230V, 7 CABLE/HOSE ASSEMBLY, OPTICAL SENSOR, EU CE
4011546cald	IONIZATION BAR, LENGTH:457MM, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
As-20af	IONIZED BLOWER 9KS RMS MAX 120VAC 60HZ
A2a7s	
05.06.20.0010	
12011804 - Performax Easy	
R50-Blue-Bar-26.5inch	STATIC NEUTRALIZER BAR SHOCKLESS 6INCH RANGE
4050202	MOTOR
4012556	CHARGEMASTER GENERATOR NEGATIVE POLARITY 115/230V
R50-Blue-Bar-14-1/2in	NEUTRALIZER BAR 8KV BAR W/CORD 14-1/2IN
4011154	VISIONI CONTROLLER, 120V, 50 HZ
Vcmbp30	CHARGER
4011547cald	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
4016015c	CHARGER BOARD

4008404	CHARGER
08.05.25.7000 - A2a7s Power	
Vcm30-N	CHARGEMASTER GENERATOR NEGATIVE POLARITY 115/230V
0805257000	
Ivse300	STATIC ELIMINATOR VOLUME 115VAC 435W 5AMP
13200038	
4008729	(PRICE/EA) AEROSTAT GUARDIAN CR2000 2-FAN CLEANROOM OVERHEAD IONIZER, 120V, 60 HZ
R50-Blue-Bar-53in	STATIC NEUTRALIZER BAR SHOCKLESS 8KVAC
Ch25-N	ELECTROSTATIC GENERATOR 2/3MA 25KV OUTPUT
4012229	(PRICE/EA) FUSION IN-LINE LOCALIZED IONIZER, TUNGSTEN (W) EMITTERS
Sdvp	PERFORATION DETECTOR CHARGING UNIT
P-Sh The Upper Electrode Is Double	
Hd-C 2500mm	
Vcmbp60	CONTROLLER
4004063	IONIZING AIR BLOWER, APPROVAL BODIES:CE / UL, DEPTH:17.1CM, EXTERNAL DEPTH:6.75, EXTERNAL HEIGHT:4, EXTERNAL WIDTH:42.75, FEATURES:PATENTED POINT C
4088013	R50 BLUE BAR, 41.1" OL W/7FT CABLE
4014683	POWER SUPPLY
0805254000	
4012563	GENERATOR
4012022	PC2 IONIZING AIR BLOWER, MANUAL EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:100CFM, DEPTH:3.5, WIDTH:6, HEIGHT:7.8, SUPPLY VOLTAGE VAC:24
4012245cald	PC2 IONIZING AIR BLOWER, AUTOMATIC EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW
17809	
As20a W/Oplt, Part Number-4100735as 20 Bar & Block Zus	
11179001	POWER SUPPLE DUAL POLARITY 1AMP 120V 50/60HZ
11040040 - Cm5 30 Negativ	
4050230	POWER SUPPLY FOR IONIZATION BARS 230V 50HZ
A6c7s,Art. Nr. : 08.05.60.7000	
Pshnex-230-50hz.	
T780 80x66	
4012245	PC2 IONIZING AIR BLOWER, AUTOMATIC EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:100CFM, DEPTH:3.5, WIDTH:6, HEIGHT:7.8, SUPPLY VOLTAGE VAC

4002321	POWER SUPPLY MODEL N167 0.24A 120VAC 60HZ
4005106	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 230V, 7 CABLE/HOSE ASSEMBLY, EU CE
Hd-R	
4009245	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, SIDEKICK (HANDS-FREE STAND), N.A
Ecm 30 N 85-265v/50-60 Hz	
4012555	GENERATOR
11020307	
4012212	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR, N.A
13040006	
4008630	GUARDIAN CR2000 3-FAN OVERHEAD IONIZING AIR BLOWER, APPROVAL BODIES:CULUS, CE, DEPTH:6.75
4006992	(PRICE/EA) AIR IONIZER, BENCHTOP, 120VAC, IONIZER TYPE:BENCHTOP, SUPPLY VOLTAGE VAC:120V, PRODUCT RANGE:-
4011550	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
Worksurface Tester Model St 4	
Pn25a	STATIC GENERTR
4011007	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, NAM
A157c2	
4007059	TOP GUN SIDEKICK (FOR HANDS-FREE OPERATION)
Valve Type 16 Offset Design, Female Npt	
10742-001	(PRICE/EA) I-VSE 5000 STATIC CONTROL BLOWER
4012209	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, 5 CABLE/HOSE ASSEMBLY, OPTICAL SENSOR, N.A
Aerostat As-10	
Vcm60n	CHARGER
4012206	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 230V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR, EU
4011726	PREFORMAX IQ POWER SUPPLY 24VDC 1.5AMP INPUT
4011548	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
Spring Connector/Federkonnektor Hv 30/60kv 5050328(91.46.87.3900)	
4011282	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, CE-UK
12011403	
4000048	4 RING
4012205	TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR

11010012	
As-20	IONIZER BLOWER 230V
4011547	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
4088028c	BAR
91-6115- Nxfmr	
03.20.06.0623	
Meb-229-299	
Cm5 60 P	
R50-Blue-Bar	STATIC NEUTRALIZER BAR SHOCKLESS 6INCH RANGE
10735-015	(PRICE/EA) VOLUME STATIC ELIMINATOR (VSE) 3000, 230V, 50HZ CE-UK
Meb 7kv Lenth:375mm	
1500000240	
A2a7bhr 230v 5-Hz 7kv	
4011546	IONIZATION BAR, LENGTH:457MM, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
29t1-1000	
P-Sh-N-Ex	
91-0280a-C	(PRICE/EA) DIGITAL CHARGED PLATE MONITOR, MODEL 280A FOR HIGH FREQUENCY IONIZERS (MP TECHNOLOGY), SOFTWARE AND CARRYING CASE INCLUDED, CALIBRATION CER
C1750	CABLE CUTTER
14020005	
Ch-20-Ni	CHARGING UNIT .3AMP 230VAC 50/60HZ
4009894	TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 7 CABLE/HOSE ASSEMBLY, UK CE
Es2j	
25- R-1000	
4008804	(PRICE/EA) AEROSTAT GUARDIAN CR2000 2-FAN CLEANROOM OVERHEAD IONIZER, 230V, 50 HZ CE-UK
92-6115-Us	AIR FORCE BLOW-OFF GUN, 65PSI, PLUG TYPE:US, AIR PRESSURE MAX:65PSI
He3	
Fmx-002(Replacemont)fmx-004	