

Sisto

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sisto** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sisto Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
PSEUS43T	SISTO-16 PN16 DN050 Diaphragm valve according to type series booklet 8635.1 Housing 5.1301 (EN-GJL-250) without lining Flanges according to DIN EN 1092-2 form B Overall length according to EN558-1 R1 ----- case only
M230L036	Diaphragm for diaphragm valve SISTO-16 / -16HWA / -20 PN16 DN050 and SISTO-16S PN16 DN050-065 according to type series booklet 8635.1 /8635.33 /8643.1 /8635.101 (part 443) -Material: EPDM -Dimension: MD115 mm -SISTO part no .: 42489192
PSEUS43T	Pressure piece suitable for SISTO-16 DN50 -Size MD115 -SISTO part no. 42416443
PSEUS43T	Support spiral suitable for SISTO-16 DN50 -Size MD115 -SISTO part no. 42416465
PSEUS63T	Seal set suitable for SISTO-LAP-SF200.003.5/30 consisting of: - COMPLETE PISTON 200 -LOCKING RING 40x1.75 -BEARING BUSHING 22/40 -GASKET 210/200X1 -DICHT-ABSTR.SATZ22 -O-RING 15X1.5 -O RING 35X3 -SISTO part no. 42426351
M130A009	SISTO-RSK PN16 DN100 Swing check valve according leaflet 8675.1 - body 5.3103 (En-GJS-400-18-LT) with hardrubber-lining NR-H flange dimensions according to DIN EN 1092-2 Form B face to face length according to EN558-1 R1 -disc made out 1.0045 (S355) with softrubber-coating IIR -cover 5.3103 (EN-GJS-400-18-LT)/hardrubber-lining NR-H - bolts A2-70 -standard painting 40 µm RAL 7040 (grey) -SISTO-Material: face-to-face length: Baulnge: 350 mm

M132A008	SISTO-RSK PN16 DN080 Swing check valve according leaflet 8675.1 - body 5.3103 (EN-GJS-400-18-LT) without lining flange dimensions according to DIN EN 1092-2 Form B face to face length according to EN558-1 R1 -disc made out 1.0045 (S355) with soft rubber-coating IIR - cover 5.3103 (EN-GJS-400-18-LT) -bolts A2-70 -standard painting 40 µm RAL 7040 (grey) -SISTO-Material: 42451852 face-to-face length: 260 mm
M251A052	SISTO-16RGAMaXX PN16 Rp 3/4 (DN020) Diaphragm valve according leaflet 8638.1 body 1.4409 (GX2CrNiMo19-11-2) without lining socket ends according to DIN EN 10226-1 (ISO 7/1) diaphragm SISTOMaXX (EPDM/W270) bonnet POM with polycarbonate handwheel -SISTO-Material: 42492605
PSEUS63T	SISTO PNEUMATIC PISTON DRIVE Type: LAP-OF-300.013.5-F10/30 Function: Spring opens - air closes -without attachments -without accessories SISTO PNEUMATIC PISTON ACTUATOR Type: LAP-OF-300.013.5-F10/30 Function: Spring opens # air closes -without mounting parts -without accessories
Rsk/Rsks	
Gg25 M16720	
Sisto-16 Rga	Diaphragm valve according leaflet 8638.1 PN16 RP 1 (DN025) body CC499K-GS without lining socket ends according to DIN 2999/1 (IOS 7/1) diaphragm EPDM/W270 bonnet 5.1301 (EN-GJL-250) handwheel operated with Rilsan-coating -SISTO-Material: 42453657
Dn65 Pn10	
Pseudw71 Sisto-10	
G25 Brefs 200	
16-S-Dn50-Gg25-M13170	