

Sitema



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sitema** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sitema Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|----------------------------------|--|
| Krg 070 10 | SITEMA rod locking KRG 70 Hydraulic keeping open permissible load 150 kN Holding force 300 kN Operating pressure min. 100 bar, max. 160 bar Net weight: 35.5 kg / each Goods tariff no .: 84799070 Country of origin: CE (European Community) |
| Krg 090 10 | SITEMA rod locking KRG 90 Hydraulic keeping open permissible load 250 kN Holding force 500 kN Operating pressure min. 100 bar, max. 160 bar 60.4 kg / each |
| KR 025 31 | SITEMA fall protection KRP 25 Pneumatic hold open permissible load 10 kN Holding force 20 kN Operating pressure min. 4 bar, max. 10 bar Initiator holder with depth stop M8x1, preset Net weight: 4.2kg / piece Tariff number: 84799070 Country of origin: CE (European Community) |
| KX 056 10 | SITEMA locking unit KFH / X 56-100 Clamping by spring force, releasing hydraulically Holding force 80 kN Operating pressure min. 100 bar, max. 160 bar Net weight: 49.0kg / piece Tariff number: 84799070 Country of origin: CE (European Community) |
| KR 080 30 | SITEMA fall protection system KR 80 Hydraulic hold open permissible load 133 kN Holding force 266 kN Operating pressure min. 40 bar, max. 250 bar Initiator holder with depth stop, preset Net weight: 57.0kg / piece Tariff number: 84799070 Country of origin: CE (European Community) |
| FL 056 03 | |
| K 140 10 - DSO.K | |
| KFH 050 50 | |
| KFH 050 70 | |
| KR 040 31 | SITEMA fall protection system KRP 40 Pneumatic opener permissible load 33 kN Holding force 66 kN Operating pressure: min. 4 bar, max. 10 bar Initiator holder with depth |

| | |
|----------------------------|---|
| | stop, preset |
| KR 056 35 | SITEMA fall protection KR/T 56 Hydraulic opener Design for tensile load permissible load 67 kN Holding force 134 kN Operating pressure: min. 40 bar, max. 250 bar Initiator holder with depth stop |
| KR.056.15 | |
| KSP 022-01 | |
| KSP 025 01 | SITEMA safety brake KSP 25 Pneumatic opener permissible load 15 kN Holding force 30 kN Operating pressure: min. 3.5 bar, max. 8 bar |
| KSP-028-02 | |
| KX 018 10 | |
| SK 056 051 | |
| SK 070 036 | |
| KFH 056 50 | SITEMA Locking Unit KFH 56 Clamping by spring force, hydraulic release Holding force 100 kN Operating pressure min. 100 bar, max. 160 bar Net Weight: 35.0kg/pcs |
| KR 080 30 | SITEMA Fall Protection KR 80 Hydraulic hold open permissible load 133 kN Holding force 266 kN Operating pressure min. 40 bar, max. 250 bar Initiator holder with depth stop, preset Net Weight: 57.0kg/pc Goods tariff no.: 84799070 Country of origin: CE (European Community) |
| KR 063 30 | SITEMA fall protection KR 63 Hydraulic hold open permissible load 100 kN Holding force 200 kN Operating pressure min. 40 bar, max. 250 bar Net Weight: 35.0kg/pcs Goods tariff no.: 84799070 Country of origin: CE (European Community) |
| KFH 050 50 | SITEMA Locking Unit KFH 50 Clamping by spring force, hydraulic release Holding force 75 kN Operating pressure min. 100 bar, max. 160 bar Net Weight: 24.6kg/pcs |
| K 100 30 | SITEMA Fall Protection K 100 Hydraulic hold open with integrated venting device permissible load 220 kN Holding force 440 kN Operating pressure min. 40 bar, max. 250 bar |
| KSP 016 01 | SITEMA safety brake KSP 16 Pneumatic hold open permissible load 2.5 kN Holding force 5 kN Operating pressure min. 3.5 bar, max. 8 bar |
| KR 056 10 | SITEMA fall protection KR 56 Hydraulic keeping open permissible load 67 kN Holding force 134 kN Operating pressure min. 40 bar, max. 250 bar |
| KR 050 030 | SITEMA fall protection KR 50 Hydraulic keeping open permissible load 52 kN Holding force 104 kN Operating pressure min. 40 bar, max. 250 bar Initiator holder with depth stop, preset |
| | SITEMA locking unit "R" KFHR 100 Clamping by spring force, |

| | |
|--|---|
| KFHR 100 70 | hydraulic release with encapsulated, ready-to-use proximity switches, unit prepared for oil filling Holding force 250 kN Operating pressure min. 130 bar, max. 160 bar |
| KR 080 30 | SITEMA fall protection KR 80 Hydraulic hold open Permissible load 133 kN Holding force 266 kN Operating pressure min. 40 bar, max. 250 bar Initiator holder with depth stop, preset Net weight: 57.0 kg/piece |
| KSP01601 | |
| KSP 016 01 1 | |
| Locking device | K/TA 100 |
| KR 028 30 | SITEMA fall protection KR 28 Hydraulic opener permissible load 15 kN Holding force 30 kN Operating pressure: min. 40 bar, max. 250 bar |
| KR 040 30 | SITEMA fall protection KR 40 Hydraulic opener permissible load 33 kN Holding force 66 kN Operating pressure: min. 40 bar, max. 250 bar Initiator holder with depth stop, preset |
| KR 028 31 | SITEMA fall protection system KRP 28 Pneumatic opener permissible load 15 kN Holding force 30 kN Operating pressure: min. 4 bar, max. 10 bar |
| KSP 032 01 | SITEMA safety brake KSP 32 Pneumatic opener permissible load 30 kN Holding force 60 kN Operating pressure: min. 3.5 bar, max. 8 bar |
| K 160 30 | SITEMA fall protection system K 160 Hydraulic opener with integrated automatic venting system Permissible load 700 kN Holding force 1400 kN Operating pressure: min. 40 bar, max. 250 bar 304.4 kg/piece |
| KR 100 30 | |
| KR-T-56-15 | |
| KR 080 35 | SITEMA fall protection KR/T 80 Hydraulic opener Design for tensile load permissible load 133 kN Holding force 266 kN Operating pressure: min. 40 bar, max. 250 bar Initiator holder with depth stop 60.0 kg/piece |
| KR/T56 | |
| K/TA 100* K 100 35 | |
| KR/T 80 | |
| Ksp 016 01 | |
| Kfhw32 | |
| Ksp Ba-B10 Safety Brakes | |
| Ksp16 | |
| Kfpa080-025 | |

| | |
|----------------------------------|--|
| Kfpa 050 020-2 | |
| Krgp 028 20 | |
| Krgp028 | |
| Krp40 | |
| Kfp 080 25-20 | |
| Kr40p | |
| SK 200 018 | SITEMA locking unit KB 200 Clamping and releasing hydraulically Holding force 1500 kN Operating pressure 140 bar, max. 140 bar |
| K140 35 | |
| Kit-Kfh30sk | |
| Krgp02220 | |
| Kr025 31 | |
| Kr40-P | |
| Kfh/X36 | |
| 002316 | |
| 1012131660100016 | |
| 10162058 Kb 200 | |
| Krgp28 | |
| Kb125 | |
| Sk050063 | |
| Sk 018 010 | |
| Kfp0401611 | |
| Krgp 016 20 | |
| Kfh1807 | |
| Krg22 Sk 022 027 | |
| Kr04011 | |
| Sk040044 | |
| Fs5011 | |
| Kfh01870 | |
| 1012131311100020 | |

| | |
|--|---|
| Krp02511 | |
| Kfp/Z160-40-2-Ini-Sk040072 | |
| KFH 056 50 DV | SITEMA locking unit KFH 56 Clamping by spring force, releasing hydraulically Operating pressure min. 100 bar, max. 160 bar Seals Viton/PTFE compound |
| Kfh 05650 Dv | |
| Krgp02820 | |
| Kfp/Z80-25 | |
| Sk 032 032 | |
| K 100 35 | SITEMA fall protection K/TA 100 Hydraulic opening Pull version, lifting piston replaceable with integrated automatic venting device permissible load 220 kN Holding force 440 kN Operating pressure min. 40 bar, max. 250 bar |
| Kfpa 063 020-2 | |
| KR 056 30 | SITEMA fall protection KR 56 Hydraulic hold open permissible load 67 kN Holding force 134 kN Operating pressure min. 40 bar, max. 250 bar Initiator holder with depth stop, preset Net Weight: 24.0kg/pcs Goods tariff no.: 84799070 Country of origin: CE (European Community) |
| Kfha 050 022 - Zr-B | |
| Kfh30-Dis-Sk030.003 | |
| Kr 056 30 | |
| Krp100 21 | |
| Kfh56 | |
| Kfha 050 022 050-1 | |
| Sk022034 | |
| Ds St03 B 8 Nutr K | |