

Sofima

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sofima** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sofima Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.





¼r¼n	Açıklama
CCA151FV1	ESE 11 N FD - CCA 151 FV 1 UFI ESE 11 - SOFIMA CCA 151 SPIN-ON screw insert ESE 11 - CCA 151= Type FD - FV= 25µ inorganic fibers - 21 µm [c] N - 1= NBR seal Buna Collapse pressure = 4 bar
CRE048MS1	ERA 40 N ME - CRE 048 MS 1 UFI ERA 40 - SOFIMA CRE 048 Hydraulic filter insert Collapse pressure = 3 bar ME - MS= 60µ metal mesh N - 1= NBR seal Buna
CCH302CV1	EPB 22 N CD - CCH 302 CV 1 UFI EPB 22 - SOFIMA CCH 302 High pressure filter insert Collapse pressure = 21 bar CD - CV= 25µ resin-impregnated paper N - 1= NBR seal Buna
20.711	Filter insert

FA0000004	FA 5528.2 CBE12F12VD UFI CBE - Sofima FA ventilation filter with filter insert EBE12VD - 40.166 - 35µ
CCH8012C1	EPB 31 N HB - CCH 801 2C 1 UFI EPB 31 - SOFIMA CCH 801 high-pressure filter insert collapse pressure = 210 bar HB - 2C= 6µ inorganic fibers 6µ - 7 µm [c] N - 1= NBR seal Buna
CCA151CV1	ESE 11 N CD - CCA 151 CV 1 UFI ESE 11 - SOFIMA CCA 151 SPIN-ON screw insert 11 - 151 = Type CD - CV = 25µ resin-impregnated paper N - 1= NBR seal Buna Collapse pressure = 4 bar
CCH302CV1-	EPB 22 N CD - CCH 302 CV 1 UFI EPB 22 - SOFIMA CCH 302 High-pressure filter insert Collapse pressure = 21 bar CD - CV = 25µ resin-impregnated paper N - 1= NBR seal Buna
0912 CCH032D1 Oil filter	
CCH152CD1 0417 Oil Filter	
Shore NBR 90 O-ring 8*2 mm	
Ca302efd1	
Era 52 N Cd - Cre 100 Cv 1	UFI ERA 52 - SOFIMA CRE 100 Hydraulic filter element Collapse pressure = 3 bar CD - CV = 25µ resin impregnated paper N - 1 = NBR seal Buna
0712cnm102fv1	
Crh 070 Fv 1	SOFIMA - Hydraulic filter cartridge Collapse pressure = 10 bar FV = 25µ inorganic fibers - 21µm [c] 1 = NBR seal Buna
Le180mn1	
0114 - Cre048ms1 / Yağ Filtre	
Fam 003-Mn-X-S-B-2-S (Ex. Fam 003mnb20)	
Cca 302 Ecd 1	
Fpb32f10wgky3x	
Cca152fd1	
Cca302ems1	
Le70mn1	
Rfm125cv1bb801tx	(ELEMENTCRE125CV1) 25 MICRON FILTRATION MATERIAL CODE: RFM125CV1BB801TX
Rfm80fd1b8732s	
Crh070wr1	
Era 51 N Cd - Cre 060 Cv 1	UFI ERA 51 - SOFIMA CRE 060 Hydraulic filter element Collapse pressure = 3 bar CD - CV = 25 resin impregnated paper N - 1 = NBR seal Buna
Cle070mn1	
Rol 340 Cd1 S F9 70	
Spm301fd1sb303xx	