Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

SP1

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

SP1 Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız SP1 Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Type PRLP measuring range 6.50t	217175 Pfeifer traction m. remote PFEIFER Radiolink – plus; Tension meter remotely readable Measuring range 0 ... 6500kg Transmission of the measured values to the reading device by radio (2.4 GHz) - range up to 1000m Suitable as a crane scale or for measuring tensile forces Battery: Standard AA 1.5V batteries can be used 2 pieces in the reading device, 4 pieces in the measuring device Battery life of the reader: about 40 hours of continuous operation Battery life measuring device: about 1200 hours of continuous operation Integrated tare function Digit increment 1.0kg Accuracy +/- 0.1% of the maximum measuring range Dead weight only 2.0kg Unit of measurement: t Temperature range −10 ... + 50 ° C Degree of protection IP67 - protected against moisture and dust Safety factor 5: 1 against breakage Including calibration certificate Delivery in a high-quality aluminum case matching shackles (2 pieces set). Art.Nr: 218252 - no included
218252	2 shackles suitable for PLLP PRLP 6.5t