

Spanset



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Spanset Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Spanset Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
24821	SpanSet Liftfix lifting strap 5.00 t Type HB 5000 - L1 = 4.00 m Loop width 80mm Loop length 500mm Band width 150mm Reinforced crane loops Color code red, DIN EN 1492-1, GS-tested
24820	SpanSet Liftfix lifting strap 5.00 t Type HB 5000 - L1 = 3.00 m Loop width 80mm Loop length 500mm Band width 150mm Reinforced crane loops Color code red, DIN EN 1492-1, GS-tested
21716	secutex protective hose SF-1 150 Length: 3,000 m
23748	4-strand round sling suspension with Safety hook type RSG-4-EKN Load capacity 10.5 t, DIN EN 1492-2 L: 1,500 m Weight: 20.00 kg HS code: 63079098 Country of origin BRD
23746	4-strand round sling suspension with Safety hook type RSG-4-EKN Load capacity 6.3 t, DIN EN 1492-2 L: 1,500 m
34549	SpanSet ABS lashing strap 5 to. 1 piece uncoated. Tape width: 50mm LC 5000 daN, STF 700 Length: 8.00m AB.5.P100.U L: 6,000m
	SpanSet Magnum Plus round sling 30.0 t according to DIN EN 1492-2, color code orange With rib structure made of high-performance fibers on the hose outside, raised woven

21247	carrying capacity information and Loop with RFID transponder Useful length L1= 3,000 m ATTENTION please check the length! the attached photos of the labels relate all only on the 60t. round sling
27674	SpanSet Magnum Plus round sling 60.0 t according to DIN EN 1492-2, color code orange With rib structure made of high-performance fibers on the hose outside, raised woven carrying capacity information and Loop with RFID transponder Useful length L1= 3,000 m
SPL-HK 30	Dicke T1= 20mm Dicke T2= 30mm Breite: 150mm
SPL-HK 50	Dicke T1= 20mm Dicke T2= 50mm Breite: 150mm
21347	SpanSet Liftfix round sling 4.00 t Type RS 4.0 - L1= 1.00 m DIN EN 1492-2, color code grey, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 1,000m
24822	SpanSet Liftfix round sling 3.00 t Type RS 3.0- L1= 6.00 m DIN EN 1492-2, color code yellow, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 6,000m
21344	SpanSet Liftfix round sling 3.00 t Type RS 3.0- L1= 5.00 m DIN EN 1492-2, color code yellow, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 5,000m
21353	SpanSet Liftfix round sling 5.00 t Type RS 5.0 - L1: 6.00m DIN EN 1492-2, color code red, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 6,000m
21343	SpanSet Liftfix round sling 3.00 t Type RS 3.0- L1= 4.00 m DIN EN 1492-2, color code yellow, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 4,000m
21324	SpanSet Liftfix round sling 1.00 t Type RS 1.0- L1= 4.00 m DIN EN 1492-2, color code violet, GS tested With woven barrel strips as carrying capacity. The crease label is sewn in two layers and therefore tear-resistant and protected against abrasion. L: 4,000m Delivery time is about.
21925	ABS ratchet lashing strap 2500 daN/50 with STF350 D001563 weight: 3 kg L: 6,000m
SpanSet Magnum Plus round sling 60.0 t	according to DIN EN 1492-2, color code orange With rib structure made of high-performance fibers on the hose outside, raised woven carrying capacity information and Loop with RFID transponder Useful length L1=8m
SPANSET 38 MM 200 METER CORDLASH	

150	
020035-2-01201-9	
GRIP-G D000162 EP.8	
PS.0050.01,5	POWER STAR SLEEVE WITH EYE (CLOTH/POLYESTER SLEEVE) / PB 5000-PR EN 1492-1, (EYE WIDTH:80MM/ LENGTH:500MM), SLUG LENGTH(L1):5000MM(5MT), SLUG WENS:150MM, SLUG THICKNESS: 6.4MM, EMNYT COEFFICIENT:7, CEN CODE:RED, CAPACITY:5000KG(5TON), (CERTIFICATE INCLUDED)
Slingshot Polyester 3 Ton 6 Meters EN1492-1	
Slingshot Polyester 3 Ton 4 Meters EN1492-1	
Slingshot Polyester 3 Ton 2 Meters EN1492-1	
Slingshot Polyester 3 Ton 1 Meters EN1492-1	
Load Band TK 50mm 12 Meters EN1492-1 Tensioner	5ton
American chain single 2.8 MT.	EN 818 -2 7x2800 SWL 3500 LBS
8MM X 1,5MT	CAPACITY 2800 KG AT 0-45 ° ANGLE CAPACITY 2000 KG AT 45-60 ° ANGLE GERMAN ORIGIN CERTIFIED
8MM X 1,5MT	CAPACITY AT 0-45° ANGLE 4250 KG CAPACITY 3000 KG AT 45-60 ° ANGLE GERMAN ORIGIN CERTIFIED
Slingshot Polyester 10 Ton 5 Meters EN1492-1	
SLING 1LEG CHAIN D10 L535 3T	
SLING 2LEG D16 L220 4.2T	
Chain Hoist For Slickline	2T, 3m
SLING 1LEG D13 L550 3.25T	
0106200500010	RS 5.0, L1 = 1.0 m Liftfix round sling, WLL: 5000 kg
0106201000030	RS 10.0, L1 = 3 m Liftfix round sling, WLL: 10000 kg
20941523	
50000000	
20909991	
20909990	
443dd160.003000	

[40000000](#)