Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Spectron

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Spectron Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Spectron Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
U33-0,5bar-0-B-0-Nfg/Fg/O2	Spectrotec pressure regulator U33 Precision diaphragm pressure regulator for non-corrosive gases up to quality 4.5, with 1 relief valve Housing material: brass Membrane: NBR Leakage rate: 10-3 mbar l / s He Gas type: NFG / FG / O2 Form: max. 10 bar Back pressure: 5 - 50 mbar 30-300 mbar 200 - 600 mbar 400 - 1,500 mbar Connections: Inlet and outlet: G½ “inside
Ssy-0185-48	
Lm53-6-L-50-1,5-0-M-M-0-A-B-Nfg/Fg/O2	Two-stage 6-port line pressure regulator for non-corrosive gases up to quality 6.0 with 2 manometers and 1 relief valve Material: Housing: chrome-plated brass Membrane: Hastelloy C276 Leakage rate: 10-8 mbar l / s He Form: max. 50 bar Back pressure: max. 1.5 bar Connections: Input and output: ¼ “NPT inside Order code: LM53-6-L-50-1,5-0-M-M-0-A-B-NFG / FG / O2
U11-40-4-... W6F	
U11-40-6-... W6E	
U13 F-50-16-0-M-M-0-NFG W6L	
Model: BU 13-2x2-20-M-0-H2	Pressure control panel
Model: BU 13-2x2 -KBU13	Spare part kit for regulator U13

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HDS-ES-300-....-M-KK1/2-H2	2 meter length ****for H2 connection****
U11W6F	S-NR:51296910 TYP:U11W6/F P1:40 bar P2:4bar ***** P2:4bar ******
U13AC-W6 C2H2	
U33-1,5BAR-0-B-0.	With P1: 10 Bar and P2: 5 – 1500 mbar.
SR-200-BS3-NFG	Spectrolab spiral tube, stainless steel zum Anschluss der Gasflaschen an der Entspannungsstation für Gase bis Qualität 6.0 * Nennweite: 4mm * 4-fach Spiralwindung für besonders hohe Flexibilität * auch für Schrankeinbau geeignet Anschlüsse: Eingang: Flaschenanschluß, BS3 - Messing verchromt Ausgang: 6mm Klemmring, Edelstahl
SR-200-DIN1-H2	Spectrolab spiral tube, stainless steel for connecting the gas cylinders to the relaxation station for gases up to quality 6.0 * Nominal size: 4mm * 4-fold spiral winding for particularly high flexibility * also suitable for cabinet installation Connections: Input: Bottle connection, DIN 477-1, No.1 Output: 6mm compression ring, stainless steel
BM55-1 Pressure Control Panel-1X1-300-20 (2 units)	
HDS-ES-300-1M-BS341-3-M-CE6	High Pressure Tube Connenction

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
EM55-3 Pressure Control Panel P1:40 P2:10 bar	(3 units)
EM55-1 Pressure Control Panel P2:10 bar (1 unit)	
EM15 Point of Use Equipment Bench	P2:10 bar bench pressure valve
75160211	GAS CLEANING SYSTEM UV PLUS/VERS. 2
Spectrocem pressure regulator LE71	Pressure regulator for non or slightly corrosive gases up to quality 6.0, complete with central filter, 2 manometers (without relief valve) Material housing: stainless steel Diaphragm: Hastelloy Type of gas: chlorine Leak rate: 10-8 mbar l/s He Inlet pressure: max. 40 bar Back pressure: max. 10 bar Connections: Input and output: 3/8" NPT inside Order code: LE71-4-L-40-10-O-M-M-O
75160211	GAS CLEANING SYSTEM UV PLUS/ VERSION 2
FE 53L-300-4-DIN477-1-M-0-A-B-FG	
U33	
U13W6L	
U11W6E	
U11W6F	
ET2000	
ET 2000-BG	
U33,03-M-NFG	
U11-W6 E-NFG-40	
U13-W6 E-NFG-40	
BT2000-2x1	manually switchable pressure control panel for non-corrosive gases, up to quality 4.5 for connecting 2 bottles/bundles Material: Housing: Brass Membrane: EPDM 2 x service gas valves

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	2 exhaust valves Filter in the service gas inlet Central filter in the pressure regulator relief valve Mounted on a stainless steel mounting plate Leak rate: 10-3 mbar l/s He Gas type: NFG/FG/O2 Pre-pressure: max. 300 bar Back pressure: adjustable up to 10 bar Connections: Inlet: G½“ outside Outlet: ¼“ NPT female BT2000-2x1-300-10-MM-0-NFG/FG/O2
HDS-PE-200-3,5M-DIN477-6-0-CM1/4	High-pressure hose assembly HDS-PE for non-corrosive technical gases except oxygen and acetylene with safety rope Material: PE Gas type: Noble gas* Length: 3.5 m Connections: Inlet: DIN477 No. 6* (200 bar) Outlet: G½" inside Order code: HDS-PE-200-3.5M-DIN477-6-0-CM1/4
LM51-6-L-200-20-0-M-M-0-A-B-H2	Spectrolab line pressure regulator Single-stage 6-port line pressure regulator for non-corrosive gases up to grade 6.0, with 2 pressure gauges and 1 relief valve Material: Housing: Brass, chrome-plated Membrane: Hastelloy C276 Leakage rate: 10^{-8} mbar l/s He Gas type: Hydrogen Pre-charge pressure: max. 200 bar Back pressure: max. 20 bar Connections: Input and output: ¼” NPT internal Order code: LM51-6-L-200-20-0-MM-0-AB-H2
Fm51 Ord.Code Fm51-6-L-200-10-Din6-M-M-0-A-B-He	
Et2000	Spectrotec output pressure regulator ET2000 sampling point pressure regulator for non-corrosive gases up to quality 4.5

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Material: Housing: brass Membrane: EPDM Leakage rate: 10-3 mbar l / s He Type of gas: flammable gases Form: max. 40 bar Back pressure: max. 10 bar Connections: Input: G⅜ "LH inside Output: hose nozzle 9mm Order code: 71705901
Ssy0185-48	SPECTROTILT - Inclinometer
Le51-6-L-200-4-0-M-M-0-A-B-H2s	
Fe51 Ord.Code Fe51-6-L-200-10-Din6-M-M-0-A-B-He	
Em55-1	Spectrolab sampling point Removal point for wall mounting for non-corrosive gases up to quality 6.0 Material: Housing: chromed brass Membrane: Hastelloy C276 * 1 piece of service gas valve with open / closed position indicator * Filter in the hot gas inlet * 1 pressure regulator EM51 with back pressure gauge * mounted on a two-piece, powder-coated aluminum base plate Leakage rate: 10-8 mbar l / s He Gas type: xxx Form: max. 40 bar Back pressure: max. 10 bar Connections: Input and output: ¼ "NPT inside Order code: EM55-1-40-10-O
Et2000-40-10-O2	
U47k3b	
Lm52-6-R-300-10-O-M-M-O-A-B	
Le51-6-L-200-10-0-M-M-0-A-B-Nh3	
Et2000-40-10-O2/Nfg/Fg	
Fe51-6-L-200-10-Cga580-M-M-0-A-B-He	
Lm51-4-L-300-50-O-M-O-B	
Rxclo12009	
Fm51-6-L-200-200	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
4001/4	SPECTROPHOTOMETER VISIBLE 325-1100NM
U11w6f	
Spectrolab Spiral Tube, Stainless Steel	Spectrolab spiral tube, stainless steel for connecting the gas cylinders to the expansion station, for gases up to quality 6.0 * Nominal diameter: 4mm * 4-fold spiral winding for particularly high flexibility * also suitable for cabinet installation Connections: Input: according to DIN 477 200 bar - acc. Type of gas Output: 6mm clamping ring, stainless steel Order code: SR-200-DIN477-gas type-related
51296910	
Et65bv	Spectrotec Extraction point for non-corrosive gases up to quality 4.5 Material: Housing: brass Membrane: EPDM * 1 after wall mounting plate * Ball valve as a shut-off device for non-flammable gases with G⅜ "RH male in the inlet * Pressure regulator for NFG (40/10 bar) with pressure gauge and Hose nozzle 6 mm in the outlet Order code: ET65-BV-1M-NFG-M10
Le51-6-L-20-4-0-M-M-0-B-B-Nh3	
Bt2000-2lx1	Automatic switching relaxation station for non-corrosive gases up to quality 4.5, for connecting 2 bottles / bundles Material: Housing: brass Membrane: EPDM * 2 pieces of service gas valves * 2 pieces of exhaust valves * Filter in the hot gas inlet * Central filter in the pressure regulator * Blow-off valve * Forward and back pressure gauge * Mounted on a stainless steel mounting plate Leakage rate: 10-3 mbar l / s He Type of gas: N2, CO2, DL (KH), Ar Form: max. 200 bar Back pressure: max. 10 bar Connections: Input: G½ "outside Output: ¼ "NPT in Order code: BT2000-2Lx1-200-10-M-M
Pc3300	ERASER

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Hds-Pe	High pressure hose line HDS-PE for non-corrosive industrial gases except oxygen and acetylene, with safety rope Material: PE Type of gas: N2, CO2, DL, Ar Length: 1 meter Connections: Input: DIN477 No. Gas-related (200 bar) Exit: G½ "inside Order code: HDS-PE-200-1M-DIN477-KK1 / 2
Opx-365c	UV LED CURING FLASHLIGHT, 365NM, UV INTENSITY CERTIFIED RECHARGEABLE WITH SMART AC CHARGER, SMART 12V DC CHARGER, HOLSTER
Bm55-2u	Spectrolab relaxation station automatically switching relaxation station for non-corrosive gases up to quality 6.0, to connect 2 bottles Material: Housing: chromed brass Membrane: Hastelloy C276 * 2 pieces of service gas valve with on / off position indicator * 2 pieces exhaust valve with on / off position indicator * Filter in the hot gas inlet * Blow-off valve * Forward and back pressure gauge * Mounted on a two piece powder coated aluminum base plate * 2 pieces bottle holders Leakage rate: 10-8 mbar l / s He Gas type: O2, He, H2, CH4, Ar Form: max. 200 bar Back pressure: max. 20 bar Connections: Input: 6mm clamping ring, stainless steel Output: ¼ "NPT in Order code: BM55-2U-200-20-M-M
66me0008	
Xs-254	SENSOR DETECTOR, 254NM, STANDARD
717 05 901	
Fm52-L	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.