



## Spirotech

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Spirotech** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Spirotech T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Bronze 1/2"</a>	
<a href="#">SpiroTech AB050</a>	ApiroTop brass large air vent SpiroTop - large air vent with no lockable Permanent vent valve and right-angled drilled Exhaust port for quick release and Ventilate of pipeline networks. Medium water and water / glycol (50/50%) Execution: brass Connection: DN 15 internal thread at the vent valve: DN 15 male thread. Operating pressure: 10 bar max. Max. Temperature: 110 degrees C
<a href="#">Wie bild 180 Grad</a>	
<a href="#">SpiroCross 200 hydraulic distributor</a>	
<a href="#">SpiroCross 250 hydraulic distributor</a>	
<a href="#">SpiroCross 80 hydraulic distributor</a>	
<a href="#">BA050L</a>	5liter
<a href="#">BA125F</a>	
<a href="#">Spirotech</a>	
<a href="#">SpiroTop PN16</a>	
<a href="#">SpiroTop PN25</a>	
<a href="#">IST21.03 DN80</a>	

<a href="#">IST 22.03 DN80</a>	
<a href="#">AB050</a>	Large air vent SpiroTop 1/2" internal thread, 10 bar, 110°, float: PP
<a href="#">Body and Cover: AISI 316L Quality Stainless Steel</a>	Sphere: AISI 316L Quality Stainless Steel Gasket:PTFE Operating Temperature: -20 / + 150 °C Threaded Three Piece Full Bore Ball Valve 1/2" AUTOMATIC AIR EXTRACTION DEVICE
<a href="#">AUTOMATIC AIR EXTRACTION DEVICE</a>	Body and Cover: AISI 316L Quality Stainless Steel Maximum Operating Temperature: -25 / +180 °C Pressure Class:PN16 Threaded Strainer 1/2"
<a href="#">AUTOMATIC AIR EXTRACTION DEVICE</a>	Body and Cover: Ni Plated Brass Globe: Chrome Plated Brass Gasket:PTFE Maximum Operating Temperature: 110 °C Pressure Class:PN16 Threaded Full Bore Ball Valve 1/2"
<a href="#">AUTOMATIC AIR EXTRACTION DEVICE</a>	Body and Cover: Ni Plated Brass Globe: Chrome Plated Brass Gasket:PTFE Maximum Operating Temperature: 110 °C Pressure Class:PN16 Threaded Strainer 1/2"
<a href="#">Automatic Air Release Device 1/2" (DN15)</a>	
<a href="#">2" Spirovent BSP FEMALE</a>	
<a href="#">AB050/R004</a>	SpiroTop Automatic Large Air Vent AISI 316 G ½ internal thread P max. 25 bar T max. 200 °C
<a href="#">SPIROTOP 1/2" Air Purger PN10 AB050</a>	
<a href="#">AB050-</a>	Large air vent SpiroTop 1/2" internal thread, 10 bar, 110°, float: PP (VPE): 12
<a href="#">AB050/030</a>	SpiroTop Automatic Large Air Vent G ½ Internal Thread P max. 16 bar T max. 110 °C
<a href="#">7738307340</a>	
<a href="#">Ua022w</a>	SPIROVENT RV2 micro bubble separator Connection: 22 mm - clamping ring
<a href="#">Ba100f</a>	SpiroVent Air separator DN 100 flange P max. 10 bar T max. 110 C
<a href="#">Ba150l</a>	
<a href="#">Tab050</a>	optional Prefabricated insulation for SpiroTop - automatic large air vent Max. 110 ° C Item No. TAB050
<a href="#">Ab050</a>	SpiroTech AB050 SpiroTop brass large air vent SpiroTop - large air vent with non-lockable Permanent- vent valve and drilled at right angles exhaust port for quick venting and ventilation of pipeline networks. Medium water and Water/Glycol (50/50%) Version : brass Connection : DN 15 inner thread at the drain valve: DN 15 outer thread Operating pressure: 10 bar max. Max. temperature : 110 degrees C
<a href="#">7738323622</a>	

<a href="#">Sanitäre Installation</a>	
<a href="#">Et 01/02</a>	
<a href="#">7747222507</a>	
<a href="#">Aa075/008</a>	
<a href="#">7738323616</a>	
<a href="#">Spirotop Ab050</a>	
<a href="#">Bf100f</a>	SpiroTrap Removable Mud separator DN 100 flange P max. 10 bar T max. 110 C
<a href="#">Et 03</a>	
<a href="#">7738323619</a>	
<a href="#">7726241011</a>	
<a href="#">S-Hc200f-002</a>	
<a href="#">Art.-Nr.: Ab050/007</a>	SPIROTOP - automatic large air vent High temperature Connection: ½ "IG T-Max .: 180 ° C P-max .: 10 bar
<a href="#">Art.-Nr.: Ab050/002</a>	SPIROTOP - automatic large air vent High temperature Connection: ½ "IG T-Max .: 180 ° C P-max .: 10 bar
<a href="#">Bv/00/03-1000 Lt</a>	
<a href="#">Bv 1/2quot;</a>	
<a href="#">Bv/00/04-750 Lt</a>	
<a href="#">Ab050-R007</a>	
<a href="#">Art.-Nr.: Aa075</a>	SPIROVENT MICROBUM BLOWER SEPARATOR CONNECTION: ¾ "IG
<a href="#">Spirtrap Dn 125</a>	
<a href="#">Et 04</a>	
<a href="#">S-Hc200f-002 (Tap)</a>	
<a href="#">Hc150f</a>	
<a href="#">Ae150</a>	
<a href="#">7747204666</a>	
<a href="#">Bv/00/01amp;02-4000 Lt</a>	
<a href="#">Ab050/002</a>	
<a href="#">Ab050/008</a>	
<a href="#">Be100f</a>	SpiroTrap Mud separator DN 100 flange P max. 10 bar T max. 110 C

<a href="#">Sv2-150-Fh</a>	
<a href="#">Ab050/R007</a>	SPIROTOP - automatic large air vent Connection: ½ "IG Max. 10 bar / 180 ° C Housing: stainless steel Float: stainless steel Art.-No .: AB050 / R007
<a href="#">Art.-Nr.: Ab050/030</a>	SPIROTOP - AUTOMATIC BIG DEVICES SPECIAL CONNECTION: ½ "IG MAX. 16 BAR / 110 ° C
<a href="#">Art.-Nr.: Ab050</a>	SPIROTOP - automatic large air vent Connection: ½ "IG Art.-No .: AB050