

Sps Electronic

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Sps Electronic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sps Electronic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
8-06-1676-0	
HL81	
IL3801F	
IS580F	
KL10	
KL15	
KS12-K	
MP01	
PE81-I	Test probe with start button, 2m connection cable for protective conductor testing and Lemosa 4-pin connector
PP20	
probe for S3301E	
R2/HA1885G	
RL21	
RL42	
RL42H	
WL23	
WS01	
LG1805B	LG1805B - Tabletop device - Safety current limiter Manufacturer standards VDE, IEC, EN, UL

Ürün	Açıklama
	Types of tests: - Continuity test - Protective conductor test (1A - 30A) 0 - 11600mOhm - Insulation test (100 - 6000VDC) 250kOhm - 10GOhm - High-voltage test AC (100 - 5500VAC) 0 - 3mA - High-voltage test DC (100 - 6000VDC) 0 - 12mA - Functional test up to 300VAC / 16A - Substitute leakage current test (0 - 270VAC) 0 - 10mA Scope of delivery: - LG1805B - Power cable - User manual - An ISO protocol or an IEC17025 calibration certificate can be ordered as an option. Connections: - Connections for high-voltage test guns - Connection for start signal from pistol - Laboratory sockets "PE source" / "PE sense" - Power supply for functional testing - IEC C13 power inlet for power cord - I/O interface - RS232 interface: Serial interface for connecting a PC - LAN connection - 2x USB ports - Connection for PE test probe
PE81-I	Test pin with start button, 2m connecting cable for protective conductor testing
ISO9001-SPS04	Calibration ISO 9001 Group 4 for PLC test devices
PE81-I	Test pin with start button, 2m connection cable for protective conductor testing and Lemosa plug 4-pin
CX02-EU	Type E socket according to national standard
CY02-EU	Power cable with EU type E plug
DAT3810	PLC data acquisition and remote control software option WINDOWS for all series, hardware license on device
R2/Ha1885g Garantieerweiterung Ha1885g Auf 2 Jahre	
D2000	
Ap02	
Pp 20 Universal Test Connector	

Ürün	Açıklama
Mc 22	
Mc 22 Mounting Clip	
Hochspannungsrelais 5000vac / Max. 30apolzahl 2, Spule 24vdc / 0,25 A	
Ha1885g	
RI42 Hochspannungsschalter 5000vac/ Max. 30a, 24vdc/0,25 A Artikel-Nr .	
WI23 Warnleuchtsatz, Standardanschlusskabel 1,5 Manzeige: Zustand Des Generators	
RI21 Hochspannungsrelais 5000vac / Max. 30apolzahl 1, Spule 24vdc / 0,25a	
Dk21	
Arc18	
RI 42 Relais	
Eh1905-Y	
RI21 Hochspannungsrelais 5000vac / Max. 30a Polzahl 1, Spule 24vdc / 0,25a	
II3801f Insulation Tester	
Mp01 Kalibrierzertifikat Gruppe 1nach Iso 9001 Inklusive Kalibrierschein	
Pp20 Universal Power Socket Pp20	
Sp02	
RI42 Hochspannungsrelais 5000vac / Max. 30a Polzahl 2, Spule 24vdc / 0,25a	
St 1800b	
RI42 Hochspannungsrelais 5000vac / Max. 30apolzahl 2, Spule 24vdc / 0,25a	
Sp03	
Ws01 Warnschild 200 X 300 Mm	

Ürün	Açıklama
Ha3600d	
Iec17025-Sps02	
Dat1800	
Ke01	