Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Stahl

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Stahl Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Stahl Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
8571/11-406 + 8571/12-406	MAX 690V 32 A 3P+E
8571/11-406	4x32A Exproof
Typ 9468/32-08-11	Remote I / O IS1 + Analog Universal Module HART for Zone 1 Ex i ---- explosion-proof Area of application (zones): 1, 2, 21, 22 Ex interface zone: 0, 1, 2, 20, 21, 22 Number of channels: 8 Ex i inputs / outputs Max. Voltage Uo: 24.4 V Max. Current Io (2-wire): 80 mA Max. Current Io (3-wire): 81.8 mA Max. Power Po (2-wire): 488 mW Max. Power Po (3-wire): 499 mW Ambient temperature min. : -40 ° C Ambient temperature max. : +75 ° C Gas explosion protection: II 2 (1) G Ex ia [ia Ga] IIC T4 Gb Dust explosion protection: II (1) D [Ex ia Da] IIIC For further information see: r-stahl.com webcode 9468A HS product number: 85363010 DE 0.275 KG
6001/522-9510-15-131	Linear luminaire for fluorescent lamps GRP explosion-proof Luminaire cover: clear Tub material: polycarbonate Housing material: polyester resin Execution: standard execution Housing color: light gray (RAL 7035) Number of lamps: 2 Lamp power: 18 W Dimensions (L x W x H): 700 x 184 x 125 mm Rated operating voltage AC: 220.00 - 240.00 V Rated operating voltage DC: 220.00 - 240.00 V Application area (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb IIC T4 Gb

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Dust explosion protection: II 2 D Ex tb IIIC T80 ° C Db Ambient temperature min. : -30 ° C Ambient temperature max. : +50 ° C Note through-wiring: max. 3x16 A Maximum ambient temperature 2: +55 ° C Note through-wiring 2: max. 3x10 A Impact resistance (IEC 62262): IK10 Through-wiring: with 5 conductors 2.5 mm2 Ballast: 6042 / 243-21 Threaded plate: 2x plastic Holes: 3 x M25 attached Cable and Cable entries: 2 x M25 Ø 7 - 17 mm Cable entry material: black polyamide Sealing plug: 2 x M25 x 1.5 Closure plug material: black polyamide Documentation languages: German English For more information see: r-stahl.com web code 6001A
6002/4128-0100-152-1110-11 -8500	Replacement of type: 6002 / 2182-5400-5131-0 6002 / 1182-5400-5131-0 Luminaire cover: clear Tub material: polycarbonate Housing material: polyester resin Execution: standard execution Housing color: light gray (RAL 7035) Number of lamps: 1 Lamp power: 22 W Light distribution: 120 ° x120 ° with diffuser Luminous flux of the luminaire: 2,910 lm Luminaire efficiency: 132 lm / W Luminaire efficiency DC operation: 50% DC Light color: neutral white Color temperature: 5,000 K LED service life: L90B50 ≥ 100,000 h Operating device service life: C10 ≥ 50,000 h, Ta ≤ 60 ° C Dimensions (L x W x H): 700 x 184 x 125 mm Rated operating voltage AC: 100.00 - 240.00 V Rated operating voltage DC: 110.00 - 250.00 V Application area (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb ib mb op is IIC T4 Gb Dust explosion protection: II 2 D Ex tb op is IIIC T100 ° C Db Ambient temperature min. : -40 ° C Ambient temperature max. : +50 ° C Note through-wiring: max. 3x16 A Maximum ambient temperature 2: +60 ° C Note through-wiring 2: max. 3x10 A Impact resistance (IEC 62262): IK10 Diffuser: with diffuser

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Through-wiring: with 5 conductors 2.5 mm2 Ballast: 6045 / 211-120-10 Threaded plate: 2x plastic Holes: 3 x M25 attached Cable and Cable entries: 2 x M25 Ø 7 - 17 mm Cable entry material: black polyamide Sealing plug: 2 x M25 x 1.5 Closure plug material: black polyamide Documentation languages: German English For more information see: r-stahl.com web code 6002D HS goods number: 94054039 DE Net weight: 4,450 KG
222826	Mounting rail for 6001 accessories Consists of 1 pair
8571/11-406	Switch socket explosion-proof Rated operating voltage AC: 415 V Frequency range: 50 - 60 Hz Detailed number of poles: 4 P (3 P + PE) Identification color: red Coding (time setting): 6 Housing material: polyamide Application area (zones): 1, 2, 21, 22 Scope: European Union (ATEX) IECEx Ambient temperature min .: -30 ° C Ambient temperature max.: +55 ° C Rated operational current: 32 A Gas explosion protection: II 2 G Ex db eb IIC T5 Gb Dust explosion protection: II 2 D Ex tb IIIC T75 ° C Db Maximum ambient temperature 2: +40 ° C Gas explosion protection2: II 2 G Ex db eb IIC T6 Gb Dust explosion protection2: II 2 D Ex tb IIIC T60 ° C Db Degree of protection (IP): IP66 Entries: 2 x M32 x 1.5 Cable and line entries: 1 x M32 x 1.5 Introduction 1 type: 8161/7-M32-2109 Cable entry material: black polyamide Cable diameter: 9... 21 mm Sealing plug: 1 x M32 x 1.5 Closure plug material: black polyamide Plate with threaded holes: - For more information see: r-stahl.com web code 8571A
8571/12-406	plug explosion-proof Rated operating voltage AC: 415 V

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Frequency range: 50 - 60 Hz Detailed number of poles: 4 P (3 P + PE) Identification color: red Coding (time setting): 6 Housing material: polyamide Application area (zones): 1, 2, 21, 22 Scope: European Union (ATEX) IECEx Ambient temperature min .: -30 ° C Ambient temperature max.: +55 ° C Rated operational current: 32 A Gas explosion protection: II 2 G Ex db eb IIC T5 Gb Dust explosion protection: II 2 D Ex tb IIIC T75 ° C Db Maximum ambient temperature 2: +40 ° C Gas explosion protection2: II 2 G Ex db eb IIC T6 Gb Dust explosion protection2: II 2 D Ex tb IIIC T60 ° C Db
8570/11-306	3x16 A Ex-Proof
8570/12-306	3x16 A Ex-Proof
9170/21-12-21s	Switching amplifier Field circuit Ex i explosion-proof Number of channels: 2 Connection type: screw terminal Output per channel: 1 changeover contact - power relay LFD relay: No. Nominal current: 18 mA SIL: 2 Ambient temperature min.: -20 ° C Ambient temperature max.: +70 ° C Max. Voltage Uo: 9.6 V Max. Current Io: 10 mA Max. Power Po: 24 mW Gas explosion protection: II (1) G Ex [Ex ia Ga] IIC Dust explosion protection: II (1) D [Ex ia Da] IIIC For more information see: r-stahl.com web code 9170A
8560/51-4222	
8146/5-V37-300-50-0050	Safety switch 10 A explosion-proof Replacement of type: 8537 / 2-300-7000 Rated operating voltage AC: 690 V Rated operational current: 10 A Housing material: glass fiber reinforced polyester resin Detailed number of poles: 3 poles Auxiliary contact normally closed: without Auxiliary contact normally open: 1 normally open / lagging Additional clamp: standard (without)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Application area (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb IIC T6 Gb Dust explosion protection: II 2 D Ex tb IIIC T80 ° C Db Ambient temperature min .: -40 ° C Ambient temperature max.: +51 ° C Special conditions for extended ambient temperature, see operating instructions: Extended ambient temp. min .: -40 ° C Extended ambient temp. max .: +69 ° C Degree of protection (IP): IP66 Cable entry: 2 x M25 Ø 7 ... 17 mm 1 x M20 Ø 4 ... 13 mm Connection cross-section: 2.5 ... 4 mm2 Connection cross-section HIKO: 1.5 ... 1.5 mm2 finely stranded
6043/792-201	201644 Repair kit 1: 1 6043 / 792-201 220V - 254V, 18 / 36W HS product number: 85041080 DE Net weight: 2.100 KG
258328	Ballast repair kit Usage: 6000 1 / 2x18W 6042/2 1xDC 230V
200207	40 A safety switch explosion-proof Type: 8146/5-V37-305-51-1010-K Replacement of type: 8537 / 2-305-5001-K 8537 / 2-705-7001
8570/12-306-S-XX-X-XX-XXX 3-pole plug	200 to 250 V AC, 50 / 60 Hz, 16 A
9182/10-51-14s	201682 temperature transmitter field circuit Ex i explosion proof Type : 9182/10-51-14s Number of channels : 1 Type of connection : screw terminal Pitch : 17.6mm Signal types : Temperature input Output : 0/4 ... 20 mA active / source Rated voltage : 24 V DC SIL : 2 Minimum ambient temperature : -20 °C Ambient temperature max. : +70 °C Area of application (zones) : 2 Gas explosion protection : II 3 (1) G Ex nA nC [ia Ga] IIC T4 Gc Dust Ignition Protection : II (1) D [Ex ia Da] HS goods number: 85363010 DE

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
YL6S/C-D-050-Y-EN-SF-A-ST-00-	225074 Case Material : Polyester glass fiber reinforced Housing color : black Material dome : polycarbonate, prismatic Rated operating voltage AC : 0 V Rated operating voltage DC: 24 V Tolerance : -10 ... 10% Rated operating current flashing light : 320 mA Rated operating current horn : 280 mA Rated operational current : 600 mA Illuminant : Xenon flash tube Lens Color : Yellow Flashlight : 5 J Flash frequency : 1 Hz Number of lamps : 1 Volume control : 18 dB (A) balance Degree of protection IP (IEC 60529) : IP66/IP67 Area of application (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex d IIC T5/T4 Gb Dust explosion protection : II 2 D Ex tb IIIC T95 °C /T110 °C Db Ambient temperature min. : -60 °C / -60 °C Ambient temperature max. : +40 °C / +55 °C Option 1 : - Mounting parts : included Cable and line entries: can be ordered as an accessory Sealing plug : 2 x dust cap For more info see : r-stahl.com Webcode YL6SA HS goods number: 85311095 DE Net Weight: 4,000KG
PLUG 8570/12-306, 16A, 1P+N+PE, 200-250V	
PLUG 8573/12-200 with color violet, 16A, 1P+N+PE,	20-25V
Cable Prysmian 2XRY (SWB) 3x2.5 0.6/1kV	
Socket SSI-213 2P+PE 16A 200-250V IP44 IEK	
8040/1180X10L07SA05	Series ConSig 8040 explosion-proof Type: 8040/1180X-10L07SA05 Rated operating voltage AC: 550 V Rated operational current: 10 A Case material: polyester resin Area of application (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb IIC T6 Gb Dust explosion protection: II 2D Ex tb IIIC T80 °C Db Ambient temperature min.: -60 °C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Max. ambient temperature: +40 °C Degree of protection (IP): IP66 Center slot: EMERGENCY STOP mushroom button red (rotary arrow) Built-in element in the middle: contact element Switching process in the middle: opener/closer Cable entry below: 1 x M25 07..... 17 mm Flanges and plates: : without flanges, without plates
6050/604-801-7B2-008850-002	Housing material: aluminum seawater resistant Housing color: Standard Protective glass material: thermally resistant Pressed glass Protective glass version: clear Protective basket: No Version: hanging installation Lamp power: 80 W Light source: LED Light color: 5000K - neutral white Color temperature: 5,000 K Color rendering: >= 80 Light distribution: medium distribution Luminaire luminous flux: 8,800 lm Luminaire efficiency: 113 lm/W Interfaces: DALI Dimensions (L x W x H): 310 x 260 x 231.5 mm Rated operating voltage AC: 220 ... 240 V Area of application (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb op is IIC T4 Dust explosion protection: II 2 D Ex tb op is IIIC T110 °C Ambient temperature min.: -40 °C Ambient temperature max.: +70 °C Protection class (IP): IP66 / IP68 (10 m) Cable and line entries: 1 x M25 x 1.5 Sealing plug: 1 x M25 x 1.5 For further information see: r-stahl.com web code 6050C
6050/5111-01061-10000-11	Manufacturer: STAHL 6050/5111-01061-10000-11 II 2 G Ex d e op is IIC t4 Gb II 2 D Ex tb IIC T100C Db IP66 PTB 11 ATEX 1045 IECEx PTB 12.0017 -40C<Ta<+55C 65W 100V - 277V
8560/51-4272	Rated operating voltage AC: 250 V Rated operating current: 6.3 A

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Characteristics: sluggish Rated breaking capacity max: 63 A Fusible Link Type :- Housing material: polyamide Area of application (zones): 1, 2 Gas explosion protection: II 2 G Ex eb mb IIC Gb Firedamp protection: I M2 Ex eb mb I Mb Protection class (IP): IP20 Ambient temperature min.: -50 °C Ambient temperature max.: +70 °C Packaging unit: 5 pieces For further information see: r-stahl.com web code 8560A
PTB 99 ATEX 2158 U 6.3A 250V	
Tranberg TEF 2460	230V Green Perimeter Light
ET-436-A-TX-BT-R3-TFT-64GB-PES	
9002/13-280-100-041 STAHL: 158818	
270158	auxiliary contactor explosion-proof Type: 8510/122-03-60D-730 Rated operating voltage: 100 ... 250 V AC/DC Auxiliary contacts: 7 (4 NO + 3 NC) Housing material: epoxy resin Application area (zones): 1, 2 Gas explosion protection: II 2 G Ex de IIC Firedamp protection: I M2 Ex de I Ambient temperature min.: -20 °C Ambient temperature max.: +60 °C Protection class (IP): IP20 For further information see: r-stahl.com Webcode 8510M
SWH5002 ZONE:1 (11,8 MT	
DN10PN500 GA STAHL K331091000-G 21/15	
SU-A 1443110 5.00M/MIN/20.00M/MIN	POWER: 0.07-0.32 KW RPM: 595-2670 RPM MOTOR
BRAKE MODULE STAHL BR2 A5785540 575V 2A	
8570/12-306-S-XX-X-XX-XXX	3-pole plug, 200 to 250 V AC, 50 / 60 Hz, 16 A
8040/114 - Y150	E-STOP JUMBO RED MAINTAINED PUSHBUTTON
8010/C1661	LED INDICATING, LAMP WHITE

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8602C3-054-B-C06	INDICATOR LAMP BEZEL AL
8602C3-001-S	ACTUATOR SERIES, 8602/3
1782580	STAHL clamp 8146/1061-3D- 1TS35+1UK5-N made of EEx e molding material
034299	8150/1-0360-0176-091-3311 H176.5 x W360 x D91 Ex e
20-E1FW-M20 Cable Gland	
20S-E1FW-M20 Cable Gland	
25S-E1FW-M25 Cable Gland	
20S16-E1FW-M20 Cable Gland	
Yodalex YL60 B N50 R	
8602A0727-1-2-R-V	
AA0189R1 card	for 8265/02-0010-C1532
AA0195R1	
9175/20-16-11s	
03 434 00 94 0	
Type: 8008 / 2-116	control switch explosion Proof Type: 8008 / 2-116 Rated operating voltage AC: 690V Rated operating current: 16 A Number of poles: 4 Housing material: epoxy resin Contact material: silver-nickel Area of use (zones): 1, 2 Gas explosion protection: II 2 G Ex db eb IIC T6 Weather protection: I M2 Ex de I Ambient temperature min. : -50 ° C Ambient temperature max. : +60 ° C Connection cross-section: 1.5 ... 4 mm2 single-wire 1.5 ... 2.5 mm2 finely stranded For further information see: r-stahl.com Webcode 8008A
Ssw7-Rk512	
119848	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
139954	
124633: 6600/521-8510-2150	
Box Eex E, T5, C Side M20x1.5 6 Pcs. / D M25h1,5 1pc. M20x1.5 2 Pcs.	
90021119903000	
Gite-Cxy8469-Bfn-617-15	
227224	
8602c3-734-B-45h-E08	
130171 8030/51-033	
857021306	MODULE
807012ar	
9001/01-280-075-101	
8214028010	COUNTER PRESET PULSE 12-24VDC
Steuergerõ;T Auswahl Sth 6102-009	
8146/1s71-3d-1ts35+32u- N 32 Terminal	
138482	
8560/51-4222 (Box= 5 Pcs.)	
8003/131-Ã173;?001	
Wcs-Is311	Interface Module 295009150
111770	
8125507388002	PANEL
8040/11	
Et-75-B-Rs422	
138520 8161/5-M25-17	
8074/1-1	
Et-8-Rs422/Rs-422-4mb	OPERATOR INTERFACE EXICOM ET8 FALCON NET

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
03 430 04 27 0	
Yl50d50arf	
9170/10-11-11s	
121700	
217981bg01	
8800007516	
115817	
857015306	PLUG
9603/31-22-10	Supply Unit
Sh3005ex	
Et-306-A-Tx-Tft	OPERATOR INTERFACE 10.4INCH LED BACKLIT 24VDC
168555	
8003/111-009	
9603/51-22-10	Transmitter-Supply Unit
8562/52-2040-100	2P MCB C10A 10KA
8602A0054-1-rt	BEZEL WITH COLORED LENS RED
8040/1180x-09xxxba05 - - By 8040/1190x-09xxxba05	
8161/5-?40-28	
9466/12-08-11	
5p32aip67	
167080: 6608/522-9611-7267	
9170/20-12-11s	
Et-306-Tx	OPERATOR INTERFACE TFT 10.4INCH LED BACKLIT 24VDC
2200372735198	
2 X Sh4012-32 4/1 L3 Oe	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8013/22-02-43	
36653005	
2152280100	
Mt-577-Sx-Tft-T-Ac-Al	
3232008280	
2150900100	
St 37-2k	
119844	
4233001180	
9185/11-35-10	
138417	
8602a0054-1-Ws	
80 130 02 21 0 - (By 8013/311-Al)	
155908	
9475/12-04-11	4 Channel Digital Output Module D-74653
1626963	
8082-01-02	
5p63aip67	
136126	
669982	
Membrane / Sticker Quot;Pushquot;	
130171	
9001/51-280-110-00c836	Intrinsic Safety Repeater Barrier
Part No: Ptb01 Atex 1129	
9165/16-11-11s	
2151010100	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
155346	
5p125aip67	
8602807177aa	
8604a0146-1-01-1	
(129095) 8013/311-Al	
2227681136653119	
8415/24-A-9 (By 8013/321-Al)	
019116	
8602 1126 Eexell Ptb 01 Atex 1129u Lcie 03atex0025u	
8703-Push Button Assembly (Obsolete Replaced By 8602)	
9475/12-04-21	4 Channel Digital Output Module PTB 99 ATEX 2220
8570/12-306	
Part No: Ptb01 Atex 1001	
9001/01-168-075-101	
130176	
226551	Accessories set Cover frame Product range: 6.14 / 2 x 18 W Mounting type: Flush mounting Material Fasteners: Sheet steel, powder coated
8602a0727 1-2-R-V	
20t3cds1rs431	
04 430 01 46 0 D6	
8146/2073	
155399	
9176/20-12-00s	
8118/131-814	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Art.Nr.321000	
124894	
214192be01	
227-762-01-00-01	DRIVE MODULE
130692	
8602A0054-1-gn	BEZEL WITH COLORED LENS GREEN
9621/04	ICS 1000 Switching Input Module
8118/121-805 / 133114	
857512112	
124632 6600/522-8010-2230 !! By 6401	
61612611210	BEACON
117590	
Hsg-Et-306-V2a-W	
Mbs Kbu 23 400	MBS Current Transformer
8003/111-015	
03 430 09 28 0 4/1	
138395	
9475/22-08-51	
227500bg01	
8161/5-M20-13	
114847	
Flkm-2k250	
168554	
8415/24-G-9 (By 8013/321-Al)	
Exlux 6008 Vb	
155344	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
9475120861c1174	MODULE
Evz30	MODULE
9182/10-51-11s	
1739084219	
9170/20-10-11	Switching Repeater Series 9170
133128	
119829	
8040/12	
Wcs2-1p770	PLC MODULE
8146/5073	
9440220111	MODULE
9480/12-08-11	TEMPERATURE INPUT MODULE 8 CHANNEL
94132121084ff	COUPLER
9460/12-08-11	Remote I/O IS1 Analog input module explosion Proof Version: Ex i inputs, 8 channels for 2-wire transmitters Area of use (zones): 1, 2, 21, 22 Ex interface zone: 0, 1, 2, 20, 21, 22 Installation in Div. NEC 500: (Class I) 1/2 & (Class II, III) 1/2 Ex cutting in div. NEC 500: (Class I) 1/2 & (Class II, III) 1/2 Max. Voltage Uo: 26,2 V. Max. Current Io: 86 mA Max. Power Po: 561 mW Ambient temperature min. : -20 ° C Ambient temperature max. : +65 ° C Gas Explosion Protection: II 2 (1) G Ex ib [ia Ga] IIC T4 Gb Dust explosion protection: II (1) D [Ex ia Da] IIIC For further information see: r-stahl.com Webcode 9460A HS Product number: 85363010 DE Net weight: 0.321 KG
108951	
9477/15-08-12	8 Channel Open Contact Digital Output Module PTB 01 ATEX 2188

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8602c3-734-B-90h-E08	
858141207	RECEPTACLE 125AMP 3POLE 480V 100HP 50/60HZ
8146/1051	
117252	
162693	
Mt 80-A	OPERATOR TERMINAL WITH MOUNTING BRACKET
138454	
6012/5114-2540-051-3111-00	Linear luminaire with LED sheet steel explosion-proof Housing material: sheet steel Disc material: safety glass Version: universal Housing Color: white, RAL 9016 Number of lamps: 1 Lamp power: 28 W Light distribution: - Luminaire luminous flux: 2,200 lm Luminaire efficiency: 79 lm / W Color temperature: 5,000 K Dimensions (L x W x H): 730 x 280 x 87 mm Rated operating voltage AC: 110.00 - 240.00 V Rated operational voltage DC: 110.00 - 250.00 V Area of use (zones): 1, 2, 21, 22 Gas explosion protection: II 2 G Ex db eb IIB T6 Gb Dust explosion protection: II 2 D Ex tb IIIC T80 ° C Db Ambient temperature min. : -40 ° C Ambient temperature max. : +55 ° C Note through wiring: max. 12 A Degree of protection (IP): IP65 Diffuser: with diffuser Through-wiring: with 5 conductors 2.5 mm2 Ballast: 6042 Address module: without Drill holes: 3 x M25 Cable and Cable entries: 2 x M25 Ø 7 - 17 mm Material cable entry: polyamide black Sealing plug: 1 x M25 x 1.5 Materia
0443003220	
8602/3	
9603/71-22-10	Supply Unit

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
9575/12-08-61	
114779 6000/521-8011-3130	
9001/01-280-100-101	
P20189007	
138406	
8040/1380x- 54co6xxxx- 01l13ba05-01l08ba05	
123291	
130899	
Et-125-Rs422	Operator Panel ET125 200020670200
Fsqc-5460	
8214/122-2-S30	COUNTER PRESET PULSE 12-24VDC
9118/11-11-10 - Obsolete (Replaced By 9118/11-11-10)	
155785	
9470/22-16-11	INPUT MODULE DIGITAL 16CHANNEL
138382	
9001/01-168-020-101 (158555)	
61612612210	BEACON
Mt-316-S-Tx	
B219733bg01	
03 430 02 43 0 D6	
9603/71-22-11	Messumformer ICS 1000 Module
8223210300	
3833000180	
8118/222	
5784660	TEMP CONTROL

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8146/.081	
138389	
8070/1-1-S	
8602c3-727-B-M01-02-E08	
127244	
9611/ 51-11-00	ICS 1000 Swithing Input Module 9611
80 130 03 21 0 - (By 8013/311-Al)	
0443047650	
3p32aip67	
8581/12-507	PLUG 5PIN 125AMP 500V 7H BLACK
9182205111s	TRANSMITTER
D40s5-23agv	
145285	
90010115839010	
8102/22-31	
Art.Nr.331021	
218116	
B227500bg01	
5785540	
A3-4333000170	
Et-416-A-Tx-73041000005	
143544 8290/3-M25	
119849	
03 430 07 28 0	
9311521100	
Et-75-B	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8602 Stop	
9182-20-51-115	
9251/02-60	Relay Repeater 9251/0.-.0
8013/321-Al	
9475120851	MODULE
115828	
8562/52-5030-060	
8070/1-1-Hh-K	
132973	
Et-436-A-Tx-R1-Tft-100gb-P	
Tex 303016-S1	
108952	
8070/1-1-Hr311	
8602a0054-1	
261206	Accessories set ceiling mounting Type: 6.12 / 5 Product range: 6.12 Use: 6014 6018 6114 6118 6414 6418 Mounting type: Flush mounting Material fixing parts: galvanized steel Surface treatment: galvanized
143556 8290/3-M16	
2 X Sh4012-32 4/1 L3	
Sle1	
115738	
8602a0726-1-3-Rr-V	
28142112076fc78v	
8040/2380z- 54c06xxxx- 31e?F..	
Push Button Control Box 1739084219	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
155463	
8579-31-506	
B/2 F11/101.211 650/2550 Kw 0.06/0.025 Amper 0.7/0.9	
119173	
8163/1-20-E1fw-M20	
Art. Nr. 150495 , Type 8570/12-506	
366501392007470700	
8579/12-407	PLUG 4PIN 63AMP 480/500VAC 7H BLACK
155476	
131303	
8003/111-010	
9475/12-08-61	INPUT MODULE DIGITAL 16CHANNEL
8146/5-602-5002	
Hf-7200	
23279801	
9170/20-12-21	Switching Repeater Series 9170
136678 8146/5041	
124910	
04 430 01 47 0	
9194/50-01	
8560/51-4071	SAP 149138 Description 8560 / 51-4071 Sich.M0,125A 250V 80A 5 ST Rated operating voltage AC: 250V Rated operating voltage DC: 60 V Rated operating current: 0.125 A. Characteristic: medium-term Short-circuit protection max. : 80A Housing material: polyamide Area of application (zones): 1, 2 Gas explosion protection: II 2 G Ex e mb II T ..

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Weather protection: I M2 Ex e mb I Degree of protection (IP): IP20 Ambient temperature min. : -50 ° C Ambient temperature max. : +70 ° C Packing unit: 5 ST For further information see: r-stahl.com Webcode 8560A
Et-208	
80 130 01 21 0 - (By 8013/311-Al)	
138383	
8415/24-R-9 (By 8013/321-Al)	
155457	
124643 6600/542-8010-2230	
8602c3-726-B-M01-02-E08	
160321 / 9170/10-12-21s	
80401180x35c06ba45	
Bp7230cs	CARBON STEEL BACK PANELS
858141407	RECEPTACLE 125AMP 3POLE 480V 100HP 50/60HZ
8161/5-?50-35	
Press-Guns For Svm280 Cartridge System	
8161/5-?25-17	
5764660	TEMPERATURE CONTROL
8003-111-001	
114779	
8602A0054-1-bl	BEZEL WITH COLORED LENS BLUE
8602808167aabg732	
8602a0015-1	
Sk-Drag-Gbic-Sx	
03 434 01 04 0 L3	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8146/1s71	
Yl6s-C-D-050-R-En-Rn-A-St-Dl-00-00	
80400019	
03 432 01 52 0	
214176 Bg01	
8064/21-330- 30-163	
Svm 280	
Et-75	
Et-556-A	
8570/11-306	
P20062484	
9440-15-01-11	
115819	
01644e0g 8003 Ptb 01 Atex 1129u	
9001/00-280-100-101	
106074	
9160/13-11-11s	
212338be01	
3432200580	
136703	
C2016	VERTICAL DISCONNECT HANDLE W PRE-MOUNTED CONTROL
9170/10-12-21s	
9001/01-280-100-00	24VDC Safety Barrier 250V
93525310k02	
Et-8-Rs422/Rs-422	OPERATOR INTERFACE EXICOM ET8 FALCON NET
120431 / 6147/2-2	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
138394	
9002/22-032-300-111	
P23279801	
8581/11-507	SWITCH SOCKET 125AMP 500V 50/60HZ 5PIN
109133	
9164/13-22-08	
155512	
21 3334 0090 0	
150579	
153029 (Type 8579/12-406)	
9165/16-11-10s	
90010316800010	
N242010hwt	N SERIES ENCLOSURE, STAINLESS STEEL HINGED, LATCHED DOWN COVER
C-Lux 6108 Vb	
8570802760	
2141920100	
115806	
9440/15-01-11	CPU AND POWER MODULE RS485 5.2AMP 250V
9460/12-08-11 8 Ai-Module	
8102/21-31	
Et-316-A-Fx-50001000001-000000000000	
8125/5051-2	
857115506	PLUG
Lcie 03 Atex 6308 Switch	
155479	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Vb-300	
Mt-316-A-Tx-62031001003	
01 430 00 53 0	
271810010034309	
2129560100	
120535	
8602930840	
9001/01-083-442-00	6VDC Safety Barrier 250V
8040/1180x-10l07ba08.	
8800007546	
9465/12-08-11	
8013/22-02-93 By 129095 8013/311-Al	
5785260	
106073	
145280	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.