

Standard Pump

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Standard Pump Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Standard Pump T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
1608	
833	
P-280P-2	
SP-ENC-2-V	
SP-PP-HH	
SP-PVDF-47	
SP-SS-39	
st 1.8-85	
SP-280P-2	Electric motor 230-240V, 50-60Hz, 825W IP44 (TEFC) LVR, with undervoltage release, without speed control with motor cable and plug With low voltage release Without speed control With motor cable and plug
SP-280P-2	Electric Motor 230-240V, 50-60HZ, 825W IP44 LVR With low voltage release Without speed control With motor cable and

Standard Pump

YURSAT yedek par¼a tedariki yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distrib¼t¼r¼ yada temsilcisi deĐildir.

	plug
SP-7600-47	Pump tube 1200 mm - 47" Shaft Stainless Steel, Hose connection 1 1/4" for 1" hose, max. Temp. 80°C, AtEx 40°C Pump mechanism stainless steel 1200 mm Shaft stainless steel, connection 1 1/4" for hose1"
SP-280P-2-V	electric motor 230-240V, 50-60Hz, 825W IP44 USP, with undervoltage release, with speed control, with motor cable with plug Electric Motor 230-240V, 50-60HZ, 825W IP44 With low voltage release With speed control With motor cable and plug HS code 8413.406040
SP-280P-2-V	Electric Motor 230-240V, 50-60HZ, 825W IP44 With low voltage release With speed control With motor cable and plug
SP-PVDF-39	Pump tube PVDF 1000 mm - 39" Shaft Hastelloy, Hose connection 1 1/4" for 1" hose, max. Temp. 80°C,
Electric barrel pump SP-280P-2-PP-39,	with undervoltage release, without speed control
Pump tube polypropylene SP-PP-39	Length 39", 1000 mm,
Centrifugal pump wear rings	SDS 350-350 Q:1765 M3/H H:29M 200KW 1450RPM
SP-7600-39	Pumpwerk High Volume, Edelstahl 316, 1000mm - 39", Gewicht 5,0 kg Dual Use
SP-B2	compressed air motor Successor to SP-A2, version without trigger lock Must not be used for flammable or explosive media and corresponding zones.
Sp-280p-2 Drum-Pump-Motor, Open Drip Proof (Ip44), 220-240v/1/50-60hz, 825 Watts, Lvr	
Sp-Pp-39	
Sp-Pvdf-39	
Sp-800sr-751p-39	
Snm 32-125 Snã 11114	
Sp-Enc-2-V Drum-Pump-Motor, 230-240v/50-60hz, Tefc (Ip54), 825 Watts, Variable Speed	
1608 Impeller For Pp-Pipeteil	
Sp-Pp-39 Die Pumpe Drum-Pump, Polypropylene, 39 (1000 Mm), Hastelloy-Shaft, High Volume Version	
Sp-Enc-2-V Motor (Ip54) With Variable Speed	
Sp-Pvdf-47 Pump Tube	

Type: Snm 32-125
Lh-9032
Sp-Ss-39 Pumpe (1000mm, Aisi316)
Sp-Ss-39 Pumpe Sp-Ss-39 (1000mm, Aisi316)
835
Sp-280p-2 Motor Ip44, 825vt, 220v
835 Installation
9034m-A
P-280p-2 Standard Pump Motor, Open Drip Proof, Ip44220-240v, 1-Phase, 50-60hz, 825 Wattssingle Speed
Sp-Pvdf-47 Pumpe (1200mm, Pvdf)
Sp-800sr
Sp-Pp-39 Sp-Pp-39 (Length 1000mm)
833 Tri-Clamp
Sp-280p-2
Sp-Ss-39 Pumpe (Length 1000mm)
Dd700-181-39-T
Sp-Pp-39 Drum-Pump, Polypropylene, 39" (1000 Mm), Hastelloy-Shaft, High Volume Version
Sp-280p-2 Motor Sp-280p-2 (Ip44, 825 0,825 Kw 220v)
Sp-800sr-751p-39 Pumpwerk Edelstahl Ss316l, 3a, 39" (1000 Mm), Stator Ptfе, 9,0 Kg