Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Stiko

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Stiko Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Stiko Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
PT100 - 0/450 degrees	- plunge length 30cm-thickness 9mm (0550) SAVI Contact thermometers. PT100 THERMIBEL A temperature and humidity measuring device is required, there will be output information for both humidity and temperature (4-20mA-10V..)
Contact thermometer	0-100 degrees 100 Ø 100 'C x 300 mm.x Ø 12 M11 Silicone F (0547) SAVI Contact thermometers. PT100 THERMIBEL A temperature and humidity measuring device is required, there will be output information for both humidity and temperature (4-20mA-10V..)
Contact thermometer	0-100 degrees 100 Ø 100 'C x 300 mm x Ø 12 M11 silicone f (0546) SAVI Contact thermometers. PT100 THERMIBEL A temperature and humidity measuring device is required, there will be output information for both humidity and temperature (4-20mA-10V..)
2018-60249	
RPX280X280XT-DUPLEX-PT, Double pen	Case : 280 x 280mm, with ø223mm (9") Chart

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Case style : Transportable Case Material : Case + case-related SS parts: AISI316 Window : Plexiglass Pressure range : 0 - 160 bar Temperature range : -20 / +60 °C Accuracy : Class 1,0% Logo on door : Neutral Logo on front panel : Neutral Capillary length : 1x 3.000 mm Armour material : Stainless steel 304 Stem diameter : ø 12 mm Stem Length : 1x 100 mm Ls= Stem material : Stainless steel 321 Pressure connection size : 1/4 NPT Connection location : Lower back connection Temperature connection type : A, plain stem Wetted parts : Stainless steel 316 Mechanical clock, single speed : 24 hours Charts : Comes with 100 charts per recorder Pens : Comes with 2 pens per measuring system per recorder Specifications : Blue and red pens instead of standard black pen Chart number : 123-333-74
Calibration certificate	
Txr100xt-A-K	
Pbx160xb	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.