

Straub

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Straub Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Straub T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|---|----------|
| Eco Grip Ø88.9 - Stainless Steel A4 | |
| 100695 | |
| 103519 | |
| 103537 | |
| 1105 | |
| 1110 | |
| 1112 | |
| 13146 | |
| 481-525-300 | |
| G20206 | |
| G20351 | |
| G20450 | |

| | |
|---|---|
| G20550 | |
| G20551 | |
| G20558 | |
| G20601 | |
| G20650 | |
| G20900 | |
| G21051 | |
| STRLE48 | |
| WGR560 | Item No.: G21107 STRAUB-GRIP FF 133.0 mm NBR/ES W5 Clamping range 131.7 - 134.3 Housing 1.4404 or equivalent Screws A4-80 Bolt 1.4404 or equivalent Sealing sleeve NBR Operating pressure (Ind.) 21.00 Temperature -20°C - +80°C |
| article_code=6829/0612 | name plate=6620M0016 NORMA Grip-E-FP-W5-NBR ø133.0 |
| article_code=6829/0612 | name plate=6620M0018 NORMA Grip-E-FP-W5-NBR ø133.0 |
| OPEN-FLEX 1 □ 114.3mm EPDM/ES PN20 W5 | 35650 Sealing Sleeve :EPDM Clamping Range :112,5. - 116.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :20 |
| OPEN-FLEX 1 □ 76.1mm EPDM/ES PN25 W5 | 35250 Sealing Sleeve :EPDM Clamping Range : 74.5-77.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25 |
| OPEN-FLEX 1 □ 88.9mm EPDM/ES PN25 W5 | 35350 Sealing Sleeve :EPDM Clamping Range :87.5-90.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25 |
| OPEN-FLEX 1 □ 48.3mm EPDM/ES PN25 W5 | 35000 Sealing Sleeve :EPDM Clamping Range :47.0 - 49.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25 |
| OPEN-FLEX 1 □ 60.3mm EPDM/ES PN25 W5 | 35150 Sealing Sleeve :EPDM Clamping Range :59.0-63.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25 |
| GRIP 33.7 mm EPDM/ES W5 | ALTERNATIVE (Bu boyuttaki OpenFlex modeli üretimden kaldırılmıştır) G20100 Sealing Sleeve :EPDM Clamping Range :33.2-34.2 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :39 |
| 30600 | 108.0mm EPDM/W5 /PN20 Clamping range 106.5-110.0 Pressure ind. 20 EPDM Casing 1.4404 Bars A4-80 |
| 30800 | 133.0mm EPDM/W5 / PN16 Clamping range 131.0-135 Pressure ind. 16 Sealing sleeve : EPDM Casing 1.4404 Bars A4-80 |
| 3" SCH40 304L | |

| | |
|--|--|
| Grip-L 33.7mm NBR/W5 | clamping range 33.2-34.2 pressure :39 sealing sleeve NBR Casing 1.4404 Bars A-4-80 Bolts1.4404 |
| 1017 Marquardt 648 1264.3501 | |
| 36050 | STRAUP-OPEN-FLEX 1Ø168,3mm EPDM/W5 I PN16 |
| 35350 | STRAUP-OPEN-FLEX 1Ø 89.9 mm EPDM/W5 I PN25 |
| STR30250 | 76.1 mm Pipe Outer Diameter, EPDM Gasket, SS Bolt |
| 270200490 | Flange C 48.3 DIN 2633 1.4571 PN 16 |
| WGR560- various other things | various other things Article number: 35250 STRAUB Open-Flex-1 W5 DN 65 / 76.1 mm PN 25 EPDM / ES |
| Grip FF 76.1 EPDM/W2 | with steel strip bearing, VDS clamping range mm 75.3-76.9 Pressure 56 Sealing sleeve EPDM Casing 1.4404 bars 1,722 Bolts 1.0737 temperature -30 to 100 degrees |
| 35650 | |
| 406.4 EPDM/W5 | with steel band layer with drinking water approval Clamping range mm 402.5-410.5 Pressure 7 Sealing sleeve: EPDM NSF Casting 1.4162 bars A4-80 Temperature -20 +100 degrees |
| G20300 | STRAUBGRIP 48.3 EPDM/W5 with steel band insert Customs tariff number: 73072900 Country of origin: CH Clamping Range mm: 47.8 48.8 Operating pressure (Ind.) / Pressure (Ind.): 28 Sealing sleeve: EPDM Housing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| SPI XXSC4 | Pipe Coupling - DN50-450 |
| G20300 | STRAUBGRIP Ø 48.3 EPDM/W5 PN28 with stainless steel band insert Clamping range (mm): 47.8-48.8 Operating pressure (Ind.) / Pressure (Ind.): 28 Sealing sleeve: EPDM Casing: 1.4404 or equivalent |
| G20450 | STRAUBGRIP Ø 60.3 EPDM/W5 PN23 with stainless steel band insert Clamping range (mm): 59.7 - 60.9 Operating pressure (Ind.) / Pressure (Ind.): 23 Sealing sleeve: EPDM Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| G20650 | STRAUBGRIP Ø 88.9 EPDM/W5 PN26 with stainless steel band insert Clamping range (mm): 88.0-89.8 Operating pressure (Ind.) / Pressure (Ind.): 26 Sealing sleeve: EPDM Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| G21350 | STRAUBGRIP Ø 168.3 EPDM/W5 PN16 with stainless steel band insert Clamping range (mm): 166.6-170.0 Operating pressure (Ind.) / Pressure (Ind.): 16 Sealing sleeve: EPDM Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| | STRAUBGRIP Ø 219.1 EPDM/W5 PN16 with stainless steel band insert, approved for drinking water use Clamping range |

| | |
|--|--|
| 21412 | (mm): 216.9 - 221.3 Operating pressure (Ind.) / Pressure (Ind.): 16 Sealing sleeve: EPDM NSF Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| 25199 | STRAUBGRIP Ø 273.0 EPDM/W5 PN7 with stainless steel band insert, approved for drinking water use Clamping range (mm): 270.5 - 275.5 Operating pressure (Ind.) / Pressure (Ind.): 7 Sealing sleeve: EPDM NSF Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| 25310 | STRAUBGRIP Ø 323.9 EPDM/W5 PN5 with stainless steel band insert, approved for drinking water use Clamping range (mm): 320.5 - 327.0 Operating pressure (Ind.) / Pressure (Ind.): 5 Sealing sleeve: EPDM NSF Casing: 1.4404 or equivalent Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| 102460 | STRAUBGRIP Ø 355.6 EPDM/W5 PN10 with stainless steel band insert, approved for drinking water use Clamping range (mm): 352.0 - 359.0 Operating pressure (Ind.) / Pressure (Ind.): 10 Sealing sleeve: EPDM NSF Casing: 1.4162 Screws / Bars: A480 Bolts: 1.4404 or equivalent Temperature: 20°C to +100°C |
| Grip-L 166,6 - 170,0mm | |
| Grip-L 166,6-170,0mm | |
| 491-625-300 | |
| 41681663 | |
| Grip W5 114,3mm | NBR PN bar 22 |
| 42218654 | |
| Grip-L 47,8 - 48,8mm | |
| 41806532 | |
| S30651/1-L-114,3 | |
| 381-215-200 | |
| S30251/1-L-76,1 | |
| 42216950 | |
| Grip-L 138,3-141,1mm | |
| Grip-L 33,2 - 34,2mm | |
| 392-420-400 | |
| 381-108-200 | |
| Grip-L 59,7 - 60,9mm | |

| | |
|--|---------------|
| 500246716 | |
| Grip W5 168,3mm | NBR PN Bar 16 |
| 491-525-300 | |
| Grip-L 113,2-115,4mm | |
| 500246715 | |
| Grip-L 113,2 - 115,4mm | |
| Rep-Flex Kupplung Reparaturd525mm (525-535) L=300mm Nbr/Es | |
| Grip-L 26,4 - 27,4mm | |
| Grip-L 273,0mm | |
| 41625338 | |
| Grip-L 138,3 - 141,1mm | |
| Grip-L 216,9 - 221,3mm | |
| Grip-L 59,7-60,9mm | |
| Grip-L 88,0 - 89,8mm | |
| Grip-L 33,2-34,2mm | |
| 381-269-300 | |
| Grip-L 75,3-76,9mm | |
| 381-159-200 | |
| Grip-L 41,9-42,9mm | |
| Grip-L 48.3 Kupplung | |
| S30151/1-L-60,3 | |