

Stuvex

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Stuvex Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Stuvex Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
503-1050-003	
503-1500-000	
651-1100-040	
651-1100-075	
651-1100-080	
663-0410-020	
SG/E-TES01-V2/IP	Earth Monitoring System for Trucks Brand: Stuvex * Type: Capacitive + Resistive * Material: Body in AISI304 stainless steel * Dimensions: 200x300x155mm * Assembly: wall mounting ... cable glands: 3x M20 incl. (1D/2G) ... equipped with an earth connection * Voltage supply: 110-240VAC +10%/-15%, 50-60Hz 24VDC, +/-20% * Output contacts: potential-free, NO, 1A @ 250 VAC / 30 VDC potential free, SPDT, 6A @ 250 VAC / 30 VDC * Indication: ... Power supply: 24 VDC, max. 100 mA - Grounding OK: 1x green Grounding NOT OK: 1x red * Equipped with a key switch - Truck detection on/off" * Protection class: IP66 * Temperature: -30°C to +54°C * Humidity: max. 95% at 20°C, non-condensing * ATEX ITS18ATEX103783

Ürün	Açıklama
	EX II 2 (1) D Ex tb [ia Da] IIIC T135°C Db * IECEx ITS 18.0042
CR1/65V15	Cable reel aluminium Cable: : H05VV-F 2x1.5 + 1.5mm ² , 15M Length 15 meters Connection length: 2 meters Automatic blocking mechanism Cable line Seal kit: IP65 Housing: aluminum Pivoting attachment Weight: 10kg Assembled including connector (F). Cable: H05RN-F 2x1.5 + 1.5mm ² - Length 15 meters - Connection length 1.7 meter Assembled including connector (F). Automatic blocking mechanism (default setting: braked) Cable management system with rollers Seal kit: IP65 Behuizing: aluminum Ground connection housing Pivoting attachment (in stainless steel) Weight: 10kg Mark: CE0344 Ex II 2GD ISSeP 04 ATEX 084X ATEX ITS18ATEX103783 ITS 18.0042
SG/B-CMS1-SCM	Clamp Medium StuvEx, incl. M connector In stainless steel 1.4401 (AISI 316) Size: 210mm Opening: 3±mm Temperature range: -40°C to +80°C Weight: 0.6kg Including integrated strain relief Suitable for use in ...of zones 20, 21, 22 ...of zones 0, 1, 2 Cable ...Type: H07RN-F 2x1.5 + 1.5 mm ² ...Length: 0.2 m ...water and oil resistant Connector, M ...PA6.6, blue

Ürün	Açıklama
651-1100-080 Fc Ar-01 Alarm Relay For Fcu Rp01	
651-1100-075 Fc Rp-01 Firing Card Rp - Squib	
503-1050-003 Cm1 - Erdungszange Ss	
503-1500-000 Set Of Plugs (M+f)	
503-3250-010	
651-1100-040 Em-01 Earth Monitor	