



Sycon

Garanti: 12 ay
 Bu ürünne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Sycon Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sycon Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
SYCON 2602	SYCON 2602 analyzer in a housing, 110/230 V. 30-210160 Compact and fully automatic online analyzer for limit value monitoring of the Total hardness: - Easy commissioning with the configuration assistant - low indicator consumption (5,000 analyzes per bottle) - tool-free maintenance and easy cleaning - high measuring accuracy through self-calibration - Monitoring of a limit value - 2 relay outputs for limit value and device error - 1 input contact - SD card for storage of measured values - Software updates via SD card - no condensation on the optics - compact design 280x250x135 mm - multicolored, multilingual graphic display - Supply voltage 85-264 VAC - in the housing
SYCON 2802	Analyzer, on wall bracket, 110/230 V. Item no .: 30-010164 Reliable, accurate and fully automatic online analyzer for measuring the Total hardness in the range 0.02-30 ° dH (0.35-534 ppm CaCO ₃): - Easy commissioning with the configuration assistant - low indicator consumption - tool-free maintenance and easy cleaning - high measuring accuracy through self-calibration - Monitoring of 2 limit values - Indicator level monitoring - 4 programmable relay outputs for limit values, pre-cooler, flushing valves, pumps,

Errors, lack of indicators, rear derailleurs - 1 current interface 0 / 4-20 mA - 2 digital inputs for water meters, turbines, flow monitors, external controls - SD card for storage of measured values - Software updates via SD card - no condensation on the optics - multicolored, multilingual graphic display - compact design 280x250x135 mm - Supply voltage 85-264 VAC - on wall bracket

[33-099005](#)

Housing for SYCON series (with wall mounting set)

[Profibus-Dp-Configurator](#)

[Generator Tachometer 6v D.C.Per 1000 R.P.M. Open Ckt. 50 Ma Max](#)

[Shaft Flexible Drive-2.62 In. Long](#)