

## Sycon

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Sycon** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Sycon Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">SYCON 2602</a>	SYCON 2602 analyzer in a housing, 110/230 V. 30-210160 Compact and fully automatic online analyzer for limit value monitoring of the Total hardness: - Easy commissioning with the configuration assistant - low indicator consumption (5,000 analyzes per bottle) - tool-free maintenance and easy cleaning - high measuring accuracy through self-calibration - Monitoring of a limit value - 2 relay outputs for limit value and device error - 1 input contact - SD card for storage of measured values - Software updates via SD card - no condensation on the optics - compact design 280x250x135 mm - multicolored, multilingual graphic display - Supply voltage 85-264 VAC - in the housing
<a href="#">30-010164</a>	SYCON 2802 analyzer on wall bracket, 230 V Reliable, accurate and fully automatic online analyzer for measuring Total hardness in the range 0.02-30 °dH (0.35-534 ppm CaCO3): - easy commissioning through configuration assistant - low indicator consumption - tool-free maintenance and easy cleaning - high measurement accuracy through self-calibration - Monitoring of 2 limit values - Indicator level monitoring - 4 programmable relay outputs for limit values, pre-coolers, flush valves, pumps, Error, indicator deficiency,

	switching mechanisms - 1 current interface 0/4-20 mA - Protocol Modbus RTU RS-485 - 2 digital inputs for water meters, turbines, flow monitors, external controls - SD card for storing measured values - Software updates via SD card - no condensation on the optics - multi-colored, multilingual graphic display - compact design 280x250x135 mm - Supply voltage 85-264 VAC - on wall mount
<a href="#">33-099005</a>	Housing for SYCON series (with wall mounting set)
<a href="#">32-084165</a>	Indicator H25 - 0.5 (500ml) To determine residual/total hardness Sycon 2501/2502/2602: Limit value 0.5 °dH, 0.89 °f, 0.08915 mmol/l Sycon 2702/2800/2802: Measuring range 0.15-1.5 °dH, 0.27-2.67 °f, 0.027-0.26 mmol/l
<a href="#">32-484165</a>	Value pack indicator H25 - 0.5 (4 x 500 ml containers) To determine residual/total hardness Sycon 2501/2502/2602: Limit value 0.5 °dH, 0.89 °f, 0.08915 mmol/l Sycon 2702/2800/2802: Measuring range 0.15-1.5 °dH, 0.27-2.67 °f, 0.027-0.26 mmol/l
<a href="#">Profibus-Dp-Configurator</a>	
<a href="#">Generator Tachometer 6v D.C.Per 1000 R.P.M. Open Ckt. 50 Ma Max</a>	
<a href="#">Shaft Flexible Drive-2.62 In. Long</a>	