

Sylvac

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sylvac Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Sylvac T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
2161-1002	Depth gauge 300 mm S_Depth Pro ** Display can be rotated 270 ¼, resolution 0.01 mm Data output power - RS232 / USB Function = (REFI / REFII) / Preset
1901-1014	
2101-1213	
2111-1015	
2111-1020	
2401-2101	
2401-2163	
2401-2165	
2402-0005	
2402-1001	
2502-1001	

2601-1003	
2801-1031 + 2802-5030	
2801-2226	
803.0304	
805.6501	
805.6661	
810.1502	
811.1410	
811.1425	
812.1601	
903.0300	
905.2206	
905.4321 S234	
905.4511	
905.4521	
910.1502	
910.9502 (S CAL PRO 150mm)	
953.2510	
955.6003	
DIGITAL S MIKE PRO 2601-1003	
IP67-910.1502	
S233 DIGITAL-KLEIN-MESSUHR DR. 44MM 12.5MM, * AUFLOSUNG 0.001, GUMMIBALG	
S233 DIGITAL-KLEIN-MESSUHR DR. 44MM 12.5MM, AUFLOSUNG 0.001	
S233, 905.4511.10	
S233, 905.4140	DIGITAL DIAL INDICATOR (VERTICAL) 0.01-5 MM
2801-2035	Inside micrometer 35-50 mm XT3H BT Bluetooth®, with pistol grip including setting ring, test report and operating instructions in a wooden case. Water and coolant resistant, protection class IP67 according to IEC 60529. Data transfer via Bluetooth® Smart Proximity/USB/RS232
	Inside micrometer 35-50 mm XTD3 BT Bluetooth®, with

2801-1035	ratchet feel including setting ring, test report and operating instructions in a wooden case. Water and coolant resistant, protection class IP67 according to IEC 60529. Data transfer via Bluetooth® Smart Proximity/USB/RS232
2461-1130	Ultra-light caliper UL4 3000 mm** for external and internal measurements Protection class IP67, weight 3.3 kg Measuring range 3000 mm, error limit 200 µm Functions: Zero setting, Preset (max 9999.99), mm/inch Min/Max/Delta, Display of tolerance limits, Configure via PC. Data output: S_Connect: Proximity on USB / RS232 Built-in Bluetooth® Smart, for use with PC USB dongle 5031-3017 for connecting up to 8 Sylvac Bluetooth® devices Measuring instruments Length of measuring jaws: 200 mm
8609-1060	Calibration of calipers Measuring range 0-3000 mm VDI/VDE/DGQ 2618 Sheet 9.1
8989-0220	Inspection stickers with next Calibration appointment per measuring instrument
8989-0120	Paper certificate per certificate
908.2182 Dr. 0,5mm, Hã246;He 3mm (Ps.16.450.320)	
900.1025 P 25	
2401-2020, 910 1522	
S233 Digital-Klein-Messuhr Dr. 44mm 12.5mm, * Auflosung 0.001, Gummibalg	
2101-1250 S Dial Work Basic S/25.0/0.001 **	
2401-2225 S-Cal Pro New	
805.5301	
150 Mm Sylvac Marka Kalibrasyonlu Kumpas	
905-4511-99	
2401-2020	
2601-1006 Digital S Mike Pro	
Ref.Nr.: 926.6521 Datenkabel Opto.At Duplex.2m	
S Cal Evo Bluetooth 150mm Mit Rundem Tiefenmass Å216; 1,5mm	
905.2204	
Art.Nr. 2401-1120 Ref.Nr.: 910.0522	
P10I.900.1014	

Art.Nr. 2401-2016 Ref.Nr.: 910.1507
Art. Nr. 2401-2030 Ref.Nr.: 910.1532
Art.Nr. 2401-1111 Ref.Nr.: 910.0507
905.4140
900.1010
2401-2015
2101-1210 S_Dial Advanced S/25/0.001 **
Sylvac-9082181-Aufnahme-Stift-15mm-F3;R-Ps151617-Istanbul-Turkiye
Art.Nr. 2401-1131 Ref.Nr.: 910.0532
Xtreme Xtd
2401-2015, 910 1502
2401-2030, 910 1532
S233 Digital-Klein-Messuhr Dr. 44mm 12.5mm, Auflosung 0.001
Art.Nr. 2401-1110 Ref.Nr.: 910.0502.10
Art.Nr. 2401-2015. Ref.Nr.: 910.1502
2401-1120
804.1300
901.5002
Art.Nr. 2401-2020 Ref.Nr.: 910.1522
2461-1050 911.1420
2401-2225
Digital S Mike Pro 2601-1003
Ip67
800 Luxury Digital Calipers
2111-1010
901.2003
905.4321 2121-1010
150 Mm Sylvac Marka Kalibrasyonlu Derinlik Kumpasi

[2401-2016, 910 1507](#)

[S233 Digital-Klein-Messuhr Dr.44mm
12.5mm, ** Auflosung 0.01](#)

[820.2450](#)

[900.1016](#)

[901.2004](#)

[Xtreme Xth](#)

[905.4121](#)