



Tapeswitch

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tapeswitch Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Tapeswitch T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|------------------------------------|--|
| PRSU/4 | PRSU / 4 evaluation device Supply voltage: 24V AC / DC Mounting: DIN mounting on top hat rail Contacts: 3 NO contacts, 1 NC contact Reset: aut. / Ext. Temperature range: -25 ° C to + 55 ° C Safety category: EN ISO 13849-1 PL "d" Customs tariff number: 85364190 country of origin: Germany Net weight: 0.2kg |
| 121BP/0100/2 | |
| 121BP/0250/1 | |
| CKP/C1/0175/0120/1 | |
| CKP/S1/0600/0500/4 | |
| GS140/S/4/15/LED | |
| M12/5/20 | |
| M12/8/20 | |
| PSSZ/4 | |

| | |
|---|---|
| TS26C/0805/3 | |
| TS26C/1270/1 | |
| TS26C/5000/7 | |
| TS28 | |
| TS-46-AL FC - VAL0044325 | |
| PRSU/4 | PRSU/4 evaluation device Supply voltage: 24V AC/DC Mounting: DIN mounting on top-hat rail Contact equipment: 3 NO contacts, 1 NC contact Reset: aut. / ext. Temperature range: -25°C to +55°C Safety category: EN ISO 13849-1 PL"d" Customs tariff number: 85364190 |
| Ts28/1060/4 Ts28/1060/F/A/B/Fs/Ee/0500/ 0500/N | |
| Ts3/0558/1 | |
| Ts26c/0750/9 | |
| Ts-46d - Val0044338 | |
| B1230 | SAFETY UNIT |
| 800-234-8273 | |
| B3230 | LIGHT CURTAIN |
| Ckps1sesrs100009003000 | |
| Ts26c/0805/3 | |
| Pssu/2. | |
| Ts6/2235/1 | TS6/2235/F/A/R/FS/EE/5000/ 2000/N/AC Safety Edge Type: TS6 Length: 2,235mm Profile rail: aluminum, flat Profile color: red Material: EPDM / PP Band switch: 107BPE IP67 Wiring: Fail-Safe (4-wire) Cable outlet: two-sided (EE) Cable length: 1 x 5,000mm, 1 x 2,000mm Cable type: Ölflex Robust 210; 2 x 0.5mm² Connection: make contact max. 30V @ 1A loadable End cap version: without Special feature: At the beginning and end has the safety edge is not active Range of max. 50mm. Drawing: ---- Tariff No .: 85365019 |
| B0830r | LIGHT CURTAIN RECEIVER 808MM 18MS 24VDC |
| 0921m | LIGHT CURTAIN |
| B0830r0905 | B SERIES LIGHTCURRENT |
| 0930 | LIGHT CURTAIN |
| Ts-26p | |
| 0906 | LIGHT CURTAIN |
| Ts26/Lca/0620/4w | |

| | |
|---|---|
| E3049-119-004 | |
| B/S/1200/30/15/Cb | LIGHT CURTAIN RECEIVER 12V 24VDC |
| Prsu/2 | |
| Ts26c/1700/1 | |
| Ts26c/0750/F/A/B/Fs/Oe/2000/ 2000/N | |
| Pssu/2 | |
| Prsu/4 | |
| B830 | RECTIFIER |
| Ts26/Lca/1000/4w | |
| 121- Val0008760 | |
| Ckp/S1/Se/Srs/1600/1100/3000 | |
| 0904 | LIGHT CURTAIN 608MM 30MM 24VDC |
| Ts6/860 | |
| B0630e | LIGHT CURTAIN EMITTER |
| Sp-1324-1 | |
| Ts-46-AI Fc ? Val0044325 | |
| B0630r | LIGHT CURTAIN RECEIVER |
| Bs0330r | LIGHT CURTAIN RECEIVER 0.5-15M RANGE 24VDC |
| Sensing Edge Ts-26p 750 Mm | |
| Ts-26p 750 Mm In Length | |
| 121bp/0270/1 | |
| 920022 | |
| B/S/0800/70/15/Cb | LIGHT CURTAIN |
| 121-Bp | CABLE LENGHT 8m 8m TO OTHER END+LENGHT OF RİBBON SWITCH |
| Mes0628 | LIGHT CURTAIN RANGE .3-6M CAP 28MM P.HEIGHT 630MM |
| Ckp/S1/2000/1200/7 | |
| Sab Tx 116/Sd Range 6m | |
| Sp-3291-1 | |