

Tapflo

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tapflo Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Tapflo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
16	
225.34	
225.36	
25	
27	
30	
6-009-15-1	
6-020-13	
6-020-15-1	
6-020-27	
6-020-61	
6-050-15	

6-050-15-1	Membrane, PTFE
6-050-15-3	
61	
6-100-23-3	
6-200-15	
6-200-16	
6-200-19	
6-200-202/A	
6-200-212	
6-200-22-22	
6-200-222-22	
6-200-23	
6-400-15	
6-400-15-1	
6-400-30	
6-400-36	
6-400-47	
6-400-61	
6-420-18	
Å146901	
Å164401	
ALH-1001620	
CTI EG 3F-75	
CTIAA-03	
DTX70AT	
for T100-PEE	
for T50 PEE	
For TR20 TTT	
grub screw for MN010-2 AISI	
HG120404IA	

MN010-2	
rubber sleeve for MN010-2 AISI	
T100 PTT	
T100-PEE	
T400TTT	
T50PEE	
T50TT	
TX 25 ATT (T 25)	
TX 420 AEE	
TX 70 ATT	
TX200 PEE	
TX25ATT	
TX420ANN	
TX70ATT	
T50PTT-7PV	Tapflo® compressed air diaphragm pump PET control valve
6-050-15-1	Membrane, PTFE
6-050-15-1 SPARE DIAPHRAGM TX70 ATT PUMP	
6-070-18 RİNG SET	
6-050-18-172	O-ring with seal, set FEP/FKM from serial no. 1106 XXXX
TX25XTT-1S	Tapflo® pneumatic diaphragm pump type TX25XTT-1S ATEX certified, housing: aluminum PTFE coated, Connections: stainless steel Technical description: Max. flow rate 26 l/min (with water) Max. delivery pressure 8 bar at 8 bar compressed air Suction head dry / filled 2 mWS / 8 mWS Max. solid size 3 mm Max. temperature range -20°C...+110°C Center block aluminum (not in product contact) Product-contacting housing parts: aluminum with PTFE coating Valve seats stainless steel AISI 316L PTFE membranes PTFE valve balls Suction / pressure connection G 1/2" internal thread (DN 15) Seals Klinger/NBR Control valve brass, NBR Weight 2 kg ATEX certification II 2G Ex h IIC T6...T4 Gb; II 2D Ex h IIIC T60° Air consumption see delivery curve
3000040344	Hygienic Diaphragm Pump
	Tapflo® Air-Operated Diaphragm Pump Type T225STT Technical description: Maximum flow rate 330 l/min (with water) Maximum delivery pressure 8 bar at 8 bar compressed air Suction height dry / filled 3.4 mWC / 9 mWC Max. solid particle size 10 mm Maximum temperature range -20°C to

T225 STT	+110°C, briefly up to 125°C (CIP/SIP) Center block PP, solid (not in contact with the product) Product-contacting housing parts: polished stainless steel 1.4404 (Ra<1.6) Valve seats made of polished stainless steel 1.4404 (Ra<1.6) PTFE membranes (compliant with EU 1935/2004; 10/2011) Valve balls PTFE (compliant with EU 1935/2004; 10/2011) Suction/pressure connection TRI-Clamp SMS 3017 DN50 PTFE seals (compliant with EU 1935/2004; 10/2011) Control valve brass, NBR Weight 21 kg Air consumption: see delivery curve Scope of delivery: Pump including silencer
6-050-15-1 PTFE Diaphragm	For Tapflo TX70 ATT model pump.
Alh 65	
6-400-61 Steuerventil Komplettmessing/Nbr	
6-100-222-22	
Pumpenmembrane T50pee-Ps Ptfe 6- 050-15-1	
Tx25att Pneumatische Membranpumpetyp Tx25attzertifiziert Nach Atex	
Rubber Sleeve For Mn010-2 Aisi	
Stator For Mn010-2 Aisi	
T100ptt	
Screw Pos 81.6 For Mn010-2 Aisi	
Txd-70-Ant	
Dtx 70at Aktive Pulsation Damper	
6-200-15-1	
Alh-651620	
Cti Eg 3f-75 Kreiselpumpe Mit Einem Elektromotor Cti Eg 3f-75	
Tx420aee	
6-100-25	
Membranpumpe T50 Pee	
Tx 70at? Membran-Pumpe Luft-Metall	
6-020-15-1 Membran Ptfe	
6-009-15-1 Membrane Fuer Pumpe Tr9ttt	
Tx420 Att 6-400-61	

For T50 Pee Membrane To Pump
Grub Screw For Mn010-2 Aisi
Cthaa-03
6-400-61-18
6-050-25
Screw Pos 81 For Mn010-2 Aisi
T50tt Pneumatische Membran-Pumpe
Tf400 Membran Pumpe Pos 15
6-050-61 Zur Pumpe Tx120annsteuerventil Komplettmessing/Nbr
T125 Sts-3x40
225.34 Nadelventil 1/4"datenblatt Zp02
6-100-16
6-050-61
?164401
5-222n-9125
Tx120ann
6-050-27 Sicherungsringstahl
Hg120404ia Kugelhahn 1/4"
03759 Pump Tx25-At
Alh-1001620 Pumpenschlauch Zu Alh100 Epdm
Part J/ See Sna Joint For Mn010-2 Aisi
Tx70 Att Membran-Pumpe
Filterdruckregler 1/4"
Cttaa-03 Kreiselpumpe Mit Elektromotor Cttaa-03
6-200-36
Pumpenmembrane T50pee-Ps 6-050-15- 3 Nbr
Joint Shaft For Mn010-2 Aisi

Spuk-Pls	LEVEL CONTROL PNEUMATIC 3-8BAR 6L/MIN
6120-18	
Mechanical Seal For Mn010-2 Aisi	
Female Drive Shaft For Mn010-2 Aisi	
Tx 420 Aee Pumpe	
Trd20ptt	
6-400-30 Ring	
Tx70att	
6-050-27	
Tx25 Ann	
T200pee	
6-400-15-3	
6-100-23	
5-340-152	
6-100-18	
6-100-47	
6-100-43	
6-050-15-1 Membrane	
T100pee	
6-100-23-3 VentilkugelInbr	
225.36 Nadelventil 1/2"1/2" Ab T200 Zp02inkl. Reduzierstutzen 1/2" - 1/2"	
Seal Cover For Mn010-2 Aisi	
Tx25att Druckluftmembranpumpetyp Tx25attatex Zertifiziert	
Part J/See Sn1 Joint For Mn010-2 Aisi	
6-050-15-3 Membrane	
Rotor For Mn010-2 Aisi	
?146901	
6-100-15	
6-220-18	
6-120-18 O-Ring Mit Dichtung	

Alh-401620
6-050-30
Pin For Mn010-2 Aisi
6-200-47
Tx25ann
T50ptt
Jji
6-100-36
6-020-61 Steuventil Komplett Messing/Nbr
Tm 125 Sts-3x Tm 125 Sts-3x