

Techap

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Techap Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Techap Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
117 0216	
117 0652	
117 0658	Electrode plug 3/4" with O-ring
117 1423	
350 0316	
860 0059	
860 0087	
860 0201	Temperature switch for heating, Switch-on temperature selectable, for installation in control cabinet
860 0315	
860 4010	
860 4011	
860 4042	BM1K filling to SL3K in cartridge
860 4055	
860 4060	
860 4076	
860 4083	
860 4145	
860 4191	

Ürün	Açıklama
860 4074	Chemikalien-Dampfschloß PVC, SL9.2K für Kartusche PN10 DN100/ ANSI 4", ohne Füllung Vapour Trap for Chemicals PVC,SL9.2 PN10 DN100 / ANSI 4" without binding agent
860 4077	BM1K Füllung zu SL 9 als Kartusche Binding agent BM1 for SL9K in cartridge
860 2075	Exhaust pre-washer 72 m³/h DN100 washing water volume approx. 75 l/h, Standard version with Wash water return to tank
860 2031	Additional charge for separate derivation Washing water for exhaust gas pre-scrubber 5/50/72/150 m³/h
860 4040	Chemical vapor lock SL3.2K, PVC, without filling Max. 5,000 l/h, max. 30 mbar!
860 5004	Extra charge for special flange Exhaust gas pre-scrubber PVC DIN DN50/ANSI 2" Placement in the room
860 2030	Exhaust gas pre-scrubber 5 m³/h PVC, Washing water consumption approx. 50 l/h, Standard version with Washer water drainage into tank Frost protection on site! Exhaust gas pre-scrubber arrangement below Chemical vapor lock!
860 4070	Chemical vapor lock SL7K, PVC, with flange DN100/ANSI 4" PN10 on bottom, without filling Max. 30,000 l/h, max. 30 mbar!
860 4076	BM1K filling for SL7K in cartridge
860 4078	Chemical vapor lock SL7.2K, PVC, with flanges DN100/ANSI 4" PN10 above and below, without filling Max. 30,000 l/h, max. 30 mbar!
860 2050	Flue gas pre-scrubber 50 m³/h DN100 Washing water volume approx. 150 l/h, Standard version with Wash water return to tank Frost protection on site!!

Ürün	Açıklama
860 4073	Chemical vapor lock SL9K, PVC, with Flange DN100/ANSI 4" PN10 bottom, without filling Max. 72,000 l/h, Pmax +30/-30 mbar
860 4257	Chemical vapor lock SL11K, V4A/PMMA, with flange DN125/ANSI 5" PN10 bottom, without filling Max. 150,000 l/h, Pmax +30/-30 mbar
860 5257	Chemical vapor lock SL11.2K, V4A/PMMA, with flanges DN125/ANSI 5" PN10 top and bottom, without filling Max. 150,000 l/h, Pmax +30/-30 mbar
860 4094-H	BM1K filling for SL11K loose with heating cartridge
860 0198	Heating system for SL11 220/230V 50/60 Hz, 90 W
860 4196	Regenhut-VA-SL3/5/7 -- Outdoor installation, temperatures <0°C
860 4094	BM1K filling to SL11K in cartridge - Installation in room >0°C
860 4190	Chemical vapor lock SL11K, PVC, with Flange DN125/ ANSI 5" PN10 bottom, without filling Max. 150,000 l/h, Pmax +30/-30 mbar
860 0197	Rain Hat-PPH-SL9/11
117 0210	UVK 20.1 F1 process valve conventional
117 0723	STUVK 20, 24V DC Actuator drive with Manual adjustment
117 0650	Set of connecting parts (6 parts) UV 20 F