

Thermokon

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Thermokon Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Thermokon T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
LCF Touch Modbus	RS485
49917 SFK02 PT1000 050.08	
LS02+	659253 Power supply: 15..24 V = / 24 V ~ Switching output: relay, 24 V / 1 A, with changeover contact Contact material: stainless steel V2A (1.4305) Signaling LED: red=detection of liquid; green=operation Housing: USE-S
FTA54+ VV	Outside sensor temperature, humidity - 0..5 V, 0..10 V Power supply: 15..24 V = ($\pm 10\%$) or 24 V ~ ($\pm 10\%$) Output: 2x 0..10 V = Temperature measuring range: -20..+80 °C, adjustable on the transmitter Humidity measuring range: 0..100% rH without condensation, enthalpy: 0..85 Kj/kg, absolute humidity: 0..50 0..80 g/m ³ or dew point: 0..+50 -20..+80 °C, adjustable on the transmitter Temperature accuracy: ± 0.5 °C, humidity accuracy: $\pm 2\%$ between 10..90% rH Sensor tube: 53 mm with protective cap, stainless steel mesh Impact and shatterproof housing USE-M with hinged cover (PC, pure white, IP65) Removable cable entry (M20 flex, exchangeable) and removable plug-in terminal (max. 2.5 mm ²) Potentiometer for calibrating offset values Incl.

	sun/rain protection PA6 white, mounting base and fastening screws
TF25 NTC10k T100 050.06 L2000	Cable sensor -35..+100 °C – passive Measuring insert with SI protection to protect against moisture and vibrations: NTC10k Temperature range: -35..+100 °C Sensor sleeve: stainless steel V4A, Ø=6 mm, installation length 50 mm, 16-fold segmented, IP65 Sensor line: PVC, 2x0.25 mm ² , length 2000 mm
MS-Tauchh¼lse 50 mm Typ THMSDS50	Brass, length (L): 50 mm, sleeve length (HL): 44 mm, installation length (EL): 36 mm Outside Ø=9 mm, SW22, R1/2", inside Ø=7 mm PN 16 bar, SW13 pressure screw, silicone clamping ring for 6 mm sleeve
NOVOS 3 Temp_rH weiŐ VV	Room sensor temperature, humidity – 0..5 V, 0..10 V Output: 2x 0..10 V (0..5 V optionally configurable via Thermokon NOVOSapp) Temperature measuring range: 0..+50 °C (optionally configurable via Thermokon NOVOSapp), Accuracy: ±0.5 K (typ. at 21 °C) Humidity measuring range: 0..100% rH (enthalpy, absolute humidity & dew point optionally parameterizable via Thermokon NOVOSapp), accuracy rel. Humidity: ±2% between 10..90% rH (typ. at 21 °C) Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
NOVOS 3 CO2 weiŐ Temp_rH Design 3xV	Room sensor temperature, humidity, CO2 – 0..5/10 V Output: 3x 0..10 V (0..5 V optionally configurable via Thermokon NOVOSapp) Temperature measuring range: 0..+50 °C (optionally configurable via Thermokon NOVOSapp), Accuracy: ±0.5 K (typ. at 21 °C) Humidity measuring range: 0..100% rH (enthalpy, absolute humidity & dew point optionally parameterizable via Thermokon NOVOSapp) accuracy rel. Humidity: ±2% between 10..90% rH (typ. at 21 °C) Measuring range CO2: 0..2000 ppm 0..5000 ppm (optionally configurable via Thermokon NOVOSapp), Accuracy: ±50 ppm (self-calibration dual channel) Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) with design cover (see next position) Electrical connection: Spring-loaded terminal that can be mounted without tools
Designblende NOVOS 3 Black	Plexiglass XT (PMMA) 60x109x1.5 mm Surface scratch-resistant and UV-resistant coated in RAL9005 deep black
Design panel NOVOS 3 alu	Alternativ Plexiglass XT (PMMA) 60x109x1.5 mm Surface scratch-resistant and UV-resistant coated in RAL9006 white aluminum
NOVOS 3 Temp white NTC10k	Room sensor temperature - Passive Measuring element: NTC10k Operating temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
WRF08 8T BACnet	

728423	NOVOS 3 Temp white NTC10k Room sensor temperature - Passive Measuring element: NTC10k Operating temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
731652	NOVOS 3 Temp white RS485 Modbus Room sensor temperature - RS485 Modbus Network technology: RS485 Modbus Temperature measuring range: -20..+70 °C, accuracy: ±0.5 K (typ. at 21 °C) Input: 1x input for potential-free contact Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
620871	AKF10+ NTC10k 100.06 Duct/immersion sensor -50..+150 °C - Passive Measuring insert with SI-Protection to protect against moisture and vibrations: 1x NTC10k Acid-resistant stainless steel sensor sleeve for aggressive media Ø=6 mm, installation length 100 mm, V4A Impact- and shatter-proof housing with hinged lid (PC, pure white, IP65) Removable cable entry (M20 flex, replaceable) and removable plug-in terminal (max. 2.5 mm²) including mounting clip and fastening screws
620666	VFG54+ PT1000 Contact Sensor Temperature - Passive Measuring element: PT1000 DIN Class B Impact- and shatter-proof housing with hinged lid (PC, pure white, IP65) Removable cable entry (M20 flex, replaceable) and removable plug-in terminal (max. 2.5 mm²) Sensor sleeve: brass, spring-loaded sensor contact Note: Please select sensor. Information is missing from your request.
668071	PA clamping band (max. 85°C) for pipe diameters up to 100 mm with thermal paste Set consisting of: - 1x tensioning strap, PA6.6, UV-resistant, ..+85 °C - 1x syringe of thermal paste
728423-	NOVOS 3 Temp white NTC10k Room Sensor Temperature - Passive Measuring element: NTC10k Temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Tool-free spring-loaded terminal Note: Successor
FTK140VV	SENSOR
Joy Fancoil 5do Rs485 Modbus	
Sr-Mds	
Lcf Touch Rs485 Modbus	
Akf10 Pt100 192.07	
Pt100-4x50-3mt	
Wrf04 Lon	
Akf10 Pt100 062.07	

[Thmsds100](#)

[Tf25 Trv2 T120 050.06 L1000](#)

[Tf25 Pt100 T100 050.06 L1000 3-Leiter](#)

[Fta54+ Vv](#)

[Sr65 Tf](#)