Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Thermokon

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Thermokon Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Thermokon Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
LCF Touch Modbus	RS485
49917 SFK02 PT1000 050.08	
LS02+	659253 Power supply: 15..24 V = / 24 V ~ Switching output: relay, 24 V / 1 A, with changeover contact Contact material: stainless steel V2A (1.4305) Signaling LED: red=detection of liquid; green=operation Housing: USE-S
FTA54+ VV	Outside sensor temperature, humidity - 0..5 V, 0..10 V Power supply: 15..24 V = (±10%) or 24 V ~ (±10%) Output: 2x 0..10 V = Temperature measuring range: -20..+80 °C, adjustable on the transmitter Humidity measuring range: 0..100% rH without condensation, enthalpy: 0..85 Kj/kg, absolute humidity: 0..50 | 0..80 g/m³ or dew point: 0..+50 | -20..+80 °C, adjustable on the transmitter Temperature accuracy: ±0.5 °C, humidity accuracy: ±2% between 10..90% rH Sensor tube: 53 mm with protective cap, stainless steel mesh Impact and shatterproof housing USE-M with hinged cover (PC, pure white, IP65) Removable cable entry (M20 flex, exchangeable) and removable plug-in terminal (max. 2.5 mm²) Potentiometer for calibrating offset values Incl. sun/rain protection PA6 white, mounting base and fastening screws
TF25 NTC10k T100 050.06 L2000	Cable sensor -35..+100 °C – passive Measuring insert with SI protection to protect against moisture and vibrations: NTC10k Temperature range: -35..+100 °C Sensor sleeve: stainless steel V4A, Ø=6 mm, installation length 50 mm, 16-fold segmented, IP65

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Sensor line: PVC, 2x0.25 mm², length 2000 mm
MS-Tauchhülse 50 mm Typ THMSDS50	Brass, length (L): 50 mm, sleeve length (HL): 44 mm, installation length (EL): 36 mm Outside Ø=9 mm, SW22, R1/2", inside Ø=7 mm PN 16 bar, SW13 pressure screw, silicone clamping ring for 6 mm sleeve
NOVOS 3 Temp_rH weiß VV	Room sensor temperature, humidity – 0..5 V, 0..10 V Output: 2x 0..10 V (0..5 V optionally configurable via Thermokon NOVOSapp) Temperature measuring range: 0..+50 °C (optionally configurable via Thermokon NOVOSapp), Accuracy: ±0.5 K (typ. at 21 °C) Humidity measuring range: 0..100% rH (enthalpy, absolute humidity & dew point optionally parameterizable via Thermokon NOVOSapp), accuracy rel. Humidity: ±2% between 10..90% rH (typ. at 21 °C) Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
NOVOS 3 CO2 weiß Temp_rH Design 3xV	Room sensor temperature, humidity, CO2 – 0..5/10 V Output: 3x 0..10 V (0..5 V optionally configurable via Thermokon NOVOSapp) Temperature measuring range: 0..+50 °C (optionally configurable via Thermokon NOVOSapp), Accuracy: ±0.5 K (typ. at 21 °C) Humidity measuring range: 0..100% rH (enthalpy, absolute humidity & dew point optionally parameterizable via Thermokon NOVOSapp) accuracy rel. Humidity: ±2% between 10..90% rH (typ. at 21 °C) Measuring range CO2: 0..2000 ppm | 0..5000 ppm (optionally configurable via Thermokon NOVOSapp), Accuracy: ±50 ppm (self-calibration dual channel) Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) with design cover (see next position) Electrical connection: Spring-loaded terminal that can be mounted without tools
Designblende NOVOS 3 Black	Plexiglass XT (PMMA) 60x109x1.5 mm Surface scratch-resistant and UV-resistant coated in RAL9005 deep black
Design panel NOVOS 3 alu	Alternativ Plexiglass XT (PMMA) 60x109x1.5 mm Surface scratch-resistant and UV-resistant coated in RAL9006

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	white aluminum
NOVOS 3 Temp white NTC10k	Room sensor temperature - Passive Measuring element: NTC10k Operating temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
WRF08 8T BACnet	
728423	NOVOS 3 Temp white NTC10k Room sensor temperature - Passive Measuring element: NTC10k Operating temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
731652	NOVOS 3 Temp white RS485 Modbus Room sensor temperature - RS485 Modbus Network technology: RS485 Modbus Temperature measuring range: -20..+70 °C, accuracy: ±0.5 K (typ. at 21 °C) Input: 1x input for potential-free contact Voltage supply: 15..35 V = or 19..29 V ~ Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Spring-loaded terminal that can be mounted without tools
620871	AKF10+ NTC10k 100.06 Duct/immersion sensor -50..+150 °C – Passive Measuring insert with SI-Protection to protect against moisture and vibrations: 1x NTC10k Acid-resistant stainless steel sensor sleeve for aggressive media Ø=6 mm, installation length 100 mm, V4A Impact- and shatter-proof housing with hinged lid (PC, pure white, IP65) Removable cable entry (M20 flex, replaceable) and removable plug-in terminal (max. 2.5 mm²) including mounting clip and fastening screws
620666	VFG54+ PT1000 Contact Sensor Temperature – Passive Measuring element: PT1000 DIN Class B Impact- and shatter-proof housing with hinged lid (PC, pure white,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	IP65) Removable cable entry (M20 flex, replaceable) and removable plug-in terminal (max. 2.5 mm²) Sensor sleeve: brass, spring-loaded sensor contact Note: Please select sensor. Information is missing from your request.
668071	PA clamping band (max. 85°C) for pipe diameters up to 100 mm with thermal paste Set consisting of: - 1x tensioning strap, PA6.6, UV-resistant, ..+85 °C - 1x syringe of thermal paste
728423-	NOVOS 3 Temp white NTC10k Room Sensor Temperature – Passive Measuring element: NTC10k Temperature range: -35..+70 °C Housing: NOVOS 3, PC V0, pure white, IP20, 110x100.5x23 mm (LxWxH) Electrical connection: Tool-free spring-loaded terminal Note: Successor
FTK140VV	SENSOR
255202	PS1500 Differential Pressure Switch And also the safe model of the same product.
Joy Fancoil 5do Rs485 Modbus	
Sr-Mds	
Lcf Touch Rs485 Modbus	
Akf10 Pt100 192.07	
Pt100-4x50-3mt	
Wrf04 Lon	
Akf10 Pt100 062.07	
Thmsds100	
Tf25 Trv2 T120 050.06 L1000	
Tf25 Pt100 T100 050.06 L1000 3-Leiter	
Fta54+ Vv	
Sr65 Tf	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.