



Thompson Valves

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Thompson Valves Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Thompson Valves Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
7994700.XXXX.XXXXX *	Series 79947 Designation ICO4SEXD207B2/2ECAUT1/4NPT PEL no. Y162AA1J1BS
1300000.0000.00000	
MODEL: ICO3S	INTERNAL DIAMETER: 8 MM MATERIAL: STAINLESS STEEL STEM SEALING: O-RING SEAT DESIGN: SOFT SEATED LEAKAGE CLASS: VI COIL VOLTAGE: 24VDC ATEX: EXD IIC T6 TA OPERATING PRESSURE: 1 (0-12 BARG / 0-174 PSI) PORT CONFIG: 3 (3/2 UNIVERSAL) OPERATION: A (AUTOMATIC) PROCESS CONNECT: A1 (1/4" NPT) SEAT/SEAL MAT: H (NITRILE) CONNECTION: M20X1.5 Ordering information for Maxseal Solenoid Operated Valves "ICO3S Model -YO (ICO3S Exd) Operating Pressure -1 (0-12barg/0-174psi) Port config -3 (3/2 universal) Operation- A (Automatic) Process connect -A1 (1/4" NPT) Seat/Seal materials -H (Nitrile) Conduit.connection 1 (M20x1.5) Voltage -B (24VDC) Body/trim materials-S (316SS) EX II 2 G D Certificate requirements: -ATEX 94/9/EC -CU TR 012
7994700.0006.33044	Country of Origin: UK Customs Tariff 84818073 5.060 kg Series 79947 Designation ICO4SEXD207B2/2ECAUT1/4NPT

	PEL no. Y162AA1L1BS Replacement for Y162AA1L1BS
ICO3S, YO13AA1V1BS	VALVE,SOL,ICO3S,YO13AA1V1BS,1/4",NPTF,NC BODY MATERIAL : 316 COIL TYPE : CL H CONNECTION TYPE : NPT F DISK MATERIAL : 316 ELECTRICAL CONNECTION DETAILS: M20X1.5 CONDITIONS ELECTRICAL RATING 24 VDC ENVIRONMENTAL PROTECTION: IP66/X8,NEMA 4X MODEL NO: ICO3S,YO13AA1V1BS NOMINAL SIZE: 1/4 IN NUMBER OF POSITIONS : 2 NUMBER OF ROADS : 3 SEAT MATERIAL : FKM TYPE : NC Basic Data Text: WORKING PRESSURE: 0 - 12 BAR OPERATION: AUTOMATIC HAZARDOUS AREA EXD MEDIA: LIQUID AND GAS POWER: 3 W, CV: 0.6
K41	Model: K41 Part Number: K41P8SN Serial Number: 30442/P/13 Maximum Inlet Pressure: 40BAR Outlet Range: 0.5-40BAR DN: 25mm Temperature Range: -10°C to 100°C
K42	Model: K42 Part Number: K42P8SN Maximum Inlet Pressure: 40BAR Outlet Range: 0.5-40BAR Temperature Range: -10°C to 100°C DN: 50mm Serial Number: 30442/P/10
YO12AA1H2SS-90	
IVP TYP J50	Pressure regulator
4a41-W8-611	
4a91-W7-505	
4a41-W8-140	
4a42-W5-119	
4a41-W8-035	
N3635	
Maxseal Iso3s	
4a24-G2-034	
4a41-W8-009	
4a41-W8-142	