



Thyracont

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Thyracont** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Thyracont T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
B_VSM77	
SLKBT	
SLKUSB	
SLN4	
VD85M	
VSM77D	
VSP63MA4	
W1515010	
XB15SL05	
ZSR2025	
ZZCH025	
ZZR025	
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
	Measuring cable with open ends, 2 m For analog line transmitters 0-10

W0600002	V, one side with Hirschmann 6-pin device connector, one side with open cable ends
DCERT	Factory calibration digital
VCP63MV Vacuum transmitter Pirani	absolute pressure 5.0e-4 - 1000 hPa, Corrosive gas version, platinum-rhodium filament Output signal: 2.2-8.5 V (logarithmic) Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN16 KF
XB0600002	Line socket 6-pin. GO 6 WF Mating connector for analog line transmitter 0-10 V
DCERT - Factory calibration digital	four-page calibration certificate as a PDF DOCUMENT for documentation, 4 reference points per printing decade (traceable to national DAKS standards)
VD85	Compact vacuum gauge Piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power adapter (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE protective case VD8, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack connector: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 Interface cable, 2 m, USB; VGR VacuGraph 11 software, for Windows Vista / 7 / 8 / 10 / 11
VCP63MA4	Vakuumtransmitter Pirani
XB0500004	Angle socket 5-pin, series 713 Mating connector, 5-pin for analog line transmitters 4-20 mA
DCERT	Factory calibration digital
SP363MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.0 - 10 V logarithmic (1.286 V/decade) Electrical connection: FCC68 8-pin female. Stainless steel flange DN 16 ISO-KF
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
VD85	Compact vacuum gauge piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power supply (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE VD8 protective case, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC change-over plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack plug: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 interface cable, 2 m, USB; VGR VacuGraph 11 Software, for Windows Vista / 7 / 8 / 10 / 11
VD8ANS	Connection set consisting of: - 1 piece ZTS016 DN 16 ISO-KF T-piece, stainless steel - 2 pieces ZZR016 DN 16 ISO-KF centering sealing ring, stainless steel / Viton - 2 pieces ZSR1016 DN 10/16 ISO-KF clamping ring, aluminum
VCP63MA4	Pirani vacuum transmitter
VSP63MV	Absolute pressure 5.0e-4 - 1000 hPa Corrosive gas version, platinum-rhodium filament Output signal 4-20 mA logarithmic Electrical connection: M12 A, 5-pin male Stainless steel flange DN 16 ISO-KF
VCP63MV	
ZSR1016 ISO -KF Clamp DN10/16	

VD84/1-	Compact vacuum gauge Pirani Absolute pressure 1.0e-3 - 100 hPa, with Piran probe VSP841 Data logger function, min/max memory USB interface for battery (9 V) or external power supply (15 V) Stainless steel flange DN 16 ISO-KF including battery 6 LR 61, 9V / 680 mAh
ZSW 1612	Adaptor DN 16 ISO-KF / hose nozzle (Inside diameter 12 mm)
ZNPT14	Adaptor DN 16 ISO-KF - NPT 1/4
ZZCH016	Centering ring with Baffle for sensor protection against pollution
ZZDF016	Centering ring with wire filter for sensor protection against pollution
VSP63MV-	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
THYR CONT VD 84	
Vd8alk	
Vsp62mvsw	
Wusb0002	
Vd85	
Vd8case	
Vgr	
Vd8ans	
W 1500002	
Zzr016	
Vd81	
VD8N4	Plug-in power supply 15 V Input 100 - 240 VAC / 50 - 60 Hz, AC interchangeable plug EURO, US, UK, AUS Output 15 VDC / 200 mA, DC jack plug 2.5 x 5.5 x 10 mm for VD8
Vd84	
W0606002	
Adjcert	
Vsr53d	
Zsr1016	
Vd81sw1	
Vd85m Obsolete/Replacement Vd85	
Vd83	
Vsp63mv	
Vsp52 Ma4	
Vcc200ma4	
Vsh88d	
Vd84/1	
Vsm77dl	