

Tramec

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tramec Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Tramec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
VM150	
10146	
12755	
13793	
16264	
18774	
2164410001	
9011001802	
9011051802	
BFK 50 P 15/1 B3 PAM 19/120	
EP 055 1 C 10 AQ AE09 P03 B5	
EP 075 1 C 10 AQ AE14 P27 B5	

EP 155 1 C 10 AQ AE32 P05 B5	
EP 90 2 C 35 TT AE14 P03 B5	
FC 71C 0.55 kW 4P B5	
RL 32 BC 1/1 3FI	
SFK 040H015-71B14	
TC 160 C 125/1 38/300 V B3 FLS	
VM 135 22/1 PAM 19/160	
TC 160 CV-500-3-B6-2,2-6513-380-50	
KC90	
TC-140-B-050/1-250/28-O-VB-H50-LUBR	20403 Bevel Helical Gearb.-: T Type of drive (Input type)----- -----: C (flange short) Gear size----- -----: 140 Gear stages (gearing)----- -----: B (2 stages) Gear Ratio (x:1)----- -----: 50:1 (50.18:1) Motor size flange/ shaft (Motor size)-----: Ø 250/28 mm (IEC100/112B5) Drive Position, Execution -----: O Installation position (Mounting position)----- -----: VB Output hollow shaft (Hollow shaft)----- -----: H (hollow shaft Ø 50 mm) (T2Max: 2120 Nm, at n1= 1400 rpm, P1= 6.5 kW) Thermal power -----: Pto= 7.6 kW Weight ----- -----: 75 kg Art. No. Internal. (Code)----- -----: 2014875002 / 010004 Customs tariff number/origin (Customs Tariff/origin): 84834023 / EU Life lubrication-----: Shell Omala S4 WE 320
KC-090-P-030/1-250/28-B3-00-000-H-00-LUBR	20404 Worm Gear (Wormgearbox)-----: K Drive type (Input type)-----: C (flange, short) Gear size-----: 90 Execution (version)----- -----: P Reduction (Ratio) i ----- -----: 30 : 1 Motor size flange/ shaft (Motor size)-----: Ø 250/28 mm (IEC100B5) Installation position (Mounting position)-----: B3 Output shaft ----- -----: H (hollow shaft Ø 35 mm) (Deflection torque T2max: 340 Nm at n1= 1400 rpm, P1= 2.2 kW) Thermal power -----: Pto= 1.5 kW Dyn. efficiency-----: Rd=0.76 dynamic Self-locking when Rd is less than 0.45. Weight ----- -----: Approx. 16.4 kg Art. No. Internal. (Code)----- -----: 2225248011 / 22A001 Life lubrication-: Shell Omala S4 WE 320 Customs Tariff Number/Origin (Cusoms Tariff/origin): 84834025/EU
KC-075-P-015/1-200/24-B3-00-000-H30-00-LUBR	20405 Worm Gearbox (Wormgearbox)-----: KC Drive type (Input type)-----: C (flange, short) Gear size-----: 75 Execution (version)-----: P Reduction (Ratio) x:1-----: 15:1 Motor mounting flange/shaft (Motor mounting)-----: 200/24mm (IEC90 B5) Mounting position-----: B3 Output shaft -----: Hollow shaft 30 mm (n2= 93 rpm at n1= 1400 rpm, T2= 202 Nm, P1= 2.4

	<p>kW) Weight ----- 9.5 Kg Art. No. Internal. (Code)----- : 2224427019 Life lubrication-----: Shell Omala S4 WE 320 Customs Tariff Number/Origin (Cusoms Tariff/origin)-: 84834025/EU</p>
KC75 İ:15 2224427019	
21.01-TC-112/TC-125/RC-28 bevel gear pair 16/41	<p>Bevel gear weehl couple Spare part ---: 21.01 Gearbox ----- : TC-112 / TC-125 / RC-28 Art. No. Internal (Code) -----: 2150132131</p>
13.01-TA/TC/TF-112-B-Z11 spur gear	<p>Helical gear for bevel helical gearbox Spare part ----- : 13.01 Gearbox -----: TC-112-B Number of teeth: 11 Weight -----: approx. 0.8 kg Art. No. Internal (Code) -----: 1130132021</p>
19.01-TA/TC/TF-112-B-Z56 spur gear	<p>Helical gear for bevel helical gearbox Spare part ----- : 19.01 Gearbox -----: TC-112-B Number of teeth: 56 Weight -----: approx. 1.5 kg Art. No. Internal (Code) -----: 1190132021</p>
TC-112-B-012,5/1-300/38-O-B6-H45-FLD-LUBR	<p>Bevel helical gearbox: T Drive type (Input type) ----- -----: C (flange, short) Gear size ----- --: 112 Gearing stages -----: B (2-stage) Gear ratio x:1 -----: 12.5 (13.05) Motor flange/shaft (motor coupling) -----: Ø 300/38 mm (IEC132 B5) Execution -----: O Mounting position -----: B6 Hollow output shaft -----: H (hollow shaft Ø 45 mm) Output flange -----: FLD (right) Weight -----: approx. 44.0 kg Art. No. Internal (Code) -----: 2013639004 / 01o009 Life lubrication: Shell Omala S4 WE 320</p>
21584	<p>21.01-TC-112/TC-125/RC-28 Ø38 bevel gear pair 16/41 Bevel gear pair (Bevel gear couple) Spare part -----: 21.01 Gearbox -----: TC-112 / TC-125 / RC- 28 Input hollow shaft: Ø 38 mm Teeth ----- -----: 16 / 41 Weight -----: approx. kg Internal item no. (Code) -----: 2150132131</p>
17439	<p>13.01-TA/TC/TF-112-B Z=11 spur gear Helical gear for bevel helical gearbox Spare part -----: 13.01 Gearbox ----- -----: TA/TC/TF-112-B Number of teeth: 11 Weight ---- -----: approx. kg Internal item no. (Code) ----- -----: 1130132021</p>
17440	<p>19.01-TA/TC/TF-112-B Z=56 gear Gear for helical bevel gearboxes Spare part: 19.01 Gearbox ---: T-112-B Teeth ---- -----: 56 Weight -----: approx. kg Internal item no. (Code) - : 1190132021</p>
BFK-050-FLD-040/1-105/14-B3-00-000-H25-00-LUBR 45	<p>Worm gear (Wormgearbox) ---: BFK Input type ----- ----: F (flange) Gear size ----- : 50 Design (Version) -----: FLD (output flange right) Reduction (Ratio) x:1 -----: 40 Motor flange/shaft (motor coupling): Ø 105/14 mm (IEC71 B14) Motor rotated by 45° Mounting position -----: B3 Output shaft -----: H (hollow shaft Ø 25 mm) Weight -----:</p>

	approx. 3.4 kg Art. No. Internal (Code) -----: 9012152103 / 22A002 Life lubrication: Shell Omala S4 WE 320
20404	KC-090-P-030/1-250/28-B3-00-000-H35-00-LUBR Worm gear (Wormgearbox) ---: K Input type -----: C (flange, short) Gear size ----- : 90 Version ----- -----: P Reduction (Ratio) x:1 -----: 30 Motor flange/shaft (motor coupling): Ø 250/28 mm (IEC100B5) Mounting position -----: B3 Output shaft ----- -----: H (hollow shaft Ø 35 mm) Weight ----- -----: 24.0 kg Art. No. Internal (Code) -----: 2225248011 / 22A001 Life lubrication: Shell Omala S4 WE 320
BFK-050-P-007,5/1-120/19-B3-00-000- H25-00-LUBR	
23010	EP-090-2-C-035-AQ-AE19-P12-N-B5 Planetary gearbox: EP Gear size: 90 Gear reduction steps: 2 Coaxial ----- -----: C Reduction ratio x:1 -----: 35 Output shaft: A Ø 22 mm Output flange -----: Q quadr. 90mm Input shaft: AE Ø 19 mm Drive flange (Input flange) -- -----: P12 square. 80mm Precision class ----- -----: N Mounting position: B5 Weight ----- ---: approx. 4.1 kg Art. No. Internal (Code) ----- --: 2562658408 / 60N001 Lifetime lubrication
XC 110 100 160/28 100B14	7 ArcMin
Ep 55	
9011051802 Gear-Ratio 10 Gear-Ratio 10	
17302340050011	
Ep 90	
Rep 150	
9011902401 Gearbox Bek50 P 15 B3	
?? 160 ?V-500-3-?6-2,2-6513-380-50	
M-071-B4-B14-F-230/400/50	
18773 Planetary Gearbox Ep-075-1-C- 010-A-Q-Ae14-P27-N-B5	
12358 Planetary Gearbox Ep-155-1-C- 010-A-Q-Ae32-P05-N-B5	
Tc 160 ? 125/1 38/300 V B3 Fls Getriebe	
Gear-Ratio 7.5 Gear-Ratio 7.5	
17198	
2014881001	

9011001802 Getriebe Sfk 40 Ratio 7.5	
18774 Planetary Gearbox Ep-055-1-C-010-A-Q-Ae09-P03-N-B5	
2011851003	
Rep 075	
Ep 75	
2164410001 A Worm Gear Assembly Xc 7.5 16f001 09/08	
Ep 120	
Rep 125	
Rep 100	
Xa 30 10 B3 H Sea	
11129 Gearbox RI-32-Bc-1/1-3fi-Lubr	
Sfk30	
Tc71bfld	
16264 Schneckengetriebesfk-050-P-050/1-105/14-??-00-000-H20-00-Lubr Aps237	
Orttc71d40	
Ta112b	
Ep90-2	
16314	
Xc-050-010/1-105/14-B3-000-00-000-H25-00	
Rep100/1c-3-Au19flt-Ae19-P18	SERVO GEARBOX PLANETARY 343:1RATIO 1STEP
Ep 155	
Pc125 /55/B/I=40	
15014920050002	