



Tridelta

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Tridelta Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Tridelta Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
VAN053490-2313.6-0144.18-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
4*400V 3 Phase surge arrester 100kA B type	
4*574V 3 Phase surge arrester 100kA B type	
1*1150V Phase surge arrester 100kA B type	
36kV 10kA surge arrester (to be used in 31.5kV	system) 18 Pieces 6 Sets
Surge Arrester - SBKC 144/SM-II	PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
Surge Counter DCC-M 2	
Surge Arrester - SBKC 144/SM-II	PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
DCC-M 2	
SB 192/SH-A-I	
SBKC 120/10.3	
VAN056391-2313.6-0144.20-F	Surge arrester – SBKC 144/SM-II PH-A-45x45–60x60 (2100.PH-0001.00) Q (2300.AB-0002.00)

Ürün	Açıklama
	Er-X-45x45-60x60 (2100.ER-0001.00)
SBKC 30/SH-II	
SBKC 48/SH-II	
SBK-I 9/10.1	
SBK-II 12/10.1	
SBK-II 36/10.1	
144 kV, 10 kA, ZnO, Sn: 3	
36 kV, 10 kA, ZnO, Sn:2	
Surge arrester - SBKC 144/SM-II	PH-A-45x45 - 60x60 (2100.PH-0001.00) Installation variant - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
Surge arrester - SBKC 36/SM-II	PH-A-45x45 - 60x60 (2100.PH-0001.00) Installation variant - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
Model: SBKC 144/SM-II	
VAN044426-2272.6-0024.01-F	Surge arrester - SBKC 24/SL-0 Voltage connection - A 45x45 - 60x60 (2200.PH-0001.00) Installation variant - Q (2200.AB-0001.00) Earth connection - X 45x45 - 60x60 (2200.ER-0001.00)
Surge Arrester with surge counter	
VAN045349-2313.6-0144.20-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00) 1. TRIDELTA surge arresters are type tested and manufactured as per: IEC 60099-4, ISO 9001 as well as standard EN 50123-5 in case of DC arresters. 2. Repetition of type tests is not included in our offer. 3. Routine tests as per IEC 60099-4, cl. 9.1 are included. a) measurement of reference voltage on arrester units b) residual voltage test on resistor element (ZnO varistors) c) internal partial discharge test on arrester units d) leakage check (only applicable for SB, SBK and SBKT types) 4. Routine test certificates available on request. 5. Standard factory acceptance test (FAT) as per IEC 60099-4 cl. 9.2.1 or any other special test

Ürün	Açıklama
	only on separate agreement.
VAN046722-3011.5-2036.362-F	Surge Arrester - SBK-II 36/10.1 Terminal - A (3011.4-1113.00) Terminal - A (3011.4-1113.00)
5100.5-0001.00	Surge Counter DCC 2
VAN049294-2313.6-0144.20-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN049555-2313.6-0144.20-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00) Technical conditions: 1. TRIDELTA surge arresters are type tested and manufactured as per: IEC 60099-4, ISO 9001 as well as standard EN 50123-5 in case of DC arresters. 2. Repetition of type tests is not included in our offer. 3. Routine tests as per IEC 60099-4, cl. 9.1 are included. a) measurement of reference voltage on arrester units b) residual voltage test on resistor element (ZnO varistors) c) internal partial discharge test on arrester units d) leakage check (only applicable for SB, SBK and SBKT types) 4. Routine test certificates available on request. 5. Standard factory acceptance test (FAT) as per IEC 60099-4 cl. 9.2.1 or any other special test only on separate agreement.
VAN050023-2313.6-0144.20-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN050023-1213.6-0144.06-F	Surge Arrester - SB 144/SM-A-0 line terminal - A 45x45 - 60x60 (1200.PH-0011.00) variants of installation - Q (1200.AB-0011.00) earth terminal - X (M12) 45x45 - 60x60 (1200.ER-0002.00)
5100.5-0002.00	Surge Counter DCC-M 2
VAN050401-2313.6-0144.20-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00)

Ürün	Açıklama
	Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN050401-2313.6-0154.20-F	Surge Arrester - SBKC 154/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN050401-2272.6-0042.03-F	Surge Arrester - SBKC 42/SL-0 line terminal - A 45x45 - 60x60 (2200.PH-0001.00) variants of installation - Q insulated 160-260mm (2200.AB-0017.00) Earth terminal - X 45x45 - 60x60 (2200.ER-0001.00)
VAN051023-2313.6-0072.08-F	Surge Arrester - SBKC 72/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2313.6-0090.10-F	Surge Arrester - SBKC 90/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2313.6-0108.12-F	Surge Arrester - SBKC 108/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2313.6-0120.14-F	Surge Arrester - SBKC 120/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2313.6-0144.18-F	Surge Arrester - SBKC 144/SM-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2314.6-0225.30-F	Surge Arrester - SBKC 225/SH-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
VAN051023-2314.6-0276.41-F	Surge Arrester - SBKC 276/SH-II PH-A-45x45 - 60x60 (2100.PH-0001.00) variants of installation - Q (2300.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
7371.6-0036.06-V	Surge Arrester - SBKW 36/DH-I
7300.PH-0002.00	Ph- A -Kabelschuh M12

Ürün	Açıklama
7300.AB-0002.00	AB-A-cable lug M12
He36 10kA	Parafudr YG HE36 10kA Class 1 Opt Areva Varısl
VAN061029-1813.6-0360.19-F	Surge arrester - SB 360/SM-AI Installation variant -M -4L 310x310 M20x160 Earth terminal - Er-X -45x45 up to 60x60 Technical conditions: TRIDELTA surge arresters are type-tested and manufactured according to IEC 60099-4, ISO 9001, and IEC 62848 (for DC arresters). Repetition of type tests is not included. Routine tests according to IEC 60099-4, clause 9.1 are included: reference voltage measurement residual voltage test on ZnO varistors internal partial discharge test leakage check (SB, SBK, SBKT types only) Routine test certificates available on request. Factory acceptance test (FAT) only by separate agreement. Included documents: outline drawings technical catalogue assembly and maintenance instructions Spare parts/tools are not included.
Sbk-li 24/10.1	
Ansprechzö;Hler Dcc-M 2	
Sbk... 6/10.2	
136888-10	
Sbk 144/10.3	
Sbk 144/Sm-li	Surge arresters PH-A-45x45 - 60x60 (2100.PH-0001.00) Installation variant - Q (2100.AB-0002.00) Er-X-45x45 - 60x60 (2100.ER-0001.00)
Sbk 0 45/10.1	
77.287.136888-00.2 (12)	
Sbk-lv 51/10.3	
Sbk-l 39/10.3	
Sbk 138/10.3	

Ürün	Açıklama
Sb 144/10.2-0	
Sbk-I 48/10.3	
Sbk-li 36/10.1	Surge Connection - A (3011.4-1113.00) Connection - A (3011.4-1113.00)
Sbk-c 38/20.4	
Sb 28/20.4-0-	
Sbk-lv 24/10.3	
831400	
77.287.136888-00.2	
Sbk-c48/20.4	
Sb 360/20.3-1	
170kv Parafudr-Kompozit Silikon - 144 Kv 10 Ka Zno Sn:3	
136888 (12pcs)	
136888	
Sb 28/20.4-0-?	
Varisil/He36 10ka/Class 1 /Opt	
Sbk-b 1/10/G	
Sbk 144/10.3-I	