Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Trimod Besta



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Trimod Besta Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Trimod Besta Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Typ : Db 01 051	Customs tariff number: 9026.1089 Country of origin: CH Weight (kg / each): 2.800 Trimod Besta level switch Switching module DB => E-connection: aluminum switch housing - with cable gland: M20 x 1.5 mm Microswitch: 1 x changer gold contact - Switching capacity: 30 VDC, 0.3 A Degree of protection: IP 66/67 Flange module 01 => Process connection: flange 92 x 92 mm - Pitch circle: 92 mm, hole: 4 x 13 mm - Seal: Form C Nominal pressure: PN 25, max. 25 bar
A 01 041	Trimod Besta level switch A - SPDT microswitch, changeover switch 398.65 3,986.50 with silver contacts 5A250VAC, Housing cast aluminum, seawater resistant Protection class IP 65 01 - square flange 92x92mm, PN25 Stainless steel 1.4408 041 - float 64x142 for density> 0.7 Stainless steel 1.4571
Typ : 2829.1	Besta counter flange, steel (GP250GH) Flange: square flange 92 x 92 mm Dimensions: width V = 38 mm / sleeve Ø = 76.1 mm - Opening Ø = 65 mm Material: P250GH Hole circle: 92 mm Bolts: 4 x M12, 5.8, length = 30 mm Use of test actuator: - no - Manufacturer: Bachofen AG

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
A 01 04G1-300	
A 01 041	
A01 051 E15	
A012642	
A100329	
A415604	
A415605	
A415606	
A415610	
A415617	
A415630	
A415768	
A416128	
AA 01 041	
DAAE1610101	
DB 01-051	
A415605	Typ : A 01 041 Trimod Besta level switch Switching module : A => E-connection : Aluminum switch housing - with cable gland : M20 x 1.5 mm Microswitch : 1 x changeover contact, silver contact - Switching capacity 250 VAC / 30 VDC, 5.0 A Degree of protection: IP 65 Flange module : 01 => Process connection : flange 92 x 92 mm - Bolt circle : 92 mm, bore : 4 x 13 mm Gasket : Form C Nominal pressure : PN 25, max. 25 bar Media temperature : 0...+300 °C Ambient temperature : 0...+70 °C Float module : 041 => Liquid density : min. 700 kg/m³ Switching differential : fixed 12 mm Installation length : 223 mm Pole extension : not possible

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	material mediab. Parts : stainless steel Approvals : ABS, BV, CCS, DNV, GL, LRS - RINA, RMRS Manufacturer: Bachofen AG
M0104	Trimod Besta level switch - for pneumatic regulations Switch module: M => Housing: aluminum Tax connection: G 1/8 ", internal thread (BSPP) - Speed pressure: 1.4 bar - Output signal: 0.2 ... 1.0 bar Flanschmodule: 01 => Process connection: flange 92 x 92 mm - Loch circuit: 92 mm, hole: 4 x 13 mm - Poetry: Form C Nominal pressure: PN 25, max. 25 bar Media temperature: 1 ...+250 ° C Ambient temperature: 1 ...+80 ° C Swimmer module: 04 => Density of the liquid: min. 700 kg/m³ Regular range: 30 mm Installation length: 225 mm Performing extension: G1, G2, G3, possible Material Media Parts: stainless steel Admissions: ABS, BV, DNV, GL, LRS - Rina, RMRS
A 01 04	A415604 Trimod Besta level switch Switching module : A => E-connection : Aluminum switch housing - with cable gland : M20 x 1.5 mm Microswitch : 1 x changeover contact, silver contact - Switching capacity 250 VAC / 30 VDC, 5.0 A Degree of protection: IP 65 Flange module : 01 => Process connection : flange 92 x 92 mm - Bolt circle : 92 mm, bore : 4 x 13 mm - Gasket : Form C Nominal pressure : PN 25, max. 25 bar Media temperature : 0...+300 °C Ambient temperature : 0...+70 °C Float module : 04 => Liquid density : min. 700 kg/m³ Switching differential : fixed 12 mm Installation length : 223 mm Rod extension : G1, G2, G3, possible material mediab. Parts : stainless steel Approvals : ABS, BV, DNV, GL, LRS

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- RINA, RMRS Manufacturer: Bachofen AG
Trimod Besta Level Controller	010400/PH
4056566F022	
3056585F022	
1R6004000A2	
A 01 041	Trimod Besta level switch A415605 Switching module: A => E-connection: aluminum switch housing - with cable gland: M20 x 1.5 mm Microswitch: 1 x changeover contact, silver contact - Switching capacity 250 VAC / 30 VDC, 5.0 A Protection class: IP 65 Flange module: 01 => Process connection: flange 92 x 92 mm - Hole circle: 92 mm, bore: 4 x 13 mm Seal: Form C Nominal pressure: PN 25, max. 25 bar Media temperature: 0...+300 °C Ambient temperature: 0...+70 °C Float module: 041 => Density of the liquid: min. 700 kg/m³ Switching difference: fixed 12 mm Installation length: 223 mm Rod extension: not possible Material media-related Parts: stainless steel Approvals: ABS, BV, CCS, DNV, GL, LRS - RINA, RMRS Manufacturer: Bachofen AG
A 01 041	Trimod Besta level switch A - changeover switch, 250VAC-5A, Microswitch with silver contacts Cast aluminum housing, seawater resistant Protection class IP65 01 - Square flange 92x92mm, PN25 Stainless steel 1.4408 041 - Float 64x142 for density >0.7 Stainless steel 1.4571
Typ : AA 01 041	A415632 Trimod Besta level switch Switching module: AA (SIL2) => E-connection: aluminum switch housing - with cable gland: M20 x 1.5 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Microswitch: 2 x changeover contact, silver contact - Switching capacity 250 VAC / 30 VDC, 5.0 A Protection class: IP 65 Flange module: 01 => Process connection: flange 92 x 92 mm - Hole circle: 92 mm, bore: 4 x 13 mm - Seal: Form C Nominal pressure: PN 25, max. 25 bar Media temperature: 0...+300 °C Ambient temperature: 0...+70 °C Float module: 041 => Density of the liquid: min. 700 kg/m³ Switching difference: fixed 12 mm Installation length: 223 mm Rod extension: not possible Material media-related Parts: stainless steel Approvals: ABS, BV, DNV, GL, LRS, - RINA, RMRS Manufacturer: Bachofen AG
M 01 04	Trimod Besta level controller M - pneumatic proportional controller 0.2 to 1 bar, connections 1/8“ BSPP Cast aluminum housing, seawater resistant, 01 - square flange 92x92, PN25 Stainless steel 1.4408 04 - Float stainless steel 1.4571 for density >0.7
ASH002	"Measurement element Model:43API-FA42C/LAS.AG.PES.SB ESP Ref #: 5402431 B Origin : 2A 8902 Range :0-6 bar Element : Spiral Tube Length : 15' (Spare part of foxboro pneumatic pressure indicating controller)" KODU : 43X+PB-BA, SN:5402431 B
DAAE161 01 01 - level switch	Trimod Besta level switch DAA – 2x changeover switch, 250VAC-5A, microswitch with silver contacts Housing cast aluminum, seawater resistant protection class IP66/67 E161 – Cable entry with MS screw connection sealing surface with O-ring, IP68 01 - Square flange 92x92mm, PN25 stainless steel 1.4408 01 - Float 64x110 for density >0.8 stainless steel 1.4571
A 301 99K1-	Trimod Besta level switch A - Changeover switch, 250VAC-5A Microswitch with silver contacts Protection class IP65 301 - Flange DN80-PN10,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Sealing unit PP, union PVC 99 - Float 63x120 mm, PP for density >0.65 K1 – Straight rod extension A= ? (please specify when ordering!)
A 01 041	Trimod Besta level switch A - Switch with silver contacts 546.25 5A250VAC Housing: cast aluminum, seawater resistant Protection class IP65, SIL1 01 - Square flange 92x92, PN25, Stainless steel 1.4408 041 - Float stainless steel 1.4571 64x142mm for density >0.7
M 01 04G1	Trimod Besta level regulator M - pneumatic proportional controller 0.2 to 1 bar, connections 1/8" BSPP Housing made of cast aluminum, seawater resistant, 01 - Square flange 92x92, PN25 Stainless steel 1.4408 04 - Float stainless steel 1.4571 for density >0.7 G1 – Linkage extension, straight A = ??? mm (to be specified when ordering)
30aae4 01 053	
A.01-41	
2244	
A 01 04	
Mv-01-04	
13c 6780 B 8016a	
A 01 041	
P 01 04	
Ls400e	
Daa 01 04	
A01 141	
Daae161 01 01	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
A 01 051e15	
A 01 01	
A 01 051	
Daa 01 051	
Zk8 22c 041	
P01041	
Type A 01 04	
U3a 01 041	
Zk5 01 041	
2831 3	
Typ : Daae161 01 041	
M 01 04	
2315	
A 01 04g3	
Db 01 04	
I020-1c1cc-Pdxxx	
G3	
Xa80104g3	
In8 31n 041	
DB 01 051	Trimod Besta level switch DB - Switch, 30VDC-0.3A, Microswitches with gold-plated contacts Housing: cast aluminum, seawater resistant Protection class IP67, O-ring sealed 01 - Square flange 92x92mm, PN25 Stainless steel 1.4408 051 - Float 64x142 for density >0.75 Stainless steel 1.4571 with protective bellows Perbunan
T-2315	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
2831.3	
Zk8 01 04	
Haa 22c 041	
Typ : A 01 041	Tariff no .: 9026.1089 Country of origin: CH Weight (kg / h): 1,800 Trimod Besta level switch Switching module: A => E connection: aluminum switch housing - with cable gland: M20 x 1.5 mm Microswitch: 1 x change-over contact, silver contact - Switching capacity 250 VAC / 30 VDC, 5.0 A Protection class: IP 65 Flange module: 01 => Process connection: Flange 92 x 92 mm - Bolt circle: 92 mm, hole: 4 x 13 mm - Seal: Form C Nominal pressure: PN 25, max. 25 bar Media temperature: 0 ... + 300 ° C Ambient temperature: 0 ... + 70 ° C Float module: 041 => Density of the liquid: min. 700 kg / m^3
A01 051 E 141 Ip 65	
A 301 99k1	
U3a 01 04	
A 01 090	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.