

Ufi

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Ufi Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ufi Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
E Se22n Me 60 Micron	
CCH302FD1	EPB 22 N FC - CCH 302 FD 1 UFI EPB 22 - SOFIMA CCH 302 high-pressure filter insert collapse pressure= 21 bar FC - FD= 12µ inorganic fibers - 12 µm [c] N - 1= NBR seal Buna
CCH3012C2	EPB 21 F HB - CCH 301 2C 2 UFI EPB 21 - SOFIMA CCH 301 high-pressure filter insert collapse pressure= 210 bar HB - 2C= 7µ inorganic fibers (210 bar) F - 2= Viton seals
CCH302FC2	EPB 22 F FB - CCH 302 FC 2 UFI EPB - SOFIMA CCH 302 high-pressure filter insert collapse pressure= 21 bar FB - FC= 6µ inorganic fibers - 7µm [c] F - 2= FKM - Fluoroelastomer
CCH3012C2	EPB 21 F HB - CCH 301 2C 2 UFI EPB 21 - SOFIMA CCH 301 high-pressure filter insert collapse pressure= 210 bar HB - 2C= 7µ inorganic fibers (210 bar) F - 2= Viton seals
CCH1532T1	EPB 13 N HA - CCH 153 2T 1 EPB 13 - SOFIMA CCH 153 high-pressure filter insert

Ürün	Açıklama
	collapse pressure= 210 bar HA - 2T= 5µ inorganic fibers N - 1= NBR seals Buna
CRH015CD1	ERD 21 N CC - CRH 015 CD 1 UFI ERD 21 - SOFIMA CRH 015 Hydraulic filter insert Collapse pressure = 10 bar CC - CD= 10µ resin-impregnated paper N - 1= NBR seal Buna
CRE100FV1	ERA 52 N FD - CRE 100 FV 1 UFI ERA 52 - SOFIMA CRE 100 Hydraulic filter insert Collapse pressure = 10 bar FD - FV= 25µ inorganic fibers - 21 µm [c] N - 1= NBR seal Buna
CRH620FT1	ERD 62 N FA - CRH 620 FT 1 UFI ERD 620 - SOFIMA CRH620 hydraulic filter element Collapse pressure = 10 bar FA - FT= 5µ inorganic fibers - 5 µm [C] N - 1= NBR gasket
A-302	includes 6 replacement cartridges
CFA22SWCPE	CFA 22 SWCPE
CRE025CD1	ERA 32 N CC - CRE 025 CD 1 UFI ERA - SOFIMA CRE Hydraulic filter insert Collapse pressure= 3 bar CC - CD= 10µ resin-impregnated paper 1= NBR seal Buna
CCA151CD1	ESE 11 N CC - CCA 151 CD 1 UFI ESE 11 - SOFIMA CCA 151 SPIN-ON screw insert 11 - 151= type CC - CD= 10µ resin-impregnated paper N - 1= NBR seal Buna Collapse pressure= 4 bar
003.1654.6	EBE 12 FD - 30.1654 UFI EBE 12 - SOFIMA 30.1654 Ventilation filter insert for CBE12F12FD

Ürün	Açıklama
CCH1522C1	EPB 12 N HB - CCH 152 2C 1 UFI EPB 12 - SOFIMA CCH 152 high-pressure filter insert collapse pressure = 210 bar HB - 2C= 7µ inorganic fibers N - 1= NBR seal Buna
ASE22XFD	ASE 22 X FD UFI - SPIN-ON screw insert for CSE & CBS 22... ASE22= series X= without seal FD= fiberglass fiber 25µ
FA0000018	CBE12F12FD - 024.2037.4 UFI CBE - Sofima FA ventilation filter
RFM050028	RFM 050-FD-1-BB-6-01-SX FRA 41-B-10-BN-FC-01-WX UFI FRA 41 - SOFIMA RFM 050- return filter RFM=Max. operating pressure: 300 kPa (3 bar) Max. test pressure: 500 kPa (5 bar) Burst pressure: 1 MPa (10 bar) Fatigue test 0 - 300 kPa (0 - 3 bar) / 300,000 cycles Head: Aluminum Container: Nylon By-pass valve: standard 170 kPa (1.7 bar) Operating temperature: -25° - +110° C 41 - 050=Typ FD- FC= 12µ inorganic fibers - 12 µm [c] N - 1= NBR seals Buna B= Bypass 1.7 bar B= threaded connection (BSP) 10 - 6= G 1 1/4" 01= Hole for contamination indicator closed W - S= without filler screw X= not available
6CVA	6C SOFIMA - electric differential pressure display 2 bar (200kPa) Thread: M20 protection class IP65

Ürün	Açıklama
	cube plug according to DIN 43650
EBE12FD EBE 12 FD	UFI - Ventilation filter insert for CBE12F12FD
CCH802FC1	EPB 32 N FB - CCH 802 FC 1 UFI EPB 32 - SOFIMA CCH 802 High-pressure filter insert Collapse pressure = 21 bar FB - FC= 6µ inorganic fibers - 7µm [c] N - 1= NBR seal Buna
CCA302MN1	SE 22 N MF - CCA 302 MN 1 UFI ESE 22 - SOFIMA CCA 302 SPIN ON screw insert ESE 22 - CCA 302= Type MF - MN= 90µ metal mesh N - 1= NBR seal Buna Collapse pressure = 4 bar
CRH620FD1	ERD 62 N FC - CRH 620 FD 1 UFI ERD 62 - SOFIMA CRH 620 Hydraulic filter insert Collapse pressure = 10 bar FC - FD= 12µ inorganic fibers - 12 µm [c] N - 1= NBR seal Buna
ASE22XFD-	ASE 22 X FD UFI - SPIN-ON screw insert for CSE & CBS 22... ASE22= series X= without seal FD= fiberglass fiber 25µ
CCH802CD2	EPB 32 F CC - CCH 802 CD 2 UFI EPB 32 - SOFIMA CCH 802 High-pressure filter insert Collapse pressure = 21 bar CC - CD = 10µ resin-impregnated paper F - 2= FKM - Fluoroelastomer
Ese11nmf	
Frd31b08dncd71x	
Esa41b16wmf	
Ufi3151500	

Ürün	Açıklama
71	
Ese22ncchse01	
Esa21b04wmf	
Erd41nwrufi	
Epb32nfc	
Erd41nmdufi	
Epb32	
Esb11b03xme	
Era33ncc	
72	
Ufi3003400	
Erd41nfcufi	
Spm301fd1sb303xx	
Ufi3150100	
Ufi2341400	
Ufi2717500	
Erd41nfdufi	
Bpe 1xb06 Bn06xx	
Ufi3003200	
Ufi3093300	
Erd41nmeufi	
Ufi3096500	
Erd41nfbufi	
Bpm3011sb303xx	
Ufi3006600	
Ufi2436100	

Ürün	Açıklama
Ufi3151200	
Era41	
Erd41ncdufi	
Erd41nccufi	
Erd41nfaufi	
Ufi2667000	