Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Uni Gerate

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Uni Gerate Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Uni Gerate Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Ts1500	AR031968 PCB TS1500 230VAC / DC, cpl. for MG ... A ..
AR029019	Electro-pneumatic valve, normally closed-NC, Class A, type examination certificate according to gas appliance Gas appliance regulation EU / 2016/426, test basis EN 16678 Type: 10-4-EPVA 250-4.02.32.66 Prod.-ID .: CE0085AQ0211 Pressure range: 0 - 10 bar Nominal size: DN 250 Flange connection: PN 16 Medium: natural gas Media temp .: -20 ° C to + 60 ° C Ambient temp .: -20 ° C to + 60 ° C Installation position: vertical or horizontal drive Casing material: EN-JS1049 (GGG40.3) Inner parts: St / Ms / Al / stainless steel Sealing elements: NBR Spindle seal .: lip ring P. drive: KA160 Control pressure: 4bar to 10bar Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN 5 Casing material: Ms Sealing elements: NBR Magnet drive: 0801 Electrical power: 16W Degree of protection: IP65 Approval: EC type test. according to EN 16678 Electr.-Span .: 24 VDC Limit switch: 2 pieces mechanical Make: Schaltbau Type: S870 W1 G4R Contact: Gold Valve position: open / closed

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Electrical connection: DIN VDE 0627 / IEC 61984 Electr.-Span .: 24 VDC 1pcs spare parts for pneumatic valve Type: 10-4-EPVA 250-4.02.32.66 Serial number: NT071 Item number: AR029019 Comm.-No .: KA2006-05-091 Medium: natural gas
AR018317	Electro-magnetic valve 3/2-way valve, normally closed, with threaded connection Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN 5 Geh.-Werkst .: Ms Sealing elements: NBR Magnet drive: 0801 Electrical power: 16W Degree of protection: IP65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type test. according to EN 16678 Electr.-Span .: 24 VDC
Pilot valve F. Safety shut off valve 1	
Safety Shut off vave1 closed	
UV2.03.05	
UV2.03.04	
UV2.03.03	
UV2.02.06	
UV2.02.05	
10-MEA 15N	
10-MEA 20N	
10-MEA 25N	
10-EVSA 5-4.04 G 1/2	Solenoid valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/EU/2016/426, test basis EN 16678 Type: 10-EVSA 5-4.04 Product ID: CE0085AR0256 Pressure range: 0 - 10 bar Passage: 12mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal width: G 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Internal parts: St/Ms/Al/stainless steel Sealing elements: NBR Spindle seal: lip ring Solenoid Drive: MG008-2 Electrical power: 30 W Degree of protection: IP54 Electrical connection: cable gland Electrical voltage: 24 VDC
25-EVSO 5-4R.04.29 G 1/2	Solenoid valve, normally open-NO, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 16678 Type: 25-EVSO 5-4R.04.29 Product ID: CE0085AS0561 Pressure range: 0 - 25 bar Passage: 12mm Nominal width: G 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Internal parts: stainless steel Sealing elements: NBR Spindle seal: lip ring Solenoid Drive: MG008-2 Electrical power: 30 W Degree of protection: IP54 Electrical connection: cable gland Electrical voltage: 24 VDC
UV2.03.05	
UV2.03.04 Uni Valve	
UV2.03.03 Uni Valve	
UV2.02.06 Uni Valve	
UV2.02.05 Uni Valve	
1-EVA 5-4.09	Replaces type: 1-EVA 5-4.01 Solenoid valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Product ID: CE0085AQ0563 Pressure range: 0 - 1 bar Passage: 12mm Nominal width: G 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: 1.4408 Internal parts: St/Ms/Al/stainless steel Sealing elements: FKM (Viton) Solenoid Drive: MG005-3 Electrical power: 15 VA Degree of protection: IP54 Electrical connection: cable gland Electrical voltage: 230 VAC
1-EVO 5-4R.09	Replaces type: 1-EVO 5-4R.01 Solenoid valve, normally open-NO, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 16678 Prod.-ID-No. CE0085AS0561 Pressure range: 0 - 1 bar Passage: 12mm Nominal width: G 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Internal parts: St/Ms/Al/stainless steel Sealing elements: FKM (Viton) Magnetic drive: MG004 Electrical power: 10 VA Degree of protection: IP54 Electrical connection: cable gland Electrical voltage: 230 VAC
AR007937-01	Spare parts for solenoid valve Type: 05-EVA 125H-4.Av.00.32 Prod. No.: PT238 Article no.: AR011639 Comm. No.: KA2008-05-154 Medium: natural gas consisting of: Solenoid Drive: MG019-A2 Electrical power: 1500/90 W Degree of protection: IP54 Electrical connection: cable gland Valve control: TS1500 Electrical voltage: 230 VAC

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
05 EVA 125H 4	MG019-A2 1500/90W 230VAR
AR007937-01 (SN042)	Spare parts for solenoid valve Type: 05-EVA 125H-4.Av.00.32 Prod. No.: SN042 Article no.: AR011639 Comm. No.: KA2005-04-098 Medium: natural gas consisting of: Solenoid Drive: MG019-A2 Electrical power: 1500/90 W Degree of protection: IP54 Electrical connection: cable gland Valve control: TS1500 Electrical voltage: 230 VAC
AR011710	Type: 12-EVDF 5R.Xn.W.Ü.P.14.29 Pressure range: 0 - 12 bar Nominal width: G 1/2 Medium: hot air Media temp.: -20°C to +200°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4301 (VA) Internal parts: stainless steel Sealing elements: PTFE/FKM (Viton) Spindle seal: bellows Magnetic drive: MG018 Solenoid encapsulated with MG mounting bracket Electrical power: 125 watts Degree of protection: IP65 Type of protection: II3G Ex nA IIC T4 Gc (Zone 2) UNI0665X CE Electrical connection: Ex cable gland Electrical voltage: 220 VDC
AR048593	Solenoid valve 3/2-way version safety shut-off device, normally open or closed, with threaded connection Type: 12-EVDF 3R.Xn.W.Ü.P.09.29 Pressure range: 0 - 12 bar Nominal width: G 3/8 Medium: air Media temp.: 0°C to +200°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4301 (VA)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Internal parts: stainless steel Sealing elements: FKM (Viton) Spindle seal: bellows Valve disc seal.: FKM (Viton) Magnetic drive: MG016 Solenoid encapsulated with MG mounting bracket Electrical output: 90 W Electrical connection: Ex cable gland Degree of protection: IP 65 Type of protection: II3G Ex nA IIC T4 Gc (Zone 2) UNI0665X CE Electrical voltage: 220 VDC +10%, -15% according to SLV 3640298 index d
10.LC.GN Gas Flow adjusting valve DN10	DN 10 PB 10 Bar 3/8" Seri No: FA 081-3
15.LC.AS Air Flow Adjusting Valve DN15	DN 15 PB 10 Bar 1/2"
65.LC.GN Natural Gas Flow Regulating Valve	DN65 MEA 25NH-4 FA1084-3
50.LC.GN Natural Gas Flow Regulating Valve	DN50 MEA 20-4 FA078-2
40.LC.GN Natural Gas Flow Regulating Valve	DN40 MEA 15-4 FA079-2
AR068666	Electric solenoid valve, normally open-NO, class 0, Type test certificate according to the Pressure Equipment Directive 97/23/EC, test basis prEN 16678, DIN 3394-1, DIN EN 13611 Type: 55-EVSO 15NH-4.R.P.Xn.14.29.32.95.99 TÜV test report number: V490 2015 B2 Pressure range: 0 - 55 bar Nominal diameter: DN 40 Flange connection: PN 100 Medium: natural gas Media temperature: -20°C to +250°C Ambient temp.: -20°C to +60°C Installation position: stationary drive Case material: 1.4571 Internal parts: stainless steel Sealing elements: FFKM/PTFE Spindle seal: lip ring Magnetic drive: MG020.1 Solenoid coil cast with MG mounting bracket Electrical power: 250 watts Protection class: IP65 Type of protection: II3G Ex nA IIC T4 Gc (Zone2)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	UNI0665XCE Electrical connection: Ex cable gland Valve control: GLE250 Electrical voltage: 220 VDC +10%/-15% Limit switch: 2 pieces inductive Manufacturer: PEPPERL+FUCHS Type: NCB5-18GM40-Z0-3G-3D-10m Valve position: 2 x closed Type of protection: II 3G Ex nA IIC T6 Gc(Zone2) Electrical connection: 10 m cable end Electrical voltage: 5-60 VDC see DPSLV 00000652c Item 1 - (in progress Siemens Energy Version)
1-4-EPVA 200H-4.Z.00.32.66.99	Electro-pneumatic valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 AR069515 Type: 1-4-EPVA 200H-4.Z.00.32.66.99 Prod. Ident. No.: CE0085AQ0211 Pressure range: 0 - 1 bar Nominal diameter: DN 200 Flange connection: PN 10 Medium: ... Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: EN-JL1040 (GG25) Seat material 1.4571 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Spindle seal: lip ring P. drive: KA160 Control pressure: 4bar to 10bar Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN5 Case material: Ms Sealing elements: NBR Magnetic drive: 3803 Electrical power: 18VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type test. according to EN 16678 Electrical voltage: 230 VAC Limit switch: 2 pieces mechanical Manufacturer: Schaltbau Type: S870 W1 G1R Contact: Silver Valve position: open/close Electrical connection: DIN VDE 0627/IEC 61984

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Electrical voltage: 230 VAC with hydraulic opening delay Special: with measuring connection G 1/2 and locking screw. in the entrance and exit on both sides with air filter G 1/4
AR061901	Electric solenoid valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-EVA 5-4.P.09 Prod. Ident. No.: CE0085AQ0563 Pressure range: 0 - 1 bar Passage: 12mm Nominal width: G 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: 1.4408 Internal parts: stainless steel Sealing elements: FKM (Viton) Magnetic drive: MG005-3 Solenoid coil cast Electrical power: 15 VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Electrical voltage: 230 VAC
1-4-EPVA 200H-4.02.32.66.99	Electro-pneumatic valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Projekt: ZO058 Type: 1-4-EPVA 200H-4.02.32.66.99 Prod. Ident. No.: CE0085AQ0211 Pressure range: 0 - 1 bar Nominal diameter: DN 200 Flange connection: PN 10 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: EN-JL1040 (GG25) Seat material 1.4571 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Spindle seal: lip ring P. drive: KA160 Control pressure: 4bar to 10bar Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN5

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Case material: Ms Sealing elements: NBR Magnetic drive: 3803 Electrical power: 18VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type test. according to EN 16678 Electrical voltage: 230 VAC Limit switch: 2 pieces mechanical Manufacturer: Schaltbau Type: S870 W1 G1R Contact: Silver Valve position: open/close Electrical connection: DIN VDE 0627/IEC 61984 Electrical voltage: 230 VAC Special: with measuring connection G 1/2 and locking screw. in the entrance and exit on both sides with air filter G 1/4
AR069832	Electro-pneumatic valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-4-EPVA 200-4.02.32.66.99 Prod. ID no.: CE0085AQ0211 Pressure range: 0 - 1 bar Nominal diameter: DN 200 Flange connection: PN 10 Medium: ... Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: EN-JS1049 (GGG40.3) Seat material 1.4571 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Spindle cover: lip ring P. drive: KA 160 Control pressure: 4bar to 10bar Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN5 Case material: Ms Sealing elements: NBR Magnetic drive: 3803 Electrical power: 18VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type test. according to EN 16678 Electrical voltage: 230 VAC Limit switch: 2 pieces mechanical

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Manufacturer: Schaltbau Type: S870 W1 G1R Contact: Silver Valve position: open/close Electrical connection: DIN VDE 0627/IEC 61984 Electrical voltage: 230 VAC Special: With measuring connection G 1/2 and locking screw. in the entrance and exit on both sides. With air filter G 1/4
AR052349	Spare parts for pneumatic valves Type: 1-4-EPVA 200-4.00.32.66.99 Product no.: WT216-3 Item no.: AR052349 Comm. No.: KA2014-05-161, Pos. 2 Medium: natural gas consisting of: E-kit 1a 1-4-EPVA 200-4. 02-04, Ends.-Anb. Complete set Item 200 1pc. Valve plate PVT 200 complete. (Items 201, 241, 400, 403/5, 906, 901/3, 943) Item 402 1pc. VG seal Item 212 1pc. Spindle guide complete. (Item 403/4, 404, 405) Item 403/3 1pc. O-ring Item 217 1pc. Drive piston Item 403/2 1pc. O-ring Item 403/1 1 piece O-ring Item 216 1pc. Lead management complete. (Item 208) Item 403/4 1pc. O-ring (end attachment) Operating instructions: 221.100.003 DE; 221.100.004 EN
DN200	GAS VALVE CLOSURE
4-4-EPVA 150-4.0032.66.99	"FSV1902 A/B SEAT TİP, 4-4-EPVA 150-4.0032.66.99 MODEL
1-EVA 5-4.Xme.04	"UNI" SOLENOID VALVE 110V, 50 Hz, IP 65 , G1/2, 1BAR FILE NO. 1700 REF. UNI MODEL: 1-EVA 5-4.Xme.04 WITH INCORPURATED STRAINER EXPLOSION PROOF II2G EX MBE T5 GB (ZONE 1), TAG NO:90-150- UY-1443/ UY1448
1-EVO 5.4.RXme.09.29	1-EVO 5.4.RXme.09.29 10VA CURRENTLESS OPEN FOR TAG NO:90-150-UY1447/UY1449

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
AR069515	Electro-pneumatic valve, normally closed-NC, class A, Type test certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-4-EPVA 200H-4.Z.02.32.66.99 Replaces type: 1-4-EPVA 200H-4.Z.00.32.66.99 Prod. Ident. No.: CE0085AQ0211 Pressure range: 0 - 1 bar Nominal diameter: DN 200 Flange connection: PN 10 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical or horizontal drive Case material: 5.1301 Seat material 1.4571 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Spindle seal: lip ring P. drive: KA160 Control pressure: 4bar to 10bar Control valve: 10-EVD 2/2401 Nominal width: G 1/4; DN5 Case material: Ms Sealing elements: NBR Magnetic drive: 3803 Electrical power: 18VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type test. according to EN 16678 Electrical voltage: 230 VAC Limit switch: 2 pieces mechanical Manufacturer: Schaltbau Type: S870 W1 G1R Contact: Silver Valve position: open/close Electrical connection: DIN VDE 0627/IEC 61984 Electrical voltage: 230 VAC with hydraulic opening delay Special: with measuring connection G 1/2 and locking screw. in the entrance and exit on both sides with air filter G 1/4
AR067094	Electric solenoid valve, normally open-NO, Type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 16678 Type: 6-EVO 5-4R.P.Xn.09.29 Replaces type: 6-EVO 5-4R.P.Xn.04.29 Product ID no. CE0085AS0561 Pressure range: 0 - 6 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Passage: 12mm Cutting ring screw connection: DIN 2353-DL12A-G1/2-St Medium: natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Internal parts: stainless steel Sealing elements: FKM (Viton) Magnetic drive: MG005-3 Magnetic coil cast Electrical output: 15 VA Protection class: IP65 Ignition protection type: II3G Ex nA IIC T4 Gc (Zone 2) UNI0665 X CE Electrical connection: Ex cable screw connection Electrical voltage: 24 VDC
4-4-EPVA 150H-4.02.32.66.99	Electro-pneumatic valve, normally closed-NC, Class A, Type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Product ID no.: CE0085AQ0211 Pressure range: 0 - 4 bar Nominal diameter: DN 150 Flange connection: PN 10 - PN 16 Medium: natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 5.3103 Internal parts: St/Ms/Al/stainless steel Sealing elements: NBR Spindle seal: lip ring P. drive: KA 200 Control pressure: 4 bar to 10 bar Control valve: 10-EVD 2/2401 Nominal diameter: G 1/4; DN 5 Housing material: Ms Sealing elements: NBR Magnetic drive: 3803 Electrical power: 18VA Protection class: IP 65 Electrical connection: DIN EN 175301-803A with LED Approval: EC type examination according to EN 16678 Electrical voltage: 230 VAC Limit switch: 2 pcs. mechanical Make: Schaltbau Type: S870 W1 G1R Contact: Silver

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Valve position: Open/Closed Electrical connection: DIN VDE 0627/IEC 61984 Electrical voltage: 230 VAC Special: Limit switch under the housing
6-EVO 5-4R	
AR055940	Electric solenoid valve, normally closed-NC, Class A, Type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 05-EVA 125H-4.Av.02.32 Replaces type: 05-EVA 125H-4.Av.00.32.99 Product ID no.: CE0085AQ0563 Pressure range: 0 - 0.5 bar Nominal diameter: DN 125 Flange connection: PN 10 - PN 16 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical drive Housing material: 5.3104 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Magnetic drive: MG019-A2 Electrical output: 1500/90 W Protection class: IP54 Electrical connection: cable screw connection Valve control: TS1500 Electrical voltage: 230 VAC With measuring connection G 1/2 and locking screw in the inlet and outlet on both sides.
AR009262	Electric solenoid valve, normally closed-NC, Class A, Type examination certificate according to Gas Appliances Regulation EU/2016/426, test basis EN 161 Type: 03-EVA 15-4.02 Replaces type: 01-EVA 15-4.02 Product ID no.: CE0085AQ0563 Pressure range: 0 - 0.3 bar Passage: 34 mm Nominal width: G 1 1/2 Medium: natural gas Media temp.: -20°C to +60°C Ambient temp.: -20°C to +60°C Installation position: vertical drive Housing material: 5.3103 Internal parts: St/Ms/Al/stainless steel

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Sealing elements: NBR Magnetic drive: MG010 Electrical output: 40 W Protection class: IP54 Electrical connection: cable gland Electrical voltage: 230 VAC With measuring connection G 1/4 and locking screw in the inlet on both sides.
#160-EVS.3.R.P.09.29.95.99	Solenoid Valve NO PN200 / G3/8"
# 55-4-EPVO 15N-4.R.14.29.32.95.99	SOLENOID VALVE
VALVE_SOLENOID; CONFIGURATION: 2/2-WAY;	ELECTRICAL RATING: 110VDC 160W;DESIGN RATING: 40BAR; PROCESS FLUID: NATURAL GAS; MFR: UNI-G ERATE: MPN:40-EVF 5N: MFR: SIEMENS LTD: MPN: A2A50186929: APPLICATION: NG SKID;REF: BEZ-URP14.29.32.95.99
AR068499	Electric solenoid valve, normally closed-NC, Class A, type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-EVA 5-4.Xme.09.78.99 Prod. ID No.: CE0085AQ0563 Pressure range: 0 - 1 bar passage: 12 mm Nominal diameter: G 1/2 Medium: Natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Interior parts: stainless steel Sealing elements: FKM (Viton) Magnetic drive: MG005A7m Electrical power: 30/3 W Protection class: IP65 Ignition protection type: II2G Ex mbe IIC T5 Gb (Zone 1) Electrical connection: Ex cable gland M20x1.5 Electrical voltage: 24 VDC Rated current: 1.648 A Limit switch: 2 inductive Manufacturer: Pepperl & Fuchs Type: NJ2-11-NG Valve position: Open/Closed Ignition protection type: II2G Ex ia IIC T6 (Zone1) Electrical connection: 2m cable end Electrical voltage: 8 VDC (Isolation amplifier provided by customer) Special: Thread reduction G 1/2A x 1/2 NPT I VA

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	additional length per valve: 50 mm (2 x +25mm)
AR048593 - 3/2-way solenoid valve	3/2-way solenoid valve safety shut-off device, open or closed when de-energized, with threaded connection Type: 12-EVDF 3R.Xn.W.Ü.P.09.29 Pressure range: 0 - 12 bar Nominal diameter: G 3/8 Medium: Air Media temperature: -20°C to +200°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4301 Interior parts: stainless steel Sealing elements: FKM Spindle seal: bellows Valve disc seal: FKM Magnetic drive: MG016 magnetic coil cast with MG mounting bracket Electrical power: 90 W Protection class: IP 65 Type of protection: II3G Ex nA IIC T4 Gc (Zone 2) UNI0665 X CE Electrical connection: Ex cable gland Electric voltage: 220 VDC + 10%/- 15% according to SLV 3640298 Index d
12-EVDF 3R.Xn.W.Ü.P.09.29	AR048593 3/2-way solenoid valve Safety shut-off device, normally open or closed, with threaded connection Type: 12-EVDF 3R.Xn.W.Ü.P.09.29 Pressure range: 0 - 12 bar Nominal diameter: G 3/8 Medium: Air Media temperature: -20°C to +200°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4301 Internal parts: stainless steel Sealing elements: FKM Spindle seal: bellows Valve disc seal: FKM Magnetic drive: MG016Xn Magnet coil encapsulated with MG mounting bracket Electrical power: 90 W

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Protection class: IP 65 Type of protection: II3G Ex ec IIC T4 Gc X (Zone 2) TUV-A 2025-TAD-0025 Electrical connection: Ex-cable gland Electrical voltage: 220 VDC + 10%/- 15%
AR061753	Electric solenoid valve, normally closed-NC, Class A, type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-EVA 5-4.09 Replaces type: 1-EVA 5-4.01 Prod. ID No.: CE0085AQ0563 Pressure range: 0 - 1 bar passage: 12 mm Nominal diameter: G 1/2 Medium: Natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 Internal parts: St/Ms/Al/Stainless steel Sealing elements: FKM (Viton) Magnetic drive: MG005-3 Electrical power: 15 VA Protection class: IP54 Electrical connection: cable gland Electrical voltage: 230 VAC
AR006668-05	to UNI-Pos. 1 acceptance test certificate EN 10204 3.1 Function - leak and strength testing incl. APZ 3.1 for the housing material (provided as a PDF file)
25-EVSO 5-4R.fr.Xde.04.29.70	AR050307 Solenoid valve, normally open-NO, type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 16678 Type: 25-EVSO 5-4R.fr.Xde.04.29.70 Prod. Ident. No.: CE0085AS0561 Pressure range: 0 - 25 bar passage: 12 mm Nominal diameter: G 1/2 Medium: Natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 1.4408 (VA) Interior parts: stainless steel

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Sealing elements: NBR spindle seal: lip ring Magnetic drive: MG008x Electrical power: 30 W Protection class: IP65 With rain cover for outdoor installation Ex marking: II2G Ex db eb IIC T5 Gb (Zone 1) II2D Ex tb IIIC T95°C Db (Zone 21) Electrical connection: Ex cable gland M20x1.5 Electrical voltage: 24 VDC Limit switches: 2 pcs. mechanical Brand: Bartec Type: 07-2511-834052U1 Contact: Gold Valve position: Open/Closed Ex marking: Ex II 2G Ex db IIC T6, T5 Gb Ex II 2D Ex tb IIIC T80°C, T95°C Db Electrical connection: 3m cable end Ölflex Heat 145C MC Electric voltage: 24 VDC
S870W1G4R	limit switch
AR065841	Electro-pneumatic valve, normally closed-NC, Class A, type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 161 Type: 1-4-EPVA 30NH-4.02.32 Prod. Ident. No.: CE0085AQ0211 Pressure range: 0 - 1 bar Nominal diameter: DN 80 Flange connection: PN 10 - PN 40 Medium: Natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: 5.3103/5.3104 Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Spindle seal: lip ring P-drive: KA70 Control pressure: 4 bar to 10 bar Control valve: 10-EVD 2/2401.Xme Nominal diameter: G 1/4; DN 5 Housing material: Ms Sealing elements: NBR Magnetic drive: 4271 Electrical power: 8.9W Protection class: IP66 Ex marking: II2G Ex eb mb IIC T4/T5 Gb (Zone 1)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Electrical connection: Ex cable gland M20x1.5 Approval: EC type-examination according to EN 16678 KEMA 98 ATEX 4452X Electrical voltage: 24 VDC with measuring connection G 1/4 and locking screw. in the entrance and exit on both sides.
200 1-4	ELEKTRO-PNEUMATISCHES VENTIL
UNI GERATE 200 1-4 EPVA 200-4 PN 10 KA160 4-10 / 10-EVD 2/2401 IP 65 (ZONE 2 AND 22)	
1-EVO 7-4R.P.01	Solenoid valve, normally open-NO, Type examination certificate according to the Gas Appliances Ordinance EU/2016/426, test basis EN 16678 Type: 1-EVO 7-4R.P.01 Prod. Ident. No.: CE0085AS0561 Pressure range: 0 - 1 bar Passage: 18 mm Nominal diameter: G 3/4 Medium: Natural gas Media temperature: -20°C to +60°C Ambient temperature: -20°C to +60°C Installation position: vertical or horizontal drive Housing material: CC493K Internal parts: St/Ms/Al/Stainless steel Sealing elements: NBR Magnetic drive: MG005-3 Magnet coil encapsulated Electrical power: 15 VA Protection class: IP65 Electrical connection: DIN EN 175301-803A with LED Electrical voltage: 230 VAC
1-EVO 7-4R G3/4	
seal, O-ring, Gasket vs.	for 40-EVSO 5N-4R
40-EVF 5N.Xn	
4-EVSA 25NH-4.Xde.02.33.71	AR051217 Solenoid valve, normally closed-NC, class A type: 4-EVSA 25NH-4.Xde.02.33.71 type examination certificate acc. to EC Gas Appliance Regulation EU/2016/426, basis of type examination EN 161 prod.-ident.-no.: CE0085AR0256 pressure range: 0 - 4 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	nominal size: DN 65 flange connect.: ANSI 150 lbs size: acc. to DIN medium: natural gas medium temp.: -20°C to +60°C ambient. temp.: -20°C to +60°C install. of valve: vertical or horizontal drive valve housing: 5.3103/5.3104 inner parts: steel/brass/alum./stainless steel Seal elements: NBR spindle sealing: lip ring magnet drive: MG018x electrical power: 125 W Protect class: IP65 Ex marking: II2G Ex db eb IIC T5 Gb (Zone 1) II2D Ex tb IIIC T95°C Db (Zone 21) electr.-connect. ex-cable gland voltage: 230 VAC Limit switch: 1 pc. mechanical Brand: Bartec type: 07-2511-734052U1 contact: silver valve position: closed Ex marking: Ex II 2G Ex db IIC T6, T5 Gb Ex II 2D Ex tb IIIC T80°C, T95°C Db electr.-connect.: 3m cable end Ölflex Heat 145C MC voltage: 230 VAC with threaded hole G 1/4 and plugs in entry and exit on both sides
1-EVO 15NH-4R.Xde.02.33	AR051218 Solenoid valve normally open-NO type: 1-EVO 15NH-4R.Xde.02.33 type examination certificate acc. to EC Gas Appliance Regulation (EU/2016/426) test basis DIN EN 16678 prod. ident. no.: CE0085AS0561 pressure range: 0 - 1 bar nominal size: DN 40 flange connect.: ANSI 150 lbs size: acc. to DIN medium: natural gas medium temp.: -20°C to +60°C ambient temp.: -20°C to +60°C install. of valve: vertical or horizontal drive valve housing: 5.3103/5.3104 inner parts: steel/brass/alum./stainless steel Seal elements: NBR magnet drive: MG014x electrical power: 70 W

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Protect class: IP65 Ex marking: II2G Ex db eb IIC T5 Gb (Zone 1) II2D Ex tb IIIC T95°C Db (Zone 21) electr.-connect.: ex-cable gland voltage: 24 VDC with threaded hole G 1/4 and plugs in entry and exit on both sides
1-4-EPVA 150-4	
1-EVA 5-4.09	AR061753 Solenoid valve, normally closed-NC, class A type examination certificate acc. to EC Gas Appliance Regulation (EU/2016/426), basis of type examination EN 161 type: 1-EVA 5-4.09 replacement for type: 1-EVA 5-4.01 Product identification number: CE0085AQ0563 pressure range: 0 - 1 bar passing: 12 mm nominal size: G 1/2 medium: natural gas medium temp.: -20°C to +60°C ambient temp.: -20°C to +60°C install. of valve: vertical or horizontal drive valve housing: 1.4408 (VA) inner parts: steel/brass/alum./stainless steel Sealing elements: FKM (Viton) magnet drive: MG005-3 electrical power: 15 W protection class: IP54 electrical connection: cable gland voltage: 230 VAC
1-4-EPVA 200-4	Electro-pneumatically controlled gas safety shut-off valve
30-4-EPV 12N	
1-4-EPVA 200H-4	
704020-GDA3RV	
MRK Ro Ma 25N-4.W.00.32	AR016306 Flow control butterfly valve normally closed-NC type examination certificate acc. to EC Gas Appliance Regulation EU/2016/426, test basis EN 16678 intermediate exhaust flap actuators for control without zero obturation flow on both sides

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	type: MRK Ro Ma 25N-4.W.00.32 prod. ident. no.: CE0085AR0408 pressure: 0 - 0,15 bar nominal size: DN 65 flange connect.: PN 10 - PN 40,Ansi 300lbs medium: air medium temp.: -20°C to +60°C ambient temp.: -20°C to +60°C install. of valve: vertical drive in vertical pipeline butterfly ring: 5.1301 sealing disc: steel design: through passage version spindle: stainless steel inner parts: steel/brass/aluminium/stainless steel seal elements: NBR magnet drive: MG012 electr.-power: 50 W protect. class: IP 54 electr.-connect.: cable gland voltage: 230 VAC
02-Eva 15n-4.00.32 (Ar009289)	Note: Article AR009289 replaces transaction item AR009280, order no. KW173-2 Electric solenoid valve, normally closed NC, class A, Type test certificate according to the Gas Appliance Ordinance EU / 2016/426, testing standard EN 161 Type: 02-EVA 15N-4.00.32 Product ID No .: CE0085AQ0563 Pressure range: 0 - 0.2 bar Nominal diameter: DN 40 Flange connection: PN 10 - PN 40 Medium: natural gas Media temp .: -20 ° C to + 60 ° C Ambient temp .: -20 ° C to + 60 ° C Installation position: stationary drive Geh.-Material: EN-JL1040 (GG25) Internal parts: St / Ms / Al / stainless steel Sealing elements: NBR Magnetic drive: MG012 Electric power: 50 W Protection class: IP54 Electr. Connector: Cable gland Electr. Voltage: 230 VAC
Typ: Mrk We 300ü200.05.32.55.99	Type: MRK We 300Ü200.05.32.55.99 Rate control flap, with free shaft end (We) Wafer Actuators without zero closure Flow on both sides

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Type: MRK We 300Ü200.05.32.55.99 Pressure range: 0 - 4 bar Nominal diameter: DN 300 Flange connection: PN 6 - PN 10 Medium: air Media temp .: -20 ° C to + 200 ° C Ambient temp .: -20 ° C to + 60 ° C Installation position: arbitrary Geh.-Material: EN-JL1040 (GG25) Flap plate: Al Execution: resounding Flap shaft: stainless steel Inner parts: St / Ms / Al / stainless steel Sealing elements: FKM (Viton) with special-rule-flap-plate Special: for delta p max. = 1 bar
Typ: Mrk Ro We 125-4.05.38.55	Flow control valve,, Type examination certificate according to the Gas Appliance Ordinance EU / 2016/426, test standard EN 16678 with free shaft end (We) Wafer Actuators without zero closure Flow on both sides Type: MRK Ro We 125-4.05.38.55 Product ID no .: CE0085AR0408 Pressure range: 0 - 4 bar deltap max .: 1 bar Nominal diameter: DN 125 Flange connection: PN 10 - PN 16 150lbs ANSI, 300 lbs Medium: coke gas Media temp .: -20 ° C to + 60 ° C Ambient temp .: -20 ° C to + 60 ° C Installation position: arbitrary Geh.-Material: EN-JL1040 (GG25) Flap plate: Al Execution: resounding Flap shaft: stainless steel Internal parts: non-metallic Sealing elements: FKM (Viton) Spindle seal .: lip ring with special-rule-flap-plate
20-4 EPVA 15N	Electro-pneumatically controlled gas safety shut-off valve

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.