

## Unitronics

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Unitronics** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Unitronics Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



| rn   | Aıklama   |
|--|--|
| <a href="#">Vision V430-J-T2</a>                   |  |
| <a href="#">V120-22-UN2</a>                        | V120-22 OPLC,12/12IO,2 UNIV                      |
| <a href="#">V200-18-E3XB</a>                       | IO MODULE,18/17IN/OUT,4UNI/AN,IS                 |
| <a href="#">450.72.UNT.10</a>                      | USL-070-B05 HMI 7"                               |
| <a href="#">450.71.UNT.10</a>                      | USC-B5-TR22 PLS 2 AI-10DI , 12 TO- 8 RO          |
| <a href="#">1X2X0,34MM2 BUS CAN UNITRO.2170263</a> | Cable  |
| <a href="#">V570-57-T20B-J</a>                     | Vision V570 COLOR OPLC, WL,5.7", TOUCH, no Frame |
| <a href="#">V1210-T20Bj</a>                        | V1210 COLOR OPLC,12.1", TOUCH, NoB               |
| <a href="#">V570-57-T20-B</a>                      | V570 COLOR OPLC, WL,5.7", TOUCH                  |
| <a href="#">EX-A2X</a>                             | Expansion adapter, isolated                      |
| <a href="#">IO-AI8</a>                             | 8 Analog Input module                            |
| <a href="#">IO-TO16</a>                            | 16 digital outputs module                        |
| <a href="#">SM35-J-R20</a>                         | SM35-R20,3.5",12/8 I/O,2A,1HS                    |
| <a href="#">SM35-J-T20</a>                         | SM35-T20,3.5",12/8 I/O,2A,3HS                    |
| <a href="#">V200-18-E3XB</a>                       | IO MODULE,18/17IN/OUT,4UNI/AN,IS                 |

|   |  |
|---|--|
| <a href="#">V200-18-E1B</a>   | IO MODULE,16/10 IN/RELAY OUT,ISO             |
| <a href="#">V200-18-E1B</a>   | IO MODULE,16/10 IN/RELAY OUT,ISO             |
| <a href="#">V130-33-RA22</a>  | V130-RA22 OPLC,WL DIS,12/8 IO                |
| <a href="#">V100-17-CAN</a>   | MODULE,CANbusINTERFACE FORV130               |
| <a href="#">V200-18-E3XB</a>  | IO MODULE,18/17IN/OUT,4UNI/AN,IS             |
| <a href="#">UIA-0800N</a>   | UniStream IO, 8AI,NO ISO                     |
| <a href="#">UID-0808T</a>   | UniStream IO 8DI,8TO,24V                     |
| <a href="#">V570-57-T20B-J</a>                                      | V570 COLOR OPLC,WL,5.7",TOUCH - NO LCD FRAME |
| <a href="#">EXL-CAB1000</a>   | CABLE,XL-EXP-PLC,RJ45-RJ45,10m               |
| <a href="#">BUS PB FD P A - : 2170822</a>                           |  |
| <a href="#">V130-33-T38</a>   | V130-T38 OPLC,WL DIS,22I,16O,2A              |
| <a href="#">EX-RC1</a>  | REMOTE I/O ADAPTER                           |
| <a href="#">UNITRONİCS V200-18-E3/4XB</a>                           |  |
| <a href="#">V200-18-E3XB</a>  | IO MODULE,18/17IN/OUT,4UNI/AN,IS             |
| <a href="#">V200-18-E4XB</a>  | IO MODULE,18/17IN/TOUT,4UN/AN,IS             |
| <a href="#">IO-D16A3-TO16</a>                                       | XL-EXP,16I,3AI,16TO                          |
| <a href="#">IO-TO16</a>   | 16 digital outputs module                    |
| <a href="#">EX-D16A3-TO16</a>                                       | XL-EXP,ADPTER,16I,3AI,16O                    |
| <a href="#">IO-AI4-AO2</a>  | 4 in / 2 out analog module                   |
| <a href="#">EX-A2X</a>  | Expansion adapter,Isolated                   |
| <a href="#">V200-18-E3XB</a>  | IO MODULE,18/17IN/OUT,4UNI/AN,IS             |
| <a href="#">V200-18-E4XB</a>  | IO MODULE,18/17IN/TOUT,4UN/AN,IS             |
| <a href="#">USP-070-B08</a>   | UniStream 7" HMI PANEL B08                   |
| <a href="#">UIS-04PTN</a>   | UniStream IO, 4PT100                         |
| <a href="#">UID-0808R</a>   | UniStream IO 8DI,8RO,24V                     |
| <a href="#">UIA-0006</a>  | UniStream IO, 6AO,NO ISO, 24V                |
| <a href="#">V700</a>  |  |
| <a href="#">V570 TOUCH SCREEN</a>                                   |  |
| <a href="#">X-A2X I/O EXPANSİON MODULE</a>                          |  |
| <a href="#">EX-D16A3-TO16-</a>                                      | XL-EXP,ADPTER,16I,3AI,16O                    |
| <a href="#">EX-A2X - Expansion adapter,Isolated</a>                 |  |
| <a href="#">V200-18-E46B - IO MODULE,ISO<br/>18/17I/O,9ANA,2AO</a>  |  |
| <a href="#">V200-18-E4XB - IO<br/>MODULE,18/17IN/TOUT,4UN/AN,IS</a> |  |
| <a href="#">V200-18-E5B</a>   | IO MODULE,18/17IN/TOUT,4AIN,IS               |
| <a href="#">V130-33-TA24</a>  | V130-TA24 OPLC,WL DIS,12/10 IO               |

|  |   |
|--|---|
| <a href="#">V570-57-T20B-J</a>                                     | V570 COLOR OPLC,WL,5.7",TOUCH - NO  |
| <a href="#">EX-A2X</a>   | Expansion adapter,Isolated  |
| <a href="#">V200-18-E3XB</a>                                       | IO MODULE,18/17IN/OUT,4UNI/AN,IS  |
| <a href="#">IO-DI8-RO8</a>   | 8 in / 8 R.out digital module   |
| <a href="#">IO-AI4-AO2</a>   | 4 in / 2 out analog module  |
| <a href="#">Samba 4.3™ -</a>                                       | HMI Touchscreen Programmable Logic Controller   |
| <a href="#">V700-T20BJ</a>   | V700-T20BJ COLOR OPLC,7",TOUCH  |
| <a href="#">V200-18-E2B</a>  | IO MODULE,16/14 IN/OUT,ISO, ANA   |
| <a href="#">Ethernet card</a>                                      |   |
| <a href="#">Io-T016 I/O</a>  |   |
| <a href="#">Ex-D16a3-To16 I/O.</a>                                 |   |
| <a href="#">280-18-B20b Plc</a>                                    |   |
| <a href="#">280-18-B20b</a>  |   |
| <a href="#">M90-R1-Can</a>   | Operator Panel  |
| <a href="#">V290-19-B20b</a>                                       | 5.7" Monochrome Touchscreen   |
| <a href="#">Eu210154 Ex-A2x</a>                                    |   |
| <a href="#">Vision120-22-R34</a>                                   | PLC, Vision, 2.4 "b / w LCD, 20DI, 12RO, 2AI 11.04.19 Item No .: 111473 µ-PLC with graphic display and keyboard: - Display: FSTN LCD (128x64) 8x20 characters Keyboard: 16 membrane keys - Program size: 448 kWorte, real-time clock - 1 RS-232 (RJ11), 1 RS-485 (RJ11) - I / O extension (RJ45), MODBUS and GSM support Zung - Panel or DIN rail mounting, front IP65 - Including programming software and serial cable - 20 digital inputs (24VDC), of which 3 as counter (10kHz, 32 bit) - 12 relay outputs (230VAC / 5A, 10Hz) - 2 inputs as analog inputs (10Bit; 0-10V, 0 / 4-20mA) or as 2 additional digital inputs (24VDC) - Power supply 24 VDC - incl. programming software and cable, assembly instructions erial |
| <a href="#">Io-Ao6x</a>  |   |
| <a href="#">Jz10-11-R16 - Obsolete , Alternative Is Jz20-J-R16</a> |   |
| <a href="#">I0-Di16 I/O</a>  |   |
| <a href="#">V130-33-R34</a>  |   |
| <a href="#">V280-18-B20b</a>                                       | Product: Unitronics Vision V280-18-B20B   |
| <a href="#">Io-Di8-Ro8</a>   |   |
| <a href="#">V130-33-T2</a>   | 10 DIGITAL INPUTS   |
| <a href="#">111625</a>   |   |
| <a href="#">112270 Jz-Prg</a>                                      |   |
| <a href="#">109564</a>   |   |
| <a href="#">107881</a>   |   |
| <a href="#">Acs355-03e-12a5-4.3f/3f</a>                            | DRIVER  |
|  | PLC I / O module, 16DI, 10RO, 4TO, 2AI, 2AO Item No .: 106929 Snap-   |

|   |  |
|---|--|
| <a href="#">V200-18-E2b</a>                   | in I / O Module: - 16 digital inputs (24VDC) of which 2 as Counter (10kHz, 16 bit) isolated in groups of 8 inputs. Isolation 1KV - 4 digital outputs (24VDC / 0.5A) thereof 2 as high speed output (max. 50kHz) isolated in a group of 4 outputs , Isolation 1KV - 10 relay outputs (230VAC / 5A, 10Hz) - 2 analog inputs 10bit (0-10V, 0 (4) -20mA) - 2 analog outputs 12bit (0-10V, 0 (4) -20mA) |
| <a href="#">M91-2-R2c</a>                     |  |
| <a href="#">2170334</a>                       |  |
| <a href="#">V120-22-R1</a>                    |  |
| <a href="#">Eu210068 Io-Pt400</a>             |  |
| <a href="#">Io-Lc1</a>                        |  |
| <a href="#">Io-Ro16</a>                       | PLC remote I / O, 16RO (24VDC) Item No .: 106948 - Relay outputs (230VAC / 24VDC, 10Hz): 16 outputs - Relay type: SPST-NO - 5A resistive load, 1A inductive load - DIN rail mounting - Dimensions: 80mm x 93mm x 60mm, 125g - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC   |
| <a href="#">117824 Vision130-33-Ta24</a>      |  |
| <a href="#">121358</a>                        |  |
| <a href="#">101262</a>                        |  |
| <a href="#">V200-18-E3xb I/O</a>              |  |
| <a href="#">120336 Jz10-11-Un20</a>           |  |
| <a href="#">Jz-Rs4</a>                        |  |
| <a href="#">Sm35-J-R20</a>                    |  |
| <a href="#">Io-Di16</a>                       | PLC remote I / O, 16DI (24VDC) Item No .: 101262 - Digital inputs (24VDC): 16; - counter (10kHz, 16 bit): 1; - DIN rail mounting - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC - Dimensions: 80mm x 93mm x 60mm, 141g   |
| <a href="#">M91-2-R1</a>                      |  |
| <a href="#">126642</a>                        |  |
| <a href="#">101264</a>                        |  |
| <a href="#">107882</a>                        |  |
| <a href="#">Eu210045 , V200-18-E3xb</a>       |  |
| <a href="#">V130</a>                          | PLC Operator Panel   |
| <a href="#">01 M91-2-R34 Serie Oplc</a>       |  |
| <a href="#">Io-Ai8</a>                        |  |
| <a href="#">Io-Atc8</a>                       |  |
| <a href="#">Li2ycy Pimf 3x2x0,Lapp0034041</a> |  |
| <a href="#">Ex-A2x (Successor To Ex-A1)</a>   | PLC expansion adapter, for PLC I / O module, insulated Art. No .: 126453 - Extension adapter for M90 / 91 / Vision series - incl. cable (1,0m) - supports up to 8 extensions - Connect using the supplied cable proprietary bus - Supply voltage 12 / 24VDC - Dimensions: 80mm x 93mm x 60mm, 125g   |
| <a href="#">114157 Jz-Rs4</a>                 |  |
| <a href="#">Jz10-11-T40</a>                   |  |

[V1040-T20b](#)

10.4" COLOR TOUCH SCREEN, TFT, USB PROGRAMMING PORT, MICRO SD CARD SLOT, 800 X 600 RESOLUTION (SVGA), 65K COLORS, WHITE LED-ILLUMINATED BACKLIGHT,9 PROGRAMMABLE FUNCTION KEYS, UP TO 1024 I/OS

[121354](#)