

Valenco

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Valenco Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Valenco Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
WS/DM462 25 * 16TX4,4U-2,5GV	MKB Maintenance kit Maintenance kit for 6467243 TA - 17 pressure reducing valve 462 DN 25 diaphragm controlled, double-seated elbow valve KVS-value 4,4 m³/h, temperature *-10 up to *+180°C outlet pressure adjustable 0,8 - 2,5 bar max permissible back pressure 3,8 bar all made of CrNiMo-steel, PN 16/6 inlet *ISO-clamp connection ø50,5/33,7 x 2 outlet *ISO-clamp connection ø50,5/33,7 x 2 face to face length 100/100 mm medium wetted parts made of 1.4404/1.4435/1.4462 cone sealing *FEPM diaphragm *FPM *with protection film made of PTFE
WS/DM152 15 * 10TX0,9U-2,5YV	MKB Maintenance kit Maintenance kit for 6404108 UA - 27 pressure reducing valve *152So DN 15 diaphragm controlled, single-seated elbow valve max. pressure inlet: 8 bar KVS-value *0,9 m³/h, temperature -10 up to +180°C outlet pressure adjustable 0,8 - 2,5 bar max permissible back pressure 3,75 bar all made of CrNiMo-steel, PN 10/6 inlet *ISO-clamp connection ø50,5/21,3 x 1,6 outlet *ISO-clamp connection ø50,5/21,3 x 1,6 face to face length *110/90 mm cone sealing *metallic, with throttle cone diaphragm FPM with protection film made of PTFE

WS/DM505 15 * 16TX0,4E -12EV	MKB Maintenance kit Maintenance kit for 6498316 TA - 6 pressure reducing valve *505F So DN 15 diaphragm controlled, single-seated globe valve KVS-value 0,4 m³/h, temperature *-35 up to *+130°C outlet pressure adjustable 4 - 12 bar max permissible back pressure *16 bar all made of CrNiMo-steel, PN *16/*16 inlet *ISO-clamp connection ø34/21,3 x 1,6 outlet *ISO-clamp connection ø34/21,3 x 1,6 face to face length 130 mm cone sealing *EPDM diaphragm *EPDM
WS/AS2 25 * 16TX -6KV	MKB Maintenance kit Maintenance kit for 72391076 A - 1 Separator AS 2 *DN 25 turn trap with integrated ball float trap globe valve flow rate 200 l/h at 6 bar differential pressure operating pressure range 0-6 bar, temperature max +190°C inlet *ISO-clamp connection ø50,5/33,7 x 2 outlet *ISO-clamp connection ø50,5/33,7 x 2 face to face length *158 mm fluid trap outlet: BSP male G 1/2A, downwards all made of CrNiMo-steel, PN 16 cone seal FFKM, body gasket Aflas (FEPM)
WS/AS2 40 * 16TX -6YV	MKB Maintenance kit Maintenance kit for 72391136 A - 2 Separator AS 2 *DN 40 turn trap with integrated ball float trap globe valve flow rate 1200 l/h at 6 bar differential pressure operating pressure range 0-6 bar, temperature max +190°C inlet *ISO-clamp connection ø64/48,3 x 2 outlet *ISO-clamp connection ø64/48,3 x 2 face to face length *193 mm fluid trap outlet: BSP male G 3/4A, at the side all made of CrNiMo-steel, PN 16 *face to face dim. 193 mm cone seal metallic, body gasket Aflas (FEPM) max. pressure of the float: 20 ba