

Valpes



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Valpes Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Valpes T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Er100.93a.Gp6	Electrom. Drive ER 100.93A.GP6 series "ER-PLUS" with control card, 100 Nm, input signal 4-20mA / 0-20mA / 0-10V with manual operation, 4 microswitches, Operating temperature - 10 ° C / + 55 ° C, 100-240V AC 50 / 60Hz (100-350V DC), 45W, 110s runtime (without load), ED 50%, IP 66, ISO 5211 F05 / F07 SW22 DVK.
VS100.90A.G00	DN 150 /12Stk DN 200 /28Stk. in 2 ausf¼hrungen 220V
ER60.90B.G00	Electrom. Drive ER60.90B.G00 "ER Plus" with manual actuation., 4 microswitches, operating temperature -10 ° C to + 55 ° C, 60 Nm, 12-48V DC (15-30V AC 50 / 60Hz), 45 W, 10s running time (not specified) Load), ED 50%, IP 66, ISO 5211 F05-F07 double square SW22
ER20.X0A.M00	Electrom. Drive ER20.X0A.M00 "ER Premier" with Manually operated, 4 microswitches, operating temperature -10 ° C up to + 55 ° C, 20 Nm, 100-240V AC 50 / 60Hz (100-350V DC), 15 W, 9s running time (without load), ED 30%, IP 65, ISO 5211 F03-F04 / F05 SW 14 double square
VS100.90A.GP5	Electrom. Drive VS 100.90A.GP5 with Manual operation, 4 microswitches, Operating temperature -20 ° C to + 70 ° C, 100 Nm, 100V - 240V AC, 45 W, 15s running time, ED 50%, IP 68, ISO 5211 F07 / F10 SW22 with POSI card (4-20mA / 0-10V)

VS150.909.R00.B	Electrom. Drive VS 150.909.R00.B with manual actuation, 4 Microswitch, operating temperature -20 ° C to + 70 ° C, 150 Nm, 400V TRI, 135 W, 20s running time, ED 50%, IP 68, ISO 5211 F07 / F10 SW22 Built-in EPR.1.B (potentiometer 1K Ohm)
ER20.X03.M00.167	electrom. Drive ER 20.X03.M00.167 "ER Premier" with manual actuation, 4 micro switches, Operating temperature -10°C to +55°C, 20 Nm, 24V AC 50/60Hz (24V DC), 15 W, 7s running time (or similar) load), ED 30%, IP 65, ISO 5211 F03-F05/F04 SW14 double square including optional card: wiring with 2 veins possible
ER45.858R 45NM 230V 24W VALPES electric actuator	
OS3051-2 RO	
ER45.858R 45NM 230V 24W VALPES electric actuator	
ER20.X0B.GS6	electrom. Drive ER 20.X0B.GS6 "ER Plus" Failsafe with Manual operation, 4 microswitches, operating temperature -10°C to +40°C, 20 Nm, 24-48V DC (24-30V AC 50/60Hz), 15 W, 9s Running time (without load), ED 50%, IP 66, ISO 5211 F03-F04-F05 SW14 double square Failsafe function for power failures - FAIL CLOSE (CW) Bluetooth control option
ER35.X0A.G00	
VS300.909.R00	Electrom. Drive VS 300.909.R00 with manual operation, 4 Micro switch, operating temperature -20°C to +70°C, 300 Nm, 400V TRI, 135 W, 35s runtime, ED 50%, IP 68, ISO 5211 F07/ F10 SW22 230V AC required for direction of rotation control Heating included, required for use of 230V AC
VS300.909.R00	Electrom. Drive VS 300.909.R00 with manual operation, 4 Micro switch, operating temperature -20°C to +70°C, 300 Nm, 400V TRI, 135 W, 35s runtime, ED 50%, IP 68, ISO 5211 F07/ F10 SW22 230V AC required for direction of rotation control Heating included, required for use of 230V AC
ecoflo - BV2-3-200-F1-6-PA 175 -SA	DN200 PN16
ER60.93B.GP6	Electric drive ER 60.93B.GP6 series "ER-PLUS" with POSI card, 60 Nm, input signal 4-20mA / 0-20mA / 0-10V with manual operation, 4 micro switches, operating temperature -10°C/+55°C 12-48V DC (15-30V AC 50/60Hz), 45W, 68s running time (without load), ED 50%, IP 66, ISO 5211 F05/F07 SW22 DVK
ER20.X03.M00	
VRX25.70B.G00.F	Electric drive VRX 25.70B.G00 with manual operation, 4 Micro switch, operating temperature -20°C to +70°C, 25 Nm, 12-48V DC (15-30V AC 50/60Hz), 45 W, 7s running time, ED 50%, IP 68, ISO 5211 F05/F07 SW17, II 2 GD Ex d IIB T6 Gb - Ex t IIIC T80°C Db IP68, LCIE 06 ATEX 6006X, electrical connection 2 x ISO M20 ***Option EFC.2 installed: 2

	additional micro switches for Return message***
VR25.70B.G00	Electric drive VR 25.70B.G00 with manual operation, 4 Micro switch, operating temperature -20°C to +70°C, 25 Nm, 12-48V DC (15-30V AC 50/60Hz), 45 W, 7s running time, ED 50%, IP 68, ISO 5211 F05/F07 SW 17
ER20-X3A-GP6-F03-F04-F05	Electric actuator, nylon polyamide PA6, modulation control, 4-20mA, 0-20mA, 0-10V or 1-10V, IP66, 25 seconds
BV2-3-200-F1-6-PA 175 SA	
ER20.X0A.G00	100V-240V 50/60Hz 20Nm 15W 90° IP65 OF N°094610/45
Er-35-558-B , Er35.X0a.G00	
212.608.411, F03/9 (A135942)	
Vs100.90b.G00	
Er10.X0a.G00 (A332383)	
Er35.X58b	
Er35.93a.Gp6 , Er60.93a.Gp6	
Er10 353	
Er100.90a.G00	Elektrom. Drive of the series ER Plus ER100.90A.G00, 4 Microswitch with manual operation, operating temp .: -10 ° C to + 55 ° C, 100 Nm 100-240V AC 50 / 60Hz (100-350V DC), 45W, IP 66, F05F07 / DVK 22, ED50%, 20s running time (without load)
Er35.90a.G00	Elektrom. Drive ER35.90A.G00 "ER Plus" with manual operation, 4 microswitches, operating temperature -10 ° C to + 55 ° C, 35 Nm, 100-240V AC 50 / 60Hz (100-350 V DC), 45 W, 7s Runtime (no load), ED 50%, IP 66, ISO 5211 F05-F07 double square SW 22
Er20.X0a.M00 100-240v Ac	
Drain Valve=dn 25 Pn40 Elec.Actuated	
Vs150.90a.Gp5	
Er100.93a.Ss2 , By Er100.93a.Gs2	
Snaa510000	
Vrx45.70b.G00	
Actuator For Vs160.90a.G.00 By Vs150.90a.G00	
Plates (For Solenoid Valve Er-45-753m)	
Pss.22/17	
Er35.X0b.Goo	

Er20.X0a.Gs2
Vs300.90b.Gp5
Vr75.70b.Gs2
279.809.511.50
A332396
Er35.558c 230 Vac 35nm By Er35.X0a.G00
Snaa933000
Ep25.508 220v 50hz 90; 25nm 30w Ip65 Dn15 Pn64
Vsx100.90b.G00
Er20.X0a.G00.
Vrx.P5
Er35.X0b.G00
Vs150.90a.M00 By Vs150.90a.G00 (A157513)
Er60.90b.G00
Urx75 70a G00
Full Set (Without Than The Main Body Of The Selonoid Valve Er-45-753m)
Adhv22/17dsds
Er20.X53m , By A332378 Er20.X0b.G00
Vs100.90b.Gp5
Vr45.709.R00á;
Er20.X58b Obsolete, Replaced By Er20.X0a.G00
Efc.2
Vrx75 70a G00
Er10.X0a.G00.E
Er60.90b.G00.167
Er10.X53s / By Er10.X0b.G00
Vs150.90b.Gp5

Er10.X0b.Gf3 180; Ek20.X08s , By Er20.X0a.M00
Er20.X03.M00.
Er20.X03.M00.K167 Elektrom. Drive ER 20.X03.M00.K167 "ER Premier" with Manually operated, 4 micro switches, operating temperature - 10 ° C to + 55 ° C, 20 Nm, 24V AC 50 / 60Hz (24V DC), 15W, 7s runtime (without load), ED 30%, IP 65, ISO 5211 F03-F05 / F04 SW 14 Double square with two DIN plugs ECD.1 including optional card: wiring with 2 wires possible
Module (For Electrovalve Er45.958r)
Vs300.90a.G00 100-240v 50/60hz 300nm 85w 90;
Vt 1000 A09 R00
Er 10.353.S
Er60.90b.G00 Elektrom
Ek150.808m-- By Vs150.90a.G00
Er10.353s By Er10.X0b.G00 (A332377)
Vrx45.703.Goo , By Vrx45.70b.G00
Er35.90a.M00
Vs300.909.R00
Er10.X0b.G00.167
F-38430; Ek20.X03s , Er20.X0a.M00
1370880002
Er 60.753-- By Er60.90b.G00.167
Vs300.903.Gp5
700000
Montagekit
Er60.93a.G00
Er100.93a.Gs2
Er60.958r , Er60.90a.G00
Er 35.558c
Pw.F03
Er10.X53s
A335407

Er20.X0a.M00	
Er10.458e , By Er10.X0a.G00.E	
A332378, Er20.X0b.G00 15-30vac/12-48vdc 20nm, F03-F04-F05/14, 9-12s, 15w, Ed50%	
Er20	
Er20.Xob.Goo	
Er60.90a Gs20	
Er100.90a.M00	Elektrom. Drive ER 100.90A.M00 "ER Premier" with Manually operated, 4 micro switches, operating temperature -10 ° C to + 55 ° C, 100 Nm, 100-240V AC 50 / 60Hz (100-350V DC), 45W, 22s running time (no load), ED 30%, IP 65, ISO 5211 F05-F07 SW22 Double square
Stv-Vs150-90b-G00	
Vs300.90b.G00	
Ek150.808m Motorized	
Er10.X0a.G00	
Vs150.90b.G00	
Er 60.93a.Gp6 Serie Quot;Er-Plusquot; Mit Regelkarte	
Vrx25.70a.Gp5	
Er20.X0a.M00 (A332677)	
Er35.X0a.G00	
Vs150.90a.G00 (A157513)	
Er 60.93a.Gp6 Serie Quot;Er-Plusquot; Mit Regelkarte Elektrom. Antrieb	
0036 Pn 25	
Er100-953m By Er100.90b.G00	
Er100.93ã170;.S00 -Osbolete- By Er100.90a.G00	
Ep100.702-4 , Er100.90b.G00	
Er10.X0b.G00 (A332377)	
614-716-103-0a	
Engine (For Solenoid Valve Er-45-753m)	
Er60.90a.M00	

Vrx25.70a.G00	
Er100.93b.G00	
Vs300.90a.G00	Elektrom. Drive VS 300.90A.G00 with manual override, 4 Micro switch, operating temperature -20 ° C to + 70 ° C, 300 Nm, 100-240V AC 50 / 60Hz, (100-350V DC) 45W, 60s running time, ED 50%, IP 68, ISO 5211 F07 / F10 SW22
Er60.950r-4	
Er10.353s - , By Er10.X0b.G00.167	
Gear Box For Engine Valve Typ Vrx25.70a.G 00	
Er60.90a.G00	
Pa2.F07 / F03	
Er10.372 - , By Er10.593.M00	
195048101	
Er35.903.M00	
Vs160.90a.G.00 By Ad019	
Ep 25.208	
Vt 600 A 09r00	
Ek60.808m , Current Version Er60.90a.M00	
Ek 60-B03m Ip65 Of No:073294/146	
Ad019	
Er100.90b.G00	
Vrx25.70b.Gf4	
271.808.511.0a	
Vrx45.70b.Gp5	
Vsa300.903.Hs2	
Ek150.808m , Replacemet Vs150.90a.G00	
Er10.X58e , By Er10.X0a.G00	
Vs150.90a.G00	
Er10.X0b.G00, 15-30vac/12-48vdc, 10nm, F03-F04-F05/14, 9-11s, 15w, Ed50%	

[137109](#)

[Er10.X0b.G00](#)

[Er10.593.M00](#)

[Vs300.90a.Gp5](#)

[Er060.938 P6 , Er60.93a.Gp6](#)