

Valves

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Valves Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Valves Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3-phase, AC Explosion-proof hydrogen-rich gas / synchronous generator - 0.37 kW, 1500 rpm, star connection For adjustable shut-off valves of tank farms type: OPEN FIELD (3791-41-07503715-98; connection dimensions 100 * 100.) Purpose and working environment: open valves, close. Petroleum products, gas reduction; for shut-off valves DN 50 mm Degree of protection IP65, explosion-proof 1ExdIICT1 / 1ExdIIIBT5
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3Phase, AC; 5.5 kW, Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection dimensions 285*285 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; For shut-off valves DN 500, DN 400 Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIIBT5
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3Phase, AC; Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 4kW; 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection dimensions 200*200 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; DN 350 mm for shut-off valves Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIIBT5
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3Phase, AC; Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 1.5kW; 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection dimensions 122*122 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; For shut-off valves DN 100 mm, DN 250 mm Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIIBT5

Ürün	Açıklama
BVW-1-050	Butterfly valve BVW-1 Zw.Fl. DN50 21bar
BVW-1-065	Butterfly valve BVW-1 Zw.Fl. DN65 21bar
BVW-1-150	Butterfly valve BVW-1 Zw.Fl. DN150 21bar
Butterfly valve BVT-1-025	
Butterfly valve BVT-1-032	
Butterfly valve BVT-1-040	
BALL VALVE VSP/2V" (DN50) PN16	AISI 316L / AISI 316L -FF GAS -PTFE/VITON -max 120 C -for. " I " -ATT. 63/90 -DE -DX- CA code 3KFC1QA2AEE3
Db-Da71f/24	