
**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



# Vatec

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

**Vatec** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Vatec Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*

| Ürün | Açıklama |
|---|---|
| Automatic aspirator type AELD35 | Description, sheet no.60201<br>Number of compressed air ejectors 1<br>Operating voltage 230V 50 / 60Hz<br>Power requirement 16 VA<br>Degree of protection IP65<br>Nominal pressure PN10<br>Required compressed air 5 - 7 bar<br>Air consumption (at 6 bar) 70 l / min<br>Suction power 300 Nl / min<br><br>Pressure level: To be clarified - we refer to our pressure level selection sheet.<br>Please note that the types VDCM € 500.00 extra cost per unit.<br><br>Materials: Housing G-CuSn10, primed<br>Polyethylene nozzles<br>Inner parts 1.4571<br>Seals NBR70 |
| Vatec | |
| Vatec | |
| 3006 PRESSURE SWITCH MODULE | |
| Type AELD45 | Description, leaflet no. 60201<br>No. of compressed air driven ejector 1<br>Voltage 230V 50/60Hz<br>Power consumption 16 VA<br>Protection IP65<br>Nominal pressure PN10<br>Compressed air required 5 – 7 bar<br>Air consumption (at 6 bar) 120 l/min<br>Capacity 500 Nl/min<br>Pressure range* PLEASE SELECT<br>Materials: Casing bronze (G-CuSn10), primed<br>Nozzles polyethylene |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

| Ürün | Açıklama |
|---|---|
| | Inner parts stainless steel (1.4571)<br>Seals NBR7 |
| Automatic Priming Unit Type AELG35, 45, 55 or65-Ex | Automatic Priming Unit Type AELG35, 45, 55 or 65-Ex<br>Number of pieces 1<br>Description, leaflet no. 62001<br>No. of compressed air driven ejector 1<br>Voltage 230V 50/60Hz<br>Power consumption 21 VA<br>Protection Automatic Aspirator IP65<br>Protection control cabinet IP66<br>Field of application Zone 1 / Zone 2<br>max. operating pressure / design pressure (AD2000) -1bar to +0,5bar / -1bar to +10bar<br>Compressed air required 5 – 7 bar<br>Control unit separate control cabinet,<br>installation out of ex-area<br>Materials: Casing ejector bronze (G-CuSn10), RAL7035<br>Tank steel galvanized, RAL7035<br>Nozzles Polyethylene<br>Inner parts stainless steel (1.4571)<br>Seals NBR70<br>Control cabinet steel, RAL7035<br>Weight each: Automatic Aspirator 28 kg<br>Control cabinet 9 kg<br>Type AELG35-Ex AELG45-Ex AELG55-Ex AELG65-Ex<br>Capacity (Nl/min) 300 500 700 1000<br>Air consumption (at 6 bar) (l/min) 70 120 190 240 |
| Additional prices each unit: | Tank made from stainless steel (1.4571) |
| Typ AELP25 | Description, publication number 62101<br>Number of compressed air ejectors 1<br>Operating voltage 230V 50/60Hz<br>Power requirement 16 VA<br>Degree of protection IP65<br>Nominal pressure PN10<br>Required compressed air 5 - 7 bar<br>Air consumption (at 6 bar) 60 l/min<br>Suction power 250 Nl/min<br>Pressure level* PLEASE SELECT<br>Materials: Housing G-CuSn10, primed<br>nozzles polyethylene<br>Internal parts stainless steel<br>Seals NBR70 |
| Automatic aspirator type AELD35 | Number of pieces 4<br>Description, leaflet no. 60201 |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | No. of compressed air driven ejector 1<br>Voltage 230V 50/60Hz<br>Power consumption 16 VA<br>Protection IP65<br>Nominal pressure PN16<br>Compressed air required 5 – 7 bar<br>Air consumption (at 6 bar) 70 l/min<br>Capacity 300 Nl/min<br>Pressure range V<br>Materials: Casing bronze (G-CuSn10), primed<br>Nozzles polyethylene<br>Inner parts stainless steel (1.4571)<br>Seals NBR70 |
| MODEL: GLA150 | BWS GLA 2<br>1. FLOAT SWITCH 6010 - 1 PCS<br>LEVEL SENSOR FOR GLA150-I-AG1, KFG LEVEL AG,CH6341, KD-3001516/3/56695,<br>L1=110MM L2=350MM, ALE/V/R11/2-V/UO-L400/12-1/ SVK44/15/A-PEDII.<br>P/N ACCORDING TO MANUFACTURER MANUAL - 6010. |
| 6010 - LEVEL SWITCH | Spare parts for Gas Discharge valve Type GLA150, Standard Design, Serial-Number unknown |
| AELD45 230V 50/60Hz | |
| AELP25-W 230V 50/60Hz | |
| Automatic Aspirator Type AELP25 | Description, leaflet no. 62101<br>No. of compressed air driven ejector 1<br>Voltage 230V 50/60Hz<br>Power consumption 16 VA<br>Protection IP65<br>Nominal pressure PN10<br>Compressed air required 5 – 7 bar<br>Air consumption (at 6 bar) 60 l/min<br>Capacity 250 Nl/min<br>Pressure range V<br>Materials: Casing bronze (G-CuSn10), primed<br>Nozzles polyethylene<br>Inner parts stainless steel<br>Seals NBR70 |
| AELD35-V 230V 50/60Hz PN16 | |
| ASED-C/W/230V/50/60Hz | |
| 3016 | MIXING NOZZLE “L35”, |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| 3020 | FUEL NOZZLE “L35”, |
| 5114 | REPAIR KIT AELD35 consisting of:<br><br>3009 guide ring, 3012 piston, 3030 valve seal, 5001 sealing ring, 5002 compression spring, 5008 O-ring,<br><br>5013 locking nut (2 pieces), 5019 hose ring |
| Piston : 3012 | |
| Driving Nozzle :3020 | |
| Mixing Nozzle : 3016 | |
| PRIMING UNIT | TYPE: PN10 G1/2"<br><br>SIZE OF NOZZLE : 45<br><br><br>SOLENOID VALVE<br><br>G1/2"<br><br>230 V<br><br>NORMALLY CLOSE<br><br>EXPROOF TYPE |
| AELD35V | |
| AELP25 | |
| AELD 35V | |
| 3022 | for: FVP 1351-F<br>ventilation gasket |
| 5004 | for:VATEC FVP 1351-F<br>sealing gasket (must be made of viton material) |
| 5006 | for:VATEC FVP 1351-F<br>impeller screw + seal |
| 5015 | for:VATEC FVP 1351-F<br>contact sealing gasket |
| AELG55 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| AELD35 | |
| Typ ASED-C | ASED-C type intake system<br>Description, printed sheet no. 71601<br>Number of vacuum pumps: 1<br>Operating voltage 230V / 60Hz<br>Speed 3360 rpm<br>Power requirement 0.4 kW<br>Vacuum pump suction capacity 170 l/min<br>Required operating fluid: 1 l/min, neutral<br>Protection class IP54<br>Pressure stage W<br>Materials:<br>Operating fluid container, galvanized steel, RAL7035<br>Pump housing G-CuAl10Ni<br>Wheel G-CuAl10Ni<br>Vacuum valve G-CuSn10<br>Control disc X6CrNiTi1810<br>NBR seals |
| Priming Unit Type Ased-C | Description, leaflet no. 71601<br>Number of vacuum pumps 1<br>Voltage 230V / 60Hz<br>Rotation 3360 RPM<br>Power consumption 0,4 kW<br>Capacity of vacuum pump 170 l/min<br>Service liquid required 1 l/min, neutral<br>Protection IP55<br>Pressure range W<br>Materials Service liquid tank steel galvanized<br>Pump casing aluminium bronze (G-CuAl10Ni)<br>Impeller aluminium bronze (G-CuAl10Ni)<br>Control disc stainless steel (X6CrNiTi1810)<br>Vacuum controlled shut-off valve bronze (G-CuSn10)<br>Inner parts stainless steel<br>Seals NBR |
| Automatic Aspirator Type Aeld35 | Description, leaflet no. 60201<br>No. of compressed air driven ejector 1<br>Voltage 230V 50/60Hz<br>Power consumption 16 VA<br>Protection IP65<br>Nominal pressure PN10<br>Compressed air required 5 – 7 bar<br>Air consumption (at 6 bar) 70 l/min<br>Capacity 300 Nl/min<br>Pressure range V<br>Materials: Casing bronze (G-CuSn10), primed<br>Nozzles polyethylene<br>Inner parts stainless steel (1.4571)<br>Seals NBR70 |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| Asvb 2081 | 400 V / 50 Hz , 1x4.0 kW, 1x1400 l/min IP 55 |
| 5114 | |
| 60201 | |
| 6005 | |
| 5225 (3022+5004+5006+5015) | |
| 3006 | PRESSURE SWITCH MODULE<br><br>Customs tariff no.: 8414 9000<br>Origin: Germany (EU) |
| P59347 | Ansaugsystem Typ ASED-C<br>Description, leaflet no. 71601<br>Number of vacuum pumps 1<br>Voltage 115V / 60Hz<br>Rotation 3360 RPM<br>Power consumption 0,4 kW<br>Capacity of vacuum pump 170 l/min |
| P59349 | Repair kit pump mechanical consisting of:<br>5218.1 Rubber Pressure Piece, 5218.2 Plug (2 Pcs.), 5218.3 Valve Plate, 5218.4 Seal (Pump Cover), 5218.5 Seal (Pump housing), 5218.6 Washer, 5218.7 Feather key, 5218.8 Mechanical Seal<br>5218Ersatzteil-Nr.<br>7523060 ASED-C |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*