

Voith Turbo

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Voith Turbo Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Voith Turbo Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
IPVP 5/-64/ 101	Voith Material-Nr.: 159.00290311
IPV 6/110-125/.. 411	Voith Material No.: 159.00405610 Replacement for H68.600610 preference: yes Pos.Weight: 45 KG
IPV 6/-125/ 411	Voith Material No.: 159.00405110 Preference: yes Pos.Weight: 35 KG
THL 3237100212	
Pump impeller 443/95*147,2 TCR. 41504010 0010/0090	
-pump impeller TCR.41448260, 010/0090/0010-	
-Hub, TCR.41446880, 0010/0090/0020-	
-Cylindrical head screw, H01.000556, 0010/0090/00	
-Spring washer, TCR.03111118, 0010/0090/0030-	
-Spacer pin, TCR.03130075, 0010/0090/0050-	
-Spacer pin, TCR.03130164, 0010/0090/0060- -	
Turbine wheel 525/444*52.1, TCR. 41541880, 0010/	0110
IPV 6/110-80/.. 111	H68.580110
366 TN09	Voith turbo coupling Motor: Electric motor

Ürün	Açıklama
	Motor type: Asynchronous motor Engine power P1 [kW]: 18.5 Engine speed n1 [min-1]: 1455 Work machine type: rake cart Rated power P2 [kW]: 12 Filling [l]: 4.4 Slippage approx. [%]: 2.5 Fusible link [°C] 160 Viewing screw: Yes Replacement for VTK number: 965460 Installation position: horizontal Drive via: external wheel Execution: Dimensions: according to Installation plan: 91500814210 with deviation Material of rotor parts: Silumin Drive side: Primary dome flange: Bore diameter: 48.00 Bore fit: H7 Hub length: 60.00 Key design: DIN 6885/1 ... hub shortened to 60mm! Output side: Connection via: coupling shaft Shaft diameter: 55.00 Shaft fit: m6 Shaft / journal length: 70,000 Key design: DIN 6885/1
Set X1 - M18	Fusible screw set X1 - M18 consisting of: 5 fusible screws 2 sealing ring for filling screw
4202840001	TUBE,METERING: 1/2IN NOM,800MM LG,GRADE: 316,MATERIAL: STAINLESS STEEL
250.00736010	Tank storage 160cm ³ 0.2/2.7bar M6 2xG1/8
Ingphs-0160riaio	
Tcr 03645367	
300156	
Sr-P160	
20103285210 (Ex. Tcr.10662120	
lpc5-40-101	

Ürün	Açıklama
Tcr.11977710	
Tcr 03645350	
Tcr.11052240	
lpc6-80-101	
Tcr 03309434	
Tvf487	
Tcr 03645192	
307900056	
Tcr.10662120	
307016439	
lpc4-32-1-0-1	
Tcr 10122460	
Ingphc-320r1g1o	
307100424	
Tcr 03658024	
15600119810-01	
307900243	
Fuse Screw Set X1 - M18 Consisting Of:	5 fuse screws 2 sealing ring for filling screw
Tcr 11052220	
We01-4m100	
K.015.190.1054.N45	
Tcr.11052220	
lpc-4	
307900042	
Tcr 03379360	

Ürün	Açıklama
Tcr 11977710	
307900024	
Tcr 03682415	
Wdxl-125sg	
Tcr.10662110	
307900057	
307025040	
Hc-Ba 110	
lpy/V-7/7-125/125-711	
Tvvs562	
Tcr 03661135	
Tcr 03616008	
L.28 307000508	
307900053	
307900055	
Zp240	
Svtl750	
Tcr 03658010	
Hyloc Hcba 110	
56.5418.10	
Tcr4188931009	
125.0178810001	
Voith Turbo Coupling 366 T09	Country of origin: unknown Preference: no Pos.Weight: 50 KG Tariff: 84836080 Technical data for the coupling insert: Engine: electric motor Motor type: asynchronous motor Motor power P1 [kW]: 22/30

Ürün	Açıklama
	Engine speed n1 [min-1]: 1460 Working machine type: chain conveyor Rated power P2 [kW]: unknown (please confirm!) Filling [l]: 4,4 / 5,0 Slippage approx. [%]: 5.3 Schmelzsicherungsschr. [° C] 140 X1 Visible screw: Yes Replacement for VTK number: 795767 Installation position: horizontal Drive via: external wheel Execution: Dimensions: after Installation plan: 91500425210 Material of rotor parts: silumin PTO: Elast. Connection coupling type ENK 200 Sx Bore fit: H7 Type key: DIN 6885/1 ... hole =? Please confirm! Output side: Connection via: clutch hub Bore fit: G6 Type key: DIN 6885/1 Bore depth: 120.00 ... hole =? Please confirm! Delivery Consisting of position;; connection coupling ENK 200 SX, including Perbunan 70, completely drilled screw for conne
Ipv4-16-471	
Tcr 03306148	
Ingphs-0125r1a1o	
307900640	
Ds-100-Po-300-S-P	
Ingphc-130r1g1o	
307200288	
9753003	
Mounting And Dismounting Device T 366 -	Pos.Weight: 2,800 KG

Ürün	Açıklama
M16	
lpc4-25-1-0-1	
Dsg-B05213	
Tcr4247147001	
Tcr 03302240	
9753002	