Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Vse Flow

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Vse Flow Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Vse Flow Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Vs0,4 Epo 12-12a11/1	
VS 0,4 GPO12V 32L11/2 - 10...28VDC	Volume sensor Measuring range: 0.03 - 40 l / min at 21 cst.
VSI 1/16 GPO54V 42R11/5 10..28 VDC	Volume sensor Measuring range: 0.30 - 50 l / min at 21 cst. Interpolation factor: 16 Steel plain bearings Customs tariff number: 90261021
VS 0,4 GPO12V 32N11/2 - 10...28VDC	Volume sensor Measuring range: 0.03 - 40 l / min at 21 cst.
VSI 2/1 EPO54V 42R11/5 10..28VDC	Volume sensor Stainless steel 1.4305 Measuring range: 0.3 - 70 l / min at 21 cst. Interpolation factor: 1 Steel plain bearings Customs tariff number: 90261021
VS 0.02 --- 0.002-2 L/min	
VSI 0,2/16 GPO12V 42R11/5 10..28VDC	volume sensor Measuring range: 0.02 - 18 l/min at 21 cst. Interpolation factor: 16 Customs tariff number: 90261021
vs2 GPO54V3211/4 VSE 1	
VS 0/1 GPO12V32Q11/4 VSE 1	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
VSI 2/1 GPO54V 42R11/5 10..28VDC	Measuring range: 0.3 - 70 l/min at 21 cst. Interpolation factor: 1 steel slide bearing
VS 0,1 GPO12V 32Q11/4 - Ex	volume sensor Measuring range: 0.01 - 10 l/min at 21 cst. Explosion protection: intrinsic safety "i" Ex II 1 G Ex ia IIc T4 - T6 BVS 05 ATEX E 071 X
GPO12V 42R11/3	VSI 0.4/8 GPO12V 42R11/3 10...28VDC,VSE
GPO12V 32W 15/2	VSI 0,4/5 GPO12V 32W 15/2 10...28VDC,VSE
VSI 0,1/1 EPO12V 42R11/5 10..28VDC	130501 volume sensor 1.4305 stainless steel Measuring range: 0.01 - 10 l/min at 21 cst. Interpolation factor: 1
VHM-Einfachaufnehmer VIII-1S10/N (T)	Output signals: PNP and NPN VSE standard plug (Special version for turbines, VTR series)
VSI 0,4/1 GPO12V 42R11/3 10..28VDC	Volume sensor 140001 Measuring range: 0.03 - 40 l/min at 21 cst. Interpolation factor: 1 Successor model to VS 0.4 GPO12V 12A11/1 1:1 interchangeable
VSI 1/1 GPO12V 42R11/5 10..28 VDC	Volume sensor Measuring range: 0.05 - 80 l/min at 21 cst. Interpolation factor: 1
32Q11/4	VS0,1 EPO12V FLOWMETRE ; BVS05 ATEX E071 X II1G EX İ A II C T6..T4
32L11/4 10..28V DC	ART.NR.:13500
32N11/4	
VSI 2/1 GPO12V 42R11/5 10..28VDC	Volume sensor Measuring range: 0.1 - 120 l/min at 21 cst. Interpolation factor: 1

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
VSI 2/16 GPO12V 42R11/5 10..28VDC	Volume sensor Measuring range: 0.1 - 120 l/min at 21 cst. Interpolation factor: 16
4386	Frequency/analog converter FU 210 Programmable frequency converter (FU210) or pulse counter (ZU210) Input frequency range: 0.1Hz..250 kHz (A/B x 90°; HTL) Analogue output: 0..+/-10V, 0/4..20 mA; 16 bits Linearization function with 24 support points 6 control inputs 6 control outputs Supply voltage: 18..30V/DC 50mA Dimensions: W 23 x H 102 x D 102 mm Protection class: IP20 Mounting: DIN rail (according to EN 60715)
VS 0,1 EPO 12T-	
PTFE VSI 0,04 / 0,1 / 0,2	AT seal set PTFE VSI 0.04 / 0.1 / 0.2 consisting of: 1 pc. 47 x 2 2 pcs. 11 x 2 1 pc. 49 x 2
Vs 0,4 Epo12v 32n11/2 - 10...28vdc	Flow sensor Stainless steel 1.4305 Measuring range: 0.03 - 40 l / min at 21 cst.
Vs Connection Cable, Pur 4pol. Blue 5m	Shielded plug and cable PVC and halogen-free, 4 x 0.34mm² Sheath color blue, 5m long 1st end: VSE standard plug shield 4pol. 2nd end: open Customs tariff number: 85444290
Vsi 0.2/16 Gp012v	
Gycz-Opm4l	
Vs 0,1 Epo12v 32q11/4 - Ex	volume sensor Stainless steel 1.4305

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Measuring range: 0.01 - 10 l / min at 21 cst. Ex-protection: intrinsic safety "i" Ex II 1 G Ex ia IIc T4 - T6 BVS 05 ATEX E 071 X Customs tariff number: 90261021
Isolating Amplifier Mk 13-Atex	Type: MK 13-P-Ex0 / 24V DC / K15 EX II (1) DG [EEx ia] IIC PTB 06 ATEX 2025 Supply voltage: 10..30 volts / DC Zolltarifnummer: 85369095
Vs 0,4 Epo 12t Flow	
Vse0.1gp012v-32n11/4	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.