

## Waircom



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Waircom** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Waircom T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">EZL1/PM</a>	Maintenance unit lubricator, EZ series Connection G1 ", sight glass with protection, Weight 1780 gr.
<a href="#">EZL1/PM</a>	Maintenance unit lubricator, EZ series Connection G1 ", sight glass with metal protection, Weight 1780 gr
<a href="#">VM8</a>	
<a href="#">EKC8 KUC/ZR</a>	1120102659200
<a href="#">EKCA8/LR</a>	Pneumatic valve, series EK, Actuation by roller lever, with spring return, Function 5/2 monostable, G1/8" weight 190 g
<a href="#">MCS4</a>	Pneumatic valve series M, mechanical operation, with plunger and spring return, Function 3/2 NC monostable Connection on the bottom of the valve Weight 40 g/piece.
<a href="#">EZ1 G1   Lubricator</a>	L 1"   Mist   Metallic protection
<a href="#">Valve G1/4 5/2  </a>	Vertical knob - Vertical knob CAM4F
<a href="#">Black short-lever switch actuator, 3 stable positi</a>	Waircom MCS-LCSB
<a href="#">URG8/2</a>	Unidirec. In-line precision flow regulator Ø 2 G1/8
<a href="#">Ø4 bottom ported   Plunger</a>	MCS4
<a href="#">CALR4</a>	mechanically operated pneumatic valve, CA series, roller lever actuation with spring return, 5/2 way G1/4"
<a href="#">EKCA4 SUC/SUC, Pneumatikventil, Serie EK,</a>	Actuation by control valves with spring return, function 5/3, center position closed, G 1/4" the solenoid coils are not included weight 490 gr
	Magnetic coil width = 22 mm, Connection voltage 24V,

<a href="#">USB02450-60</a>	50/60Hz, Weight 50 g/piece.
<a href="#">FM100</a>	Magnetic sensor, FM series, for cylinder mounting, N.O. function, reed contact with LED, 2-wire version, voltage 5 to 230V, current max. 500 mA, connection cable 3m long. weight 33 g/pc.
<a href="#">ST80</a>	Successor type for FS81, Fastening element for Magnetic sensor FM100 and FM157, Cylinder diameter 80 - 100 mm
<a href="#">EKCA4 KUC/ZR, Electrically operated</a>	pneumatic valve, series EK, electrical actuation with spring return, function 3/2 N.C., monostable, G1/4", without actuating coil, weight: 390g/pc Solenoid actuated valve, series EK, control pilot, return mechanical spring, function 3/2 N.C., monostable, G1/4", without coil, weight: 390g/pc
<a href="#">EKCA4 KUC/ZR, pneumatic valve, EK series,</a>	operated by control valve with spring return, function 5/2 monostable, G 1/4", the solenoid coil must be ordered separately weight 439 g
<a href="#">USBG/22050-60, coils for pneumatic valves,</a>	side b=30 mm, inner diameter 9 mm voltage 220V 50/60Hz weight: 105 gr.
<a href="#">MCLRU4</a>	Mechanically operated pneumatic valve, Series M, function 3/2 NC with roller lever -, Actuation from one direction only, with spring return, connection on the bottom of the valve Weight 50 g/piece
<a href="#">CS4</a>	Mechanically operated pneumatic valve, CA series, with plunger, G1/4" Function 3/2 NC spring return
<a href="#">EZL1/PM-</a>	Oiler for maintenance unit, EZ series Connection G1", sight glass with metal protection
<a href="#">EZRR2/7</a>	Pressure regulator, EZ series, Connection G1/2", Adjustment range 0.8 to 8 bar,
<a href="#">Clr8</a>	
<a href="#">Ulcry/R22050-60 Valve</a>	
<a href="#">Vdma24562</a>	
<a href="#">80/20k/160 Edh Pneumatikzylinder</a>	
<a href="#">Uzrrm4/7 Solenoid Valve</a>	
<a href="#">Uzrrm4/7f20/Ss Reducer</a>	
<a href="#">100/Sg/Ed</a>	
<a href="#">Ventil Usb-Ba-/22050-60</a>	
<a href="#">Alr4 Wegeventil</a>	
<a href="#">25/125zk</a>	
<a href="#">D3/4b Ventil</a>	
<a href="#">35/25 Dcb</a>	

<a href="#">Clr4 Ventil</a>
<a href="#">20/25 Db Pneumatikzylinder4 Pcs</a>
<a href="#">35/Sg/Hb</a>
<a href="#">Ukca4u</a>
<a href="#">Caml8f 1/8 Valve</a>
<a href="#">Kc4 Valvef/11050</a>
<a href="#">Cpui/Ct-40</a>
<a href="#">Ukca4/U Valve</a>
<a href="#">62/20kr/30 Ed3h Pneumatic Cylinder</a>
<a href="#">Ulcrv/R 22050 Ventil Magnetventil</a>
<a href="#">Urg8/2</a>
<a href="#">Ulcsv/R02450-60 3/2 N.C. 24 V Ac Bistable Manual Actuator</a>
<a href="#">Distributor</a>
<a href="#">Ssi Fm100/Ex Linear Position Sensor, Hall Effect, Magnetic, Interface Ssi Fm100/Ex</a>
<a href="#">D3/4</a>
<a href="#">200/350 XI/Ms7 Pneumatic Cylinder</a>
<a href="#">Ukca4</a>
<a href="#">Ulcrv/R02450</a>
<a href="#">Press Max 10 Bartemp 20c++80c110/120 DcbcnInc</a>
<a href="#">Udsc12kuc</a>
<a href="#">Cpui-200</a>
<a href="#">Pma 200/350 Cpui / M S 7 Pneumatic Cylinder</a>
<a href="#">Ukc8/25/U Solenoid Valve</a>
<a href="#">40/Sg/Bu Repair Kit</a>
<a href="#">Cs-8 Air Valve 1/8 Valves</a>
<a href="#">20/25db Pneumatikzylinder</a>
<a href="#">Ekca8 Klc/Klc</a>

<a href="#">Uds212kuec/Kuec</a> <a href="#">For Ukca2/U Repair Kit</a>	
<a href="#">Fm100r</a>	
<a href="#">For Ukca4/U Repair Kit</a>	
<a href="#">Ulcsv/R 22050 Valve</a>	
<a href="#">Uds 105 Kuec/Zr Pneumatisches Ventil</a>	
<a href="#">Uds 105 Kr/Kr Pneumatisches Ventil</a>	
<a href="#">Ukca/U</a>	
<a href="#">Ulcsvr11050</a>	
<a href="#">Ukca2/U</a>	
<a href="#">20r20db Pneumatikzylinder</a>	
<a href="#">Cpui/Cf-40</a>	
<a href="#">Repair Kit For Pneumatic Cylinder 40/50</a> <a href="#">Dbui / M8</a>	
<a href="#">Ukc 4/32saukc4/32/Sa</a> <a href="#">Pneumatikzylinder</a>	
<a href="#">R4m8f</a>	
<a href="#">40/50dbui Pneumatic Cylinder</a>	
<a href="#">Repair Kit For Pneumatic Cylinder</a>	
<a href="#">Y/603195-001</a>	
<a href="#">200/Sg/Cpui/M Pneumatic Cylinder</a> <a href="#">Repair Kit</a>	
<a href="#">Calr4</a>	mechanically operated valve Roller lever with spring return, 5/2 way G1 / 4 ", Weight 200 gr / piece
<a href="#">Distributormekca8 Kuc/Tq</a>	
<a href="#">Hclr8</a>	
<a href="#">Ukca2/U Pneumatic Valve With Solenoid</a> <a href="#">Va17-10</a>	
<a href="#">40/50db Pneumatic Cylinder</a>	
<a href="#">40r10db</a>	
<a href="#">Cam4 Hebel</a>	
<a href="#">Clru2</a>	
<a href="#">Mekca8kuc/Tq</a>	

<a href="#">Pressure Regulator With Manometer Ezrr2/7f20pm/Ss 16 Bar</a>	
<a href="#">100/100 Cx/Fm Pneumatikzylinder</a>	
<a href="#">40/50cpui/N</a>	
<a href="#">40/Sg/Bu Reparateursatzrepair Kit</a>	
<a href="#">Ezrr27f20pm/Sm</a>	
<a href="#">Ukca4/U Pneumatic Valve With Solenoid Va17-10</a>	
<a href="#">Ukca4/U Pneumatic Valve</a>	
<a href="#">Ulcsv/Ra11050</a>	
<a href="#">For Pma 200/350 Cpui / M S 7 Pneumatic Cylinder Repair Kit</a>	
<a href="#">Clr4,</a>	mechanically operated pneumatic valve, CA series, with roller lever and spring return, Function 3/2 N.C, G1 / 4 " Weight 215 gr / pc.
<a href="#">Ekca4kr/Zr Sliding Mechanism Valve</a>	
<a href="#">Cpui-290</a>	
<a href="#">Fm 100/C</a>	
<a href="#">100/120 Dcbc Cylinder</a>	
<a href="#">Ekca4 Kuc/Zr Valve</a>	
<a href="#">35/25 Dcb Pneumatikzylinder</a>	
<a href="#">50/25dcb</a>	
<a href="#">Fm 100/C Magnetic Sensor</a>	
<a href="#">Cpui/Sct-40</a>	
<a href="#">Cylindersmg/Rhnc12/10 Udc</a>	
<a href="#">Fm 100/C Sensor</a>	
<a href="#">Ulcsv/R22050-60 Solenoid Valves</a>	
<a href="#">20r20 Db Pneumatikzylinder4 Pcs</a>	
<a href="#">Ukc2/20nc</a>	
<a href="#">Rid6</a>	
<a href="#">50/125cpui/N1+cpui/Ct50</a>	
<a href="#">Cam4f</a>	
<a href="#">200-125-XI-N2</a>	

[Ulcsv/R02450](#)

[Clr4 Valve](#)

[63/20kr/30 Ed3h Pneumatikzylinder](#)

[Hb 100/120 Dcb/C](#)

[Uzrrm4/7 Regler](#)

[Ffp12x1,25](#)