



Warom

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Warom** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Warom Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Bny81-36x2x (2x36w) Ex	
Bjd81-Y 220v Ac 50/60hz	Explosion-proof Caution Spotlight Fittings 220V AC1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:220V AC 50/60Hz; 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
Bjd81-Y 24vdc	1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:24V DC 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
Bzc 8050-40092ba-96	
Bza8050-A2-40066 / ATEX	
BDD81-A100X	
BYA 51-36x2x	
BNY81-LED-2X18 WATT	
BZA8050-A2D1	Explosion-proof Control Unit Systems ATEX 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: -20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer

	to catalogue
BAZ8050-A1D1	Explosion-proof Control Unit Systems 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: -20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer to catalogue
15092021681	BZA8050 A2D1 CTP 415 V AC Atex IP65
Model : BAYD-B-F	Ex-Proof Wall Mounted EXIT Luminaire with Aluminum Cast Body, Tempered Glass Resistant to Thermal Shocks and Impacts, Electronic Ballast, 120 Minutes Capacity Battery
BBJ81-R / ATEX	1.Ex-mark:II2 G Ex d ib IIC T6 Gb II2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~ +55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022. Explosion-proof Audio and Visual Caution spotlight fittings
EXPROOF IICT4 16A 380VAC	
BAK51-50/240B	
BBJ81-R	
BBJ81-R	BBJ81-R, 220VAC, 100-120dB, Red, Explosion-Proof, IP66
BAT86-240-240G	FLOOD LIGHT, LED, EX-PROOF, 240W 100~300V, AC 50/60 HZ ,COOL WHITE LUMEN VALUE:29418LM 240W 100~300V, AC 50/60 HZ ,COOL WHITE, 2X3/4" INPUT, ALUMINUM CASTING BODY, ELECTROSTATIC POWDER PAINT (GRAY), REINFORCED GLASS, BLIND PLUGS INCLUDED EXCEPT GLAND. CML 18ATEX1060X II 2 G EX DB IIB+H2 T6/T5 GB
BZA 8050-A1 EXP	
BHD51-B-NPT3/4"	BHD51-B-NPT3/4"
BZC8050-A3	Tanım : Elektrostatik Toz Boyalı ALUMİNYUM Gövdeli , Yeőil Start + Kırmızı Stop + Mantar Acil Stop Butonlu, Ex-Proof Lokal Kontrol Ünitesi (Tüm Butonlar, 1NO+1NC Kontaklıdır) Atex Sert. No. : LCIE 09 ATEX 3099 Koruma Sınıfı (Gaz) : II 2G Ex de IIC T6 Gb / IP65 / ZONE 1 Koruma Sınıfı (Toz) : II 2D Ex tb IIIC T80°C Db / IP65 / ZONE 21 (1 Ad. Ex-Proof M25 Nikel Kaplı Piriç Zırhsız Kablo Rakoru Dahil)
BCZ85-16 / 250 / 3P / T	Electrostatic Powder-Coated Aluminum Alloy Housing, 200–250 VAC, 50–60 Hz, 1P+N+PE Poles, 16 Ampere, Ex-Proof Single-Phase 3x16A Plug ATEX Certificate No.: CNEX 19 ATEX 0023X Protection Class: II 2GD Ex db IIC T6 Gb – Ex tb IIIC T80°C Db / IP66 / ZONE 1–21 Including: 1 pc. Ex-Proof 3/4" Nickel-Plated Brass Unarmoured Cable Gland Included
BCZ85-16/250/3P/Z	Electrostatic Powder-Coated Aluminum Alloy Housing, 200–250 VAC, 50–60 Hz, 1P+N+PE Poles, 16 Ampere, Ex-Proof Single-Phase 3x16A Wall Socket ATEX Certificate No.: CNEX 19 ATEX 0023X Protection Class: II 2GD Ex db IIC T6 Gb – Ex tb IIIC T80°C Db / IP66 / ZONE 1–21 1 pc. Ex-Proof 3/4" Nickel-Plated Brass Unarmoured Cable Gland Included
30008.	
Bak51-50/240b	
Bay-H21x1	
Bcz8060-16/250/3p/Z	
Bayd-Bf	
Bza8050-A1	40063A CODE, normal button

Yk18df-2cs	
Bjd-Z	
Bsx-60 E27 Lamp Holder	
Bcz8060-16/250/3p	
Bat51 - Hie400	
Explosion Proof Portable E-26 220v 100w Obsolete Replacement Bsx-60	
Dqm- Ii/M20x1.5 (708001)	
Bay51-D-236	EX-PROOF ALUMINUM BODY 2X36 W
5136019	
Bdh51-C/M20 X 1.5	
Cdz-Hr160-1560-Qd	
Bat53-400-Hie400	
Bzm-16b	EX-PROOF Switch
Baz51 - Hie400	
S Series	4 INSERT BUGS
Bhd51-A M25x.5	
Bay51-Q36x2x	
Bbj81-R Dc 24v	
Bzc8050-A1g	
Bbj81-R24	
Dqm- Ii/M20x1.5 (709002)	
Bat86-160-120g	100 Watt – 100-300V – IP66, CLASS II
Bxj-Iib-Iv	
¾" Ex-Proof Fittings	
BBJ81-R	Explosion-proof Audio and Visual Caution spotlight fittings ATEX 1.Ex- mark:II 2 G Ex d ib IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~+ 55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022 page2/161.
Bay51-D-258	
Bjd-Gr	
Bhd51-B/M20x1.5	
Bjd-Gy	
Yk36df-2cs	
Bad 85-120-120-D	
Bza8050.....Ex	

Bcz85-16-250-3p	EX-PROOF MONOPHASE Plug-in
Bzx-6	
Bat86-160-120y	
Bbj81-Y	