

Watlow



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Watlow Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Watlow T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
SD6L-HJAA-AARG LIMIT CONTROLLER	
020250C1-0001B	
0720KFIREROD	
2075-8209	
230V/1100W/KMFG0120T002C/1351KFIREROD	
245643	
534533	
680000811	
697000801	
70XJBGC040A	
7E6247	
938073	
ACJ00Q160UK000	

AF1110502
BCS6J10C2
BHN717N1W-45
BHS747J5S
C4A-8124
CZ24-A24V-DC10
DA10-60C0-0000
DB20-60F0-S000
DC22-60F0-0000
DC31-24C0-0000 SCR
E2E-9958
F06016281A
FLS 612307
G1J110-L24
J20-3-S-304
K24-2-508
L2G
L2G-10198
L6EX12B
LVC2KW 003211112A
LVC2KW00321112A
MB01J3AX-3046
PM3C1CJ-AAAAAAA
PM3T1CJ-AAAAAAA
PM6C1CC-AAAAAAA
PM6C1CJ-AAAABAA
PM6L1EJ-AAAAAAA
PM6L2EJ-AAFAAAA
PM8C1FA-AAAAAAA
PM8C2FA-ARFAAAA
PM8L1AJ-AAFAAAA

RMC1U7A1U7AAAAA	
SSR-240-25A-DC1	
SSR-480-75A-DC1	
STCL-F2MG-BPAA-EZ-ZONE ST	
STCL-F2MG-BPAA-EZ-ZONE ST CONFIGURED	
VP512A12U-M0000	
KFRL012AD005A	KFRL012AD005A 2000w-240v- WATLOW KFRL012AD005A
KFRJ005AC004A	250w-240v- WATLOW KFRJ005AC004A KFRJ005AC004A
L12A-11317	3000w-240v WATLOW- L12A-11317 L12A-11317
G474312	THRMCPPL WATLOW 32 TKWPD012F
Watlow Nr. 3-10-42-5PA	4875 Volton 48.75 Watlow Nr. 3-10-42-5PA BPH 02E 02EL 26M
VF81GA3GXA	400V 12x500W 1522 1 BLOCK
573-221-2816	
5459	Volton 54.59 1,00 Stck 318,00 318,00 2141-7432 Pmlegacy Package Size 6 = 1/16th DIN Panel Legacy Model Primary Function L = Limit Controller Power Supply 1 = 100 to 240VAC Output 1 and 2 SJ - Out1 = None : Out2 = Mech Relay 5A, SPST-NO Communications A = None Auxililiary Control Functions A = None Output 3 and 4 AA - Out3 = None : Out4 = None Model Selection G = PM "Legacy" Limit Version Custom Options WP = Logo Face Plate Model Number PM6L1AJ-AAAAGWP
Volton 57.38	2157-3030 LEGACY PM Package Size 6 = 1/16th DIN Panel Legacy Model Primary Function L = Limit Controller Power Supply 2 = 100 to 240VAC plus 2 digital I-O points Output 1 and 2 EJ - Out1 = Mech Relay 5A, SPDT : Out2 = Mech Relay 5A, SPST-NO Communications A = None Auxiliary Control Functions A = None Output 3 and 4 EJ - Out3 = Mech Relay 5A, SPDT : Out4 = Mech Relay 5A, SPST-NO Model Selection G = PM "Legacy" Limit Version Custom Options WP = Logo Face Plate Model Number PM6L2EJ-AAEJGWP
01020011h	30V50W 50 cm
L30A-11330	L30A-11330 FIREROD .621 Dia by 30 long 120V 1000W SWAGED in Leads 12 long
L30A-11330	L30A-11330 FIREROD .621 Dia by 30 long 120V 1000W SWAGED in Leads 12 long
	Package Size 6 = 1/16th DIN Panel Plus Model Primary

PM6-Controller	Function C = PID Controller with Universal Input Power Supply 1 = 100 to 240VAC Output 1 and 2 CA - Out1 = Switched dc/open collector : Out2 = None Communications 6 = Profibus DP Auxiliary Control Functions A = None Output 3 and 4 AA - Out3 = None : Out4 = None Model Selection P = PM PLUS standard (isolated input 1, input 2 is always isolated) Custom Options WP = Logo Face Plate Model Number: PM6C1CA-6AAAPWP
PM4C2FC-CREJAAA	EZ Zone Controller
PM6C1CJ-AAAAPWP	Watlow PM Configured
PM6C1CA-AAAHPW	Watlow Legacy PM
VF816A36XA	Ceramic Fiber Heater
MINERAL INSULATED SENSOR	MI Sensor Style AF Sheath Outside Diameter [in] G - 0.125 inch Junction Type U - Single Ungrounded Sheath Material Q - Alloy 600 Calibration Type K Limits of Error: Standard Limits Mounting Options: None Bend Option: Straight Length Sheath Length [in]: 24.000 Lead Wire Construction D - FEP, Stranded Lead Wire Length [in]: 120 Lead Wire Termination T - Standard Split Leads Cold End Seal/Potting: 300°F Epoxy Transition Style AF - 1/4" with Spring (700), Crimped Gauge Size: 24 Gauge Insulated Singles Length [in]: 1.500 Calibrate/Cert Type: No Certification Required MI Cable Material Cert (Y/N): No Lot Control NA - None
Fluent-Heater FLC-9	Base Heater 1" O.D. x 6.5" Length 240V 3000W Watt Density (W/in ²): 375 Outlet Fitting: 1/4" Straight Inlet Fitting: 1/4" Straight Internal Baffle: 316L Stainless Steel Power and T/C Length: minimum 12 inches High Limit Sensor: K Thermocouple (350°C Max Temp)
1/2x6x750w	
030300c1-0001b Nitropenta	
Dc22-60fo-S000	
1/2x5x750w	
Sw00004-000ee	
Pc20-F20a-000	
060200545	
Sw00004-000eb	
F050200c8-A001a	
F060200c8-A001a	
0720kfirerod	

Firerod Heizpatronen 220v, 250w	
3c1-000000000	16 AND 32 LOOP CONTROLLERS
J7a81	
Pm8c1fa-Aaaaaaa Ez-Zone	
Db10-60f0-S000	
900b-2dd2-A000	MICROPROCESSOR-BASED TEMPERATURE CONTROL
2039-7367	
Pm6c1cc-Aaaaaaa Pm6c1cc-Aaaaaaa	
J5a72-N18w28	
Rmla-55jj-Aaaa	
208-C20000bs	CONTROLLER MULTI-LOOP 8CHANNEL 15-24VDC 610MA
988a-20fe-Merg	
Db10-24f0-S000	
C4a-8124 Heizelement	
050150513	
Fls 612307 Thermoelement Argeh0a675wk000	
534533 Watlow St Louis 240 V ; 400 W	
Q32-481-100-Bf2	POWER CONTROLLER 100AMP 480V 3PHASE 60HZ
Cfona18a5s-C2-35	
Pm6c1fj-Aaaabaa Controller	
Pm6l1ej-Aaaaaaa Ez-Zone	
Rmc1u7aaaaa	
Dc20-60c0-0000	
Pm4c1fj-Aaeaaaa	
Dt3480354d00aaa	
Pm6l2ej-Aafaaa Temperaturregler	
1/2x3x500w	
15776	
Db20-24f0-S000	
3-43-39-1	
1/2x16x1000w	

040200508	
989a 20ee Asrq	
C1e13-L12	
Db30-60c0-S100	
G1j110-7750	
Vp512a12u-00000 Elemento Riscaldatrice Watlow	
Pm8l1aj-Aafaaaa Ez-Zone	
Db30-60f0-S000	
L2g-10198 Heizung D 5/8", 2 3/8" 240vac 280w Firerod L2g-10198	
030300c1-0001b	
Rmaa-A3aa-Aaaa	
3x20mml=550 Mm	
Cfmna33a5s-C2-35	
Pm6c1fj-Aaaabaa	
Af1110502 Thermoelement	
Scr Control	DC31-24C0-0000
1/2x4x750w	
060200	
Db20-60f0-S000 Power-Controller	
Bls732e12-20	
L3a-11314	
Z100-30700-401	CONTROLLER MULTI-LOOP 12-24VDC
E2e-9958 Patronefirerod 0802120v 150w	
70xjbgc040a Thermoelement Mit Ringtyp: Style 70	
Acj00q160uk000 Mineral Insulated Sensor	
1/2x5x500w	
Dc31-24c0-0000	
J20-3-S-304 Kabel 3500ft	
Bhs747j5s Heizer	

Dc22-60f0-0000 Halbleiter Power Controller	
Pm6r1cj-1lajaaa	EZ-ZONE TEMPERATURE CONTROLLER 100-240 VAC 10 VA WATLOW EZ-ZONE
204-1202000	4 LOOP CONTROLLER
208-C10000ba	CONTROLLER MULTI-LOOP
Pc20-N20b-0000	
Ssh-12-T	
Af-2030321	
70xjsgc060a Thermocouples	
93bb-1ca0-00rr	1/16 DIN Microprocessor-Based Auto Tuning Control Unit
57100236	
060200c2-A001s	
Pm6c3fj-Aaaabaa	
240v-1500w-1/2-185	
1/2x4x500w	
Pm8c2fa-Arfaaaa Ez-Zone	
32cjhug072a	
Pm6c1fj-Aaaaaa	
F 06016281 Flexible Silikon-Heizung	
Da10-24f0-0000	
Af-2030322	
93bb-1fd0-00rr	Watlow 93 Temperature Controller Watlow 93
70xjsgc070a	
1/2x18x1000w	
Cfmna40j5s-C2-35	
1/2x13x1000w	
Pm6l3ej-Aaaabaa	
G6a92-L12	
Ssr-480-75a-Dc1 Relais	
Ppc-2021	MODULE 16 CHANNEL INPUT
Bcs6j10c2 Heizung	

Pm3c1cj-Aaaabaa
1/2x7x1000w
70xjsgc060a
Pm6c1cc-Aaaaaaa Pid-Controller
Bln747g8w-22
F4sh-Ffa0-01rg
815-678-2211 Part
60xjsxd096a
2039-7662
Ssr-240-25a-Dc1 Solid-State Relais
32cjhug072a Sensor
2039-7681
107993-0001 Thermoelementrev A 05/12