



Waycon

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Waycon** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Waycon T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
172805272	
SX80-2500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-250-420A-SA12	Draw wire displacement transducer, measuring range: 250 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
SX50-375-420A-SA12	Draw-wire transducer, measuring range: 375 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
MAB-A-A-900-E	Magnetostrictive displacement transducer, rectangular profile, IP67, Measuring range: 900 mm, linearity: max. $\pm 0.01\%$, Output: 4...20 mA, 5-pin connector output M12
SX50-150-420A-SA12	Cable displacement transducer, measuring range: 150 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output

SX50-125-420A-SA12	Cable displacement transducer, measuring range: 125 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output
LRW-M-275-S	Linear potentiometer with push rod (M6), rectangular profile, measuring range: 275 mm, linearity: $\pm 0.05\%$, IP60, resistance: 5 kOhm, 4-pin connector output
PMX-24	Signal converter for potentiometer, Output: 4..20 mA / 10 V / 5 V / ± 10 V / ± 5 V configurable, Supply: 9...36 VDC, galvanically isolated, with cable break detection and alarm output, for DIN rail
SX50-750-420A-SA12	Cable pull transducer, measuring range: 750 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.1%, 4-pin axial M12 connector output
SX50-250-420A-SA12-M4	Cable pull transducer, measuring range: 250 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output Option: Cable fastening, M4 terminal
K4P2M-SW-M12	4-pin cable socket, M12 angle connector including 2m cable, shielded. Cable end 40mm stripped, shield braid twisted and strand ends provided with insulated wire end ferrules.
UR2	Deflection pulley \varnothing 44 mm, ball bearing, Operating temperature - 40...80°C
LVIG-100-420A-KR01	LVDT \varnothing 20 mm with ball joints, Measuring range: ± 50 mm, IP65, linearity $\pm 1\%$ Output: 4...20 mA, Supply: 24 $\pm 20\%$ VDC, 5-wire radial cable output (1 m) Only suitable for vertical installation (Sensor body hanging)!
LVIG-50-420A-KR01	LVDT \varnothing 20 mm with ball joints, Measuring range: ± 25 mm, IP65, linearity $\pm 0.5\%$ Output: 4...20 mA, Supply: 24 $\pm 20\%$ VDC, 5-wire radial cable output (1 m)
AWP 110 0500 5K 3M A 4-20 MA	
SX50-375-420A-SA12	
SC50-125-420A-SA12	
WP90420A-SA	
LROW 1-50-D-5K-C5-X204	
SX50-375-420A-SA12	Cable-operated displacement sensor, measuring range: 375 mm Output: 4...20 mA, Supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
UFP-200-M12-10V-SA	Ultrasonic distance sensor, stainless steel (M12x1), teachable, Measuring range: 25...250 mm, axial scanning, Output: 0...10 V, Supply: 12...30 VDC, Lin.: <0.3 %, IP 65, 4-pin axial M12 connector output
Sx80-2000-420a-Ka02	
Sx50-500-420a-Sa12-IP67	Pull-wire position transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67 Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Wp -6,8t-420a-Ka02 Lenkwinkelsensor	
Sx80-2500-420a-Sa12-IP67	Pull-wire position transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67 Customs Tariff No .: 90318020 Origin: DE Weight: 0.80 kg Prefix: YES

Sx80-1000-420a-Sa12 Sensor	
Lzw-M-500	
Sm25-Hyd-F18-Ka-0	
Rp-M-180-420?-??02 Lenkwinkelsensor	
WP-90-420A-SA12	Angle of rotation sensor, anodised aluminum and stainless steel, ø 60 mm, IP67 (on the housing side), IP60 (on the shaft side), Measuring range: 90 °, spin-through, Supply: 12 ... 30 VDC, output: 4 ... 20 mA, Linearity: 0.3%, 4-pin axial connector output M12
Con006	
Sx80-1500-420a-Sa	
Sx50-125-420a-Sa	
Las-Tx-4-420a	
Sr128-015	
Sm10-T-Sa-1312112	
Las-T5-100-V	
Lrw3-C-25	
???-?-?-800-W	
4p-Gegenst.-2kab-Hyd Ptfе-UI Kabel, 2 M, Orangemit Konfektioniertem Gegenstecker, Typ Lemo Phg.0b	
Sx80-3000-420a-Sa-00	
Rx80-2500-420a-Sa12 Sensor	
Lx-Ep 40	
Lzw-M-150	
Sx120-6000-420a-Sa	
K4p2m-S-M12	Cable socket 4-pin, straight M12 plug incl. 2 m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with insulated ferrules provided
Sx80-2000-420a-Sa	
Rx80-1000-Net-Sr12-M4 Profinet,Vers: 10-30vdc,Ip65,L=1000	
Sx50-750-10v-Ka	
Sx50-1000-420a-Sa	
Mss976r-0500I02	
Md20b	
Sm100-Sg-Ka	
Cmss65-002-00-15-10	
Sx200-6-Ssi-Sr23 Seilzug-Wegaufnehmer	
Sx50-375-420a-Sa	

Lrw-M-225-S	
K4p2m-Sw-M12	Cable socket 4-pin, M12 angle plug incl. 2m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with insulated ferrules provided.
Sx50-750-420a-Ka02-Om4	
Sx50-375-420a-Ka02	
Sx50-1250-10v-Sa	
Sx200-6-Ssi-Sr23	
???-?-?-1000-W	
Imca-24v-420a Lvdt-Externelektronik F. Din-Schiene, Versorgung: 9...36 V, Ausgang:4...20 Ma	
Zx-Pa-1,5-A Bewegungserfassungs	
Sensor Lineartechnik Mav-A-A-250-E	
Lam-F-200-Hd Lasersensor	
Ima2-Lvdt3a-24v	SIEHE ANHANG
Las-T5-500-V	
Sx50-500-420a-Sa	
Sm10-T-Sa-1112112	
Lzw-M-300	
Rp-M-90-420a-Ka02 Lenkwinkelsensor	
Sx135-10-420a-Ka	
Rx120-4000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Sx50-1000-1r Sa	
Kab24-420a	
Ps-100-240ac/24dc/1.3	
Mg10-P1 Main-Modul Com-, Versorgung: 12-24vdc Rs232c	
Rx80-1000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Ras-Tx-4-420a Laser-Wegaufnehmer	
Sx80-3000-420a-Ka02	
Sx80-8000-420a-Ka02	
Sx50-1000-420a-Ka	
K4p2m-S-M12-Cat Kabel Mit Stecker	
Imca-24v-10v	
Ha705Ik-905	

Sx50-375-10-Sa	
Sx50-225-420a-Sa	
???-20-26-10-10 Kupplung	
Ima-24v-420	
Sx80-3000-Srm50	
Sx120-4000-420a-Sa	
Sm25-Hyd-T-Sa-F18	
Sx80-2000-420a-Ka	
Sx80-2500-420a-Sa	
Sx80-2500-1-G-Sr	
D4-W-M12-S Verbinder	
Rm15-Wtja-8s	
Pmx-24 Sensor	
Lzw2-F-50	
Sm25-T-Ka-H-Ks	
Sm140-Hyd-H-18-Ks	
Sm50-Hyd-T-Ka-L20-F18	
Rx80-2000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Sx50-500-420a-Sa-0	
Sx50-1000-420a-Ka02-Om4	
Con011	
Sx80-3000-420a-Sa-O Imal S00128	
Sm25-T-Sr	
Wp-320-10v-Ka02 Analoger Drehwinkelsensor	
Sx80-1500-420a	
Rx80-2000-10v-Sa12 Bewegungserfassungs	
Rp-15t-420a-Sa12 Lenkwinkelsensor	
Imca-24-420a	
K5p2m-S-M12 Kabel Mit Stecker	
Rm15-Wtpa-8p	
Sx50-50-420a-Sa	
Sx50-375-420a-Sa12	Pull-wire position transducer, measuring range: 375 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Pref .: Yes
110294	

Sx80-3000-420a-Sa-O	
Sx50-125-420a-Sa12	Pull-wire position transducer, measuring range: 125 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Mss976r-0400I03	
Zx-Hm-1,5-A Bewegungserfassungs	
Sx50-300-420a-Ka	
Sx50-125-420a-Ka02	
Sx80-2000-420a-Sa Kabeltrommel Sensor	
Lzw1-F-75	
Sx80-1000-Pro-K1	
Imca-24v-420a	
Sx80-1500	
Sx120-6000-Pro-M12-O-S1-K1	
Sx50-225-10v-Ka02	
Con012-S	
Sx50-750-420a-Ka02	