

Weh

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Weh** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Weh Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Weh -Adapter Typ 17-Patented	
TW17H M14x1.5	
TW17H M16x1.5	
300140510	C1-14736 TW17H G1/2" ND W9003-085 WEH C1-14736 TW17H-W9003-085-BB0-X, C1-14736, INOX / INOX CELL CONNECTION TW17H, C1-14736 FOR G1/2 INTERNAL THREAD DEVICE NO. C1-14736 TW17H-W9003-085/LP ALL PARTS RUST-RESISTANT BUILDING SIZE 4 SIDE CONNECTION G1/2 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
300141710	
300144706	
300145616	
300146150	
300146465	
300156740	
300164613	
300175960	

B200B-142364	
C1-109025	
C1-111794	
C1-111796	
C1-112464	
C1-114-144	
C1-118225	
C1-141954	
C1-48091	
C1-99331	
E51-095V	
E51-116730	
E69-96824	
TK22N	
TW800 F. ROHRO15,MM/ BUNDO17,5MM C1-47781	
TW800B-SON-BB0/BG4/A D:19MM	
TW800B-SON-BB0/BG5/A D:20MM	
TW800-D19 (C1-111796)	
W1212	V actuator with pin W1212 f. Type 17 E150 (BG1)
C1-16774	QUICK CONNECTOR TW141, C1-16774 FOR OUTSIDE PIPE. 12.0MM DEVICE NO. C1-16774 ALL PARTS RUST RESISTANT SIZE 2 LINE STRAIGHT NPT1/4 AG ACTIVATION: CLAMPING LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 100 BAR
C1-16773	QUICK CONNECTOR TW141, C1-16773 FOR OUTSIDE PIPE. 10.0MM DEVICE NO. C1-16773 ALL PARTS RUST RESISTANT LINE STRAIGHT NPT1/4 AG ACTIVATION: CLAMPING LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 100 BAR
W1209	300140643 V actuator with pin W1209 f. Type 17 Article no. W1209
TW800 FOR G3/4	300145203 QUICK CONNECTOR TW800, C1-15562-X2 FOR EXTERNAL THREAD G3/4 (CONNECTION ACCORDING TO DIN 2999) DEVICE NO. C1-15562-X2 - WITH THREAD COLLETS AND THREAD SLIPPER FOR EASIER ADAPTION ALL PARTS RUST RESISTANT FRAME SIZE 6 LINE STRAIGHT G3/4 IT ACTIVATION: HANDLE SLEEVE MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR / WATER / OIL / NATURAL GAS TEST PRESSURE: MAX. 50 BAR
C1-85042-X01	TK16-H35HF fueling nozzle for Hydrogen refueling TK16 High Flow Gas a adapter 9072065 WEH@ INOX / INOX Total weight: 2.10 kg TK16-H35 FILLING COUPLING; C1-85042-X01 FOR REFUELING HYDROGEN 5000PSI - VERSION: STRAIGHT - WEIGHT: 2.1KG - GAS RECIRCULATION: YES - MEDIUM NOTE: NOT FOR PRE-COOLED HYDROGEN SUITABLE - CONNECTION SIZE B1: UNF 9-16"-18 AG, SAE J514 37° CONE - CONNECTION SIZE C2: UNF 7/16"-20 AG,ISO 17268.2017-03 SAE J2600:2015-10 ALL PARTS RUST RESISTANT ACTUATION: HAND LEVER MEDIUM: HYDROGEN TEMPERATURE: MAX. 85°C PRESSURE: PS 450 BAR; PT 644 BAR

C1-14764	Art. Nr. 300140535 QUICK CONNECTOR TW17H, C1-14764 FOR INTERNAL THREAD M12X1.5 DEVICE NO. C1-14764 TW17H-W9034-045/LP ALL PARTS RUST RESISTANT SIZE 2 INLET SIDE. G1/4 IT ACTIVATION: HAND LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14769	Art. Nr. 300140694 TW17H M16x1,5 W9036-065 QUICK CONNECTOR TW17H, C1-14769 FOR INTERNAL THREAD M16X1.5 DEVICE NO. C1-14769 TW17H-W9036-065/HP ALL PARTS RUST RESISTANT FRAME SIZE 3 INLET SIDE. G3/8 female ACTIVATION: HAND LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 350 BAR
TYP: 17	
C1-141183	This product contains several materials REACH: CAS-No 7439-92-1, Pb >0.1% QUICK CONNECTOR TW01, C1-141183 FOR INTERIOR. 16.0-18.0MM DEVICE NO. C1-141183 ALL PARTS RUST RESISTANT SIZE 2 LINE STRAIGHT G1/8 IG ACTUATION: PNEUMATIC EXTERNAL CONTROL PRESSURE: 4 - 12 BAR SEALS: NEOPRENE TEST MEDIUM: AIR TEST PRESSURE: MAX. 9 BAR
coupling	Leak test will be done on the hoses in two different sizes in the couplings. I am sharing the relevant parts of the T. pictures showing the hose inner diameter and wall thickness below.
C1-14769	TW17H for internal thread M16x1.5 (TW17-W9036-065/HD), quick adapter WEH® INOX / INOX This product contains other materials REACH: CAS-No 7439-92-1, Pb >0.1% QUICK CONNECTOR TW17H, C1-14769 FOR INTERNAL THREAD M16X1.5 DEVICE NO. C1-14769 TW17H-W9036-065/HP ALL PARTS RUST RESISTANT SIZE 3 LEAD SIDE. G3/8 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 350 BAR
C1-14772	TW17H for internal thread M22x1.5 (TW17H-W9039-085/ND), quick adapter WEH® INOX / INOX This product has several materials REACH: CAS No. 7439-92-1, Pb >0.1% QUICK CONNECTOR TW17H, C1-14772 FOR INTERNAL THREAD M22X1.5 DEVICE NO. C1-14772 TW17H-W9039-085/LP ALL PARTS RUST RESISTANT SIZE 4 LEAD SIDE. G1/2 female OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14768	TW17H for internal thread M16x1.5 (TW17H-W9036-065/LP) Quick adapter WEH® INOX / INOX Customs tariff number: 73269098900 Total weight: 12.00 kg This product has several materials REACH: CAS No. 7439-92-1, Pb >0.1% QUICK CONNECTOR TW17H, C1-14768 FOR INTERNAL THREAD M16X1.5 DEVICE NO. C1-14768 TW17H-W9036-065/LP ALL PARTS RUST RESISTANT SIZE 3 LEAD SIDE. G3/8 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14768 (M16X1,5) 50 bar TW17H	
Adapter 18"	
C1-14772	TW17H for internal thread M22x1.5 (TW17H-W9039-085/ND), quick adapter WEH®) INOX / INOX This product has several materials REACH: CAS No. 7439-92-1, Pb >0.1% QUICK CONNECTOR TW17H, C1-14772 FOR INTERNAL THREAD M22X1.5 DEVICE NO. C1-14772 TW17H-W9039-085/LP ALL PARTS RUST-RESISTANT SIZE 4 SIDE SUPPLY LINE G1/2 IG ACTUATION: HAND LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14768	TW17H for internal thread M16x1.5 (TW17H-W9036-065/LP) Quick adapter WEH® INOX / INOX This product has several materials REACH: CAS No. 7439-92-1, Pb >0.1% QUICK CONNECTOR TW17H, C1-14768 FOR INTERNAL THREAD M16X1.5 DEVICE NO. C1-14768 TW17H-W9036-

	065/LP ALL PARTS RUST-RESISTANT SIZE 3 SIDE SUPPLY LINE G3/8 IG ACTUATION: HAND LEVER MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
TW800 for AG G1/2"	C1-15561 INOX (W8375-065), quick adapter QUICK CONNECTION TW800, C1-15561 FOR EXTERNAL THREAD G1/2" (CONNECTION ACCORDING TO DIN 2999) DEVICE NO. C1-15561 - WITH THREAD COLLETS AND THREAD SLIPPER FOR EASIER ADAPTION ALL PARTS RUST-RESISTANT SIZE 5 STRAIGHT SUPPLY LINE G1/2 IG ACTIVATION: HANDLE SLEEVE MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR / WATER / OIL TEST PRESSURE: MAX. 50 BAR This product contains other materials
TW800 FOR G3/4	QUICK CONNECTION TW800, C1-15562-X2 FOR EXTERNAL THREAD G3/4 (CONNECTION ACCORDING TO DIN 2999) DEVICE NO. C1-15562-X2 - WITH THREAD COLLETS AND THREAD SLIPPER FOR EASIER ADAPTION ALL PARTS RUST-RESISTANT SIZE 6 STRAIGHT SUPPLY LINE G3/4 IG ACTUATION: HANDLE SLEEVE MANUAL SEALS: NBR (BUNAN) TEST MEDIUM: AIR / WATER / OIL / NATURAL GAS TEST PRESSURE: MAX. 50 BAR
TW17H M10x1.5 CONNECTOR (C1-115632)	
TW17H M12x1.5 ISO 6149 (C1-115007)	
TW17H M16*1.5 ISO6149	
TW19M M16x1,5 ISO6149 350 BAR CONNECTOR(C1-18555)	
TW17H M18*1.5 ISO6149	
TW19M M18x1.5 ISO6149 (C1-18456)	
C1-15163 TW19M-SON-BB1-MFG-XD/BG4 M22x1.5	
TW17H UN1 1/16"-12 350 BAR CONNECTOR (C1-14789)	
TW17H 350 BAR UN3/4"-16 (C1-90015)	
C1-86246 TW19M-W9053-085-BB1-XE/BG4/UNF 7/8"-14/MFG/gelb	
TW17H UNF7/8"-14 (C1-14787)	
TW17H 350 BAR UNF9/16"-18(C1-79580)	
C1-141959	This product contains other materials REACH: CAS-No 7439-92-1, Pb >0.1% QUICK CONNECTOR TW02 C1-141959 FOR PIPE OUTSIDE 17.0-19.0MM DEVICE NO. C1-141959 ALL PARTS RUST RESISTANT SIZE 1 SUPPLY LINE STRAIGHT G1/4 IG ACTUATION: PNEUMATIC EXTERNAL CONTROL PRESSURE: 4 - 12 BAR SEALS: NEOPRENE TEST MEDIUM: AIR TEST PRESSURE: MAX. 35 BAR
TW02-1-18 17-19MM FELT	
TYP 17	The following product has a hose inlet of Ø8 and a 3/4, 1/2, 1 and 1 1/4 inch WEH adapter type 17
B200B-142369	REPLACEMENT SEALS F-FEB 1-18 FOR ADAPTER F-FE 1-18 (1 SET CONSISTS OF 5 SEALS) ITEM NAME: F-FEB 1-18 SEALING RANGE: 17.0-19.0MM (1 SEAL / ADAPTER) B200B-142369
C1-12641-X2-X01	TK21 with opening spindle for natural gas
	TVR200-S1-A02-VV-1-GI18-GI18-ES1-PC1 Check valve type TVR200 Opening pressure: 0.10 bar Technical classification according to PED 2014/68/EU Technical specification according to TVR200-1 Medium Water (Fluid Group 2) Intended use Backflow prevention Pressure PS 250 bar

C1-170066	Product family TVR200 Pressure PT 358 bar Product series TVR200-S1 Max. media temperature 200 °C Connection combination A02 - IG/IG Min. media temperature -40 °C Flow direction B1 --> B2 PED nominal diameter (DN) 6 Valve seat Ball seal State Gaseous Installation position any Pressure equipment type Pipeline Spring material 1.4571 Product type Check valve Sealing material FKM Weight 0.15 kg Length L1 56 mm Length L2 56 mm Length L3 10 mm Length L4 10 mm Wrench size SW(1) 19 mm Wrench size SW(2) 19 mm Diameter D1 22 mm Connection standard B1 DIN EN ISO 228-1
TW02-01-03/A=Ø6,6 - 8,6mm	C1-141953 Quick connection for outer diameter, smooth tube Type TW02 must always be secured by a holding device Only in vacuum applications can a holding device can be dispensed with. - P299
TW17H G1 1/4"	TW17H G1 1/4" 50 BAR CONNECTOR
C1-14736	TW17H for internal thread G1/2" (TW17H-W9003-085/ND), Quick adapter WEH® C1-14736 TW17H-W9003-085-BB0-X, C1-14736, INOX / INOX QUICK CONNECTION TW17H, C1-14736 FOR G1/2 INTERNAL THREAD DEVICE NO. C1-14736 TW17H-W9003-085/LP ALL PARTS RUST- RESISTANT BUILDING SIZE 4 SIDE CONNECTION G1/2 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR Note: Maximum product lifespan is 15 years This product contains additional materials. REACH: CAS No. 7439- 92-1, Pb >0.1%
C1-14738	TW17H for internal thread G3/4" (TW17H-W9005-125/ND), Quick adapter WEH® INOX / INOX This product has several materials. REACH: CAS No. 7439-92-1, Pb >0.1% QUICK CONNECTION TW17H, C1-14738 FOR G3/4 INTERNAL THREAD DEVICE NO. C1-14738 TW17H-W9005- 125/LP ALL PARTS RUST-RESISTANT BUILDING SIZE 5 SIDE CONNECTION G3/4 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
TW17H G1 1/4"	This product contains additional materials. REACH: CAS No. 7439-92-1, Pb >0.1% SCHNELLANSCHLUSS TW17H, C1-10393-X1 FR INNENGEWINDE G1 1/4 GERTE NR. C1-10393-X1 TW17H-W9058-165 ALLE TEILE ROSTBESTNDIG BAUGRSSE 7 ZULEITUNG SEITL. G1 IG BETTIGUNG: HANDHEBEL MANUELL DICHTUNGEN: NBR (BUNAN) PRFMEDIUM: LUFT, WASSER, L PRFDURCK: MAX. 50 BAR
TW03 G1/8 ANSCHLUSS	CELL CONNECTION TW03 C1-11821 FOR G1/8 INTERNAL THREAD DEVICE NO. C1-11821 ALL PARTS RUST-RESISTANT CONNECTION VERSION WITHOUT ROTATING FEATURE STRAIGHT SUPPLY CONNECTION G1/8 IG OPERATION: MANUAL BY TURNING SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 345 BAR
W9329	CAP SCREW G1/8 (STEEL) W9329
C1-14738-	TW17H for internal thread G3/4" (TW17H-W9005-125/ND), Quick adapter WEH® INOX / INOX QUICK CONNECTION TW17H, C1-14738 FOR G3/4 INTERNAL THREAD DEVICE NO. C1-14738 TW17H-W9005- 125/LP ALL PARTS RUST-RESISTANT BUILDING SIZE 5 SIDE CONNECTION G3/4 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14730	TW17H for G1/8" INTERNAL THREAD (TW17H-W9000-025/ND), Quick adapter WEH® INOX / INOX QUICK CONNECTION TW17H, C1-14730 FOR G1/8 INTERNAL THREAD DEVICE NO. C1-14730 TW17H-W9000- 025/LP ALL PARTS RUST-RESISTANT BUILDING SIZE 1 SIDE CONNECTION G1/8 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
C1-14732	TW17H for IG G1/4" (TW17H-W9001-045/LP) Quick adapter WEH® INOX / INOX QUICK CONNECTION TW17H, C1-14732 FOR G1/4 INTERNAL THREAD DEVICE NO. C1-14732 TW17H-W9001-045/LP ALL PARTS RUST- RESISTANT BUILDING SIZE 2 SIDE CONNECTION G1/4 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER,

C1-14734	OIL, noble gases TEST PRESSURE: MAX. 50 BAR QUICK CONNECTION TW17H, C1-14734 FOR G3/8 INTERNAL THREAD DEVICE NO. C1-14734 TW17H-W9002-065/LP ALL PARTS RUST- RESISTANT BUILDING SIZE 3 SIDE CONNECTION G3/8 IG OPERATION: MANUAL HAND LEVER SEALS: NBR (BUNAN) TEST MEDIUM: AIR, WATER, OIL TEST PRESSURE: MAX. 50 BAR
TW17...-W9000-025	G1/8"
TW17...-W9005-125	G3/4"
Tw17h G1/2" 50 Bar	
C1-137183	TW800B-SON-BB0/BG1/A=Ø8mm
300204511	
Tw 800 G1/2	
B800bg4-18	
C1-124707	
C1-122696	
Tw17h G1/2"	
C1-14762	
03 91 289116	
300159017 Tw17h-W9052-065/Lp C1-14784	
E51 - 111n	
E09 - 043p	
300140509	
300207131	
300145203	
C1-31219-X2	
300204512	
300145389	
W9325	
E51-87824	
C1-1455	
E60-6031-004	
C1-138190	
E64 - X321	
E51-277n	
C1-141190	
300155891	
F-Jnl1-0938(Ex. F-Jnl1-0937)	
3866069	

C1-14763	
C1-W6891	
C1-16112-X1	TW800B SPECIAL CONNECTOR
Tw800g	
F-Fi6-62	
F-Fe01-01 / Tw02 C1-141950	
B800bg4-16	
B800bg1-5	
C1-84248	
14 X 1,5 Cr	
F-Fi5-51	
3866071	
B800bg3-14	
E13-104841	
E02-503g-W59	
T17v	
Quick Connector - Internal Threads Tw17	
C1-16349 Tw 800b	
C1-99840	
300142043	
B800b-W8380-25	
(C1-76774)	
Tk23	
17hm22x1,5	
C1-16113-X1	TW800B SPECIAL CONNECTOR
C1-104664	
T18v16unf	
C1-57214	
T17-Bg3	
E51-102n	
Tw17h	
Tw141 22mm	
Tw17h G3/4"	
Tn1c1-118225 Ngv Nozzle (Weh Tn1c1-118225 Erdgasgostd-18mm,Dn=5mm)	
C1-114925	

E55-121e056n	
300141810 (Fe F-Fe01-02)	
C1-92534	
Tw 800 G 3/4	
C1-16349	TW800B SPECIAL CONNECTOR PLUG VERSION
17hm24x1,5	
B800b-W8394-125	
C1-14774	
C1-15561 K 73995	
300160577	
Tw17hm12x1,5	
B800b-W8387-085	
T18v14unf	
Jnlm130	
E50-138s519	
300141734 (Fe F-Fe01-03)	
C1-31849	
(C1-60440)	
16-18-Fi-B2-21	
Fi26-28-F-Fib3-33	
C1-16348	TW800B SPECIAL CONNECTOR
17hm30x1,5	
C1-19059	
F-Fi6-61	
300140508	
14 X 2	
C1-17059	
F-Fi6-63	
E50-105 S	
51-251n	
C1-15562-3/4 86879	
C1-15561-1/2 87392	
C1-14785 Tw17h-W9052-065/Hp Artikel: 300140525	
M24-M16	
Ngv2 (C1-35401-X1) *** 220 Pieces	

C1-16199 / 300140588
C1-59243-X01
B81223240008801-B812230332193
C1-15562-X2 K 75319
B800b-W 8386-065
300146227
Fi12-14-F-Fib1-12
C1-84141
T18v18unf
C1-141629
T18v20unf
E64 - X241
E50 - 248n
300145204
F-Fi1-13