

Weka Ag

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Weka Ag Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Weka Ag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
07-33115/05	
07-34837	
07-36253	
25270-1000	
25270K-20061109	
31 130-ND / 3 KABELLANGE 3 M BIETEN	
31130-NK	
31160-NA/3	
31160-NN/10	
31160-Nn/3	Magnetic switch
31967-010-05-2000	
32607-NI-05	

32607-NI-10-1200	
32607-NI-10-800	
32608-ND-10-3500	
33115/05	
33115/30	
33115/40	
33160	
34000-K-500XEAMWG	
34333/05	
34837-1950	
35615/05	
36815-6	
38662/20	
84043	
8723151	
DDD10701	
DK10218	
DK16-18	
DK16208	
DK30102-1	
PM-TEV DN25/PN 25 C-Po, h=600, d=80, 316L-PTFE-NBR	
PM-TEV DN25/PN 25 C-Ps, h=600, d=80, 316L-PTFE-NBR	
Typ 31967	
34000-A-765X	WEKA magnetic level indicator Smartline 50 series Bypass tube material 316/316L; 33.7x2mm with end cap at the top Plug ISO1" bottom Indicator rail: Makrolon for Tmax. +150°C Red-silver aluminum plates Stainless steel float for density >0.8 Design Pmax 40 bar@+20°C Operating data Medium: Oil, IOS-VG68 Operating pressure 9 bar@+85°C Connection length: L=765 mm Connections: top and bottom each G1/2"female Extras: - Production and labeling according to ATEX - Indicator rail with protective tube 80769 - Float for density >0.8
	WEKA measuring sensor ATEX Ex d Output 4-20mA,

32608-ND-10-540	measuring length 540mm Resolution 10mm Cable length 10mtr.
34300-K-700X	WEKA magnetic level indicator Standard 28 series Bypass pipe material 316/316L; 53x1.5mm with end cap at the top Flange cover bottom with drain hole G3/8" Indicator rail: Makrolon for Tmax. +150°C Red-silver aluminum plates Stainless steel float for density >0.69 Design Pmax 28 bar@+20°C Operating data Medium: Gas condensate, density 0.750 Operating pressure 2 bar@+15°C Connection length: L=765 mm Connections: side flanges DN25-PN40, EN1092-1 Extras: - Production and labeling according to ATEX - Indicator rail with protective tube 80769
32608-ND-10-700	WEKA measuring sensor ATEX Ex d Output 4-20mA, measuring length 700mm Resolution 10mm Cable length 10mtr.
MA16A6	
PM-TEQV DN10/PN16	Valve seal kit
31160-NN/3	WEKA magnetic switch bistable switch Stainless steel housing IP68 Cable 3 mtr., PVC
31160-NN/5	WEKA magnetic switch same as item 01, however, cable 5 meters.
31160-NN/10	WEKA magnetic switch same as item 01, however cable 10 mtr.
07-33115/05 Schwimmer	
179 K/200/050/140	
07-36253 Befestigungsschelle	
07-37557/3	
32607-Ni-10-1200	
31160-Nn03	
34000k-500mwg	
07-34000k Nps1a150	
37943-2	
Ddd10701 El. Antrieb Typ Car060 230v 50...60hz, Ip67	
80648	
36815-4	
07-34837 Anzeigeschiene Polycarbonat	