

Wilo

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Wilo Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Wilo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Yonos Maxo Plus 40/0,5-12 Pn6/10 (2120608)	Name: Wet runner standard High efficiency pump *** Pump type TOP-STG 40/10 is no longer in the Wilo delivery and production program! *****
NL80/200-08 180M3 50m	
Helix V 1007-1/16/E/KS/400-50	Designation: high pressure centrifugal pump Item number: 4150548
4016170	Accessories: stainless steel counter flanges (oval, 2 pieces), PN16 / DN40 Item number: 4016170
NP 65/250 - 37/2	RADPUMPE 316 EDELSTAHL
NP 65/250 - 37/2	WELLENPUMPE 316 EDELSTAHL
Stratos MAXO 50/0,5-16 PN6/10-R7	Designation: wet-running premium smart pump 2218005
121084396	
127 4291/10	
1274291/09W41	

1274291/10W22
1274291/9909
2004429
2004431
2006581
2021067
2026901
2026902
2029980
2044184
2044937
2046611
207208
2080053
2080055
2083661
2095504 / Stratos 50/1-12 PN 6/10
2104409
2111845
2113792 / Stratos-Z 40/1-8 PN 6/10
2121052
2150571 / Stratos 65/1-12 PN 6/10
2786094
2786174
2796329
2799716
2799726
2799752
2984656
4007224

4024713 / MVI 406-1/25/E/3-400-50-2
4024729 / MVI 805-1/16/E/3-400-50-2
4027301
4056567
4060456
4060469
4065553
4071198 / MVI 7006-3/25/E/3-400-50-2
4084613
4094075
4095203
4097361
4106350
4118674
4160559
4185162
4521257
605-1/16/E/S/400-50,
6070670
6070671
6079210
6086377
AISI420
HELIX V 1011-1/16/E/400-50
HELIX V 1603- 1/16/E/S/400-50
HELIX V 220-1/25/E/K/400-50 ART. NR.4161728
Helix V 1607-1/16/E/KS/400-50
IL-E 50/220-15/2-R1-L1 ART. 1 2124685/1202
IPL 40/110-0,12/4 PN 6/10 -S2

IPn 40/160-0,55/4, art.120 909
499/0310
MG12/22-Z
MHI 206-1/E/3-400-50-2
MHI 803-1/E/3-400-50-2
MHI 804-1/E/3-400-50-2
MHIL504-E-3-400-50-2/IE3 (4210656)
MVI5204-11/2-T-3-E
MVIS 410-1/16/K/3-400-50-2
PSN-X
RSD 30/6, 230V
S 40/60 DM 200/440V Oil - H
S 40/60 PN6 OIL
S40/60
S40/60DM
Top STE 40-15
TOP-S 40/7 (400/230V, ÇÒ 6/10)
TOP-S 50/15, 220/380V
TOP-S25/7
TOP-S30/10
TOP-S40/4
TOP-S40/4 DM 200/440V50/60HZ OIL3H TRANS
TOP-S40/4 DM 200/440V50/60HZ OIL3H TRANS (P/n.2111845)
TOP-S50/10 DM/PN6/10
TOP-SD 50/15 (3-400/230 V, PN 6/10)
TOP-STG 40/15
TWI 6.1817-B 9,3 KW + SMR6-930T (DOL) 9,3 KW
V 1603- 1/16/E/S/400-50, 4201316
VeroTwin-DPL 50/130-2.2/2
Z 25/6 M

[Helix V 2212-1/25/E/KS/400-50](#)

High pressure centrifugal pump Highly efficient high-pressure centrifugal pump in vertical design with inline connections. The normal-suction high-pressure centrifugal pump has an overall compact design and is easy to maintain. The pump shaft and the motor shaft of the IEC standard motor are connected using a shell coupling and a separate lantern ball bearing ensures optimal absorption of axial forces. Intermediate bearings in the hydraulics and corrosion-resistant shaft with stainless steel sleeve ensure a long service life. Special, permanently attached lifting eyes enable the pump to be easily installed. The pump is suitable for use in water supply and pressure boosting, in industrial circulation systems as well as in process water circuits and closed cooling circuits. It can also be used in fire extinguishing systems, washing systems and for irrigation. Special features/product advantages - Efficiency-optimized, laser-welded 2D/3D hydraulics with flow and degassing optimization - Corrosion-resistant impellers, guide vanes and stage housing - Volume flow and NPSH-optimized pump housing - Maintenance-friendly design with particularly robust coupling protection - Drinking water approval for pumps with medium-contacting parts made of stainless steel (EPDM version) Scope of delivery - Wilo-Helix V high-pressure centrifugal pump - Installation and operating instructions Notes on the design - The motor protection for the three-phase motor is available on request or must be provided on site - Single-phase AC motor with built-in thermal motor protection and capacitor - The standard position of the terminal box is aligned with the suction flange, but this can be changed if required - The Wilo-Helix V is equipped with a user-friendly mechanical seal in cartridge design and with a standard Seal for easy maintenance - The removal coupling (at ≥ 7.5 kW) enables the mechanical seal to be replaced without removing the motor - The flexible lantern design, available in two orientations, enables direct access to the mechanical seal - For the pump versions PN 16, PN 25 and Pmax = 30 bar, round counter flanges made of gray cast iron or stainless steel, screws, nuts and seals are available as accessories - Bypass sets are available as accessories - Wilo-Helix V(F) in VdS-certified version available on request. Operating data Flow medium: water 100% Flow temperature: 20.00 °C Concentration of the conveyed medium: 100.00% Requested volume flow: Requested delivery head: Product data Min. media temperature: -20 °C Max. media temperature: 120 °C Max. ambient temperature: 50 °C Maximum operating pressure: 25 bar Maximum inlet pressure: 10 bar Minimum efficiency index (MEI): ≥ 0.7 Motor data Mains connection: 3~400V/50 Hz Voltage tolerance: $\pm 10\%$ Rated motor power: 15 kW Motor efficiency class: IE3 Rated current: 26.7 A Rated speed: 2,900 rpm Power factor: 0.88 Motor efficiency 50%: 90.2% Motor efficiency 75%: 91.8% Motor efficiency 100%: 91.9 % Insulation class: F Protection class: IP55 Materials Pump housing: 1.4301 Impeller: 1.4307 Shaft: 1.4057 Shaft seal: BQ7EGG Seal material: EPDM Installation dimensions Suction-side pipe connection: DN 50, PN 25 Pressure-side pipe connection: DN 50, PN 25

[Scott pump X25975](#)

Serial number A068J300B03AF: 1)3 sets of service kits (

	seals, bearings)"
see list	
Yonos MAXO plus 50/0,5-16 PN6/10	<p>2120613 high-efficiency pump Wilo-Yonos MAXO plus electronically controlled, wet-running circulation pump, synchronous motor according to ECM technology and integrated power control for stepless Differential pressure control. Can be used for all heating, ventilation and air conditioning applications. Standard with: - Preselectable control modes for optimal load adaptation: Δp-c (differential pressure constant), Δp-v (differential pressure variable) - 3 speed levels (n = constant) - LED display for setting the setpoint and display error messages - Electrical connection with the Wilo plug - Fault light and contact for collective fault message - thermal insulation shell For flange pumps - flange versions: - Standard version for pumps DN 32 to DN 65: combination flange PN 6/10 (flange PN 16 according to EN 1092-2) for counter flanges PN 6 and PN 16 - Standard version for pumps DN 80 / DN 100: flange PN 6 (designed PN 16 according to EN 1092-2) for counter flange PN 6 operating data Pumped medium: Water 100% Media temperature: 20.00 °C Requested volume flow: Requested funding amount: Min. media temperature: -20 °C Max. media temperature: 110 °C Min. ambient temperature: -20 °C Max. ambient temperature: 40 °C Maximum operating pressure: 10 bar Minimum inlet height at 50°C: 7 m Minimum inlet height at 95°C: 15 m Minimum inlet height at 110°C: 23 m engine data</p>
TMW32/11	
Stratos MAXO 50/0,5-16 PN6/10	1,43 kW 230V 50Hz VSD DN50 DN50
PUMP	<p>MVI 808-1/16/E/3-400-50-2 H(m): 80M Q(m³/h):6 ,20 m³/h pmax(bar)16 bar Tmax(c):120 c n(n/m):2900 rpm KW :3 Hz : 3~ 400 V / 50 Hz A: 5,50 A CosQ:0,89 IP:IP 55</p>
DIAPHRAGM	<p>IAPHRAGM EXPENSION VESSELS-LRS SERIES type:VERTICAL TYPE LRS 1500/10 volume:1500 lt kg:263 pmax(bar)10 bar ptest(bar)15 bar Po (bar): 4 bar type of membrane:EPDM/BUTYL Tmin/Tmax:-10 c/+90 c</p>
TYP IPL L65/115-1,5/2-IE2	
2158821	
Trm4-55m	
Mv1803-1/16/E	
Top-S30/10 , By Stratos 30/1-12 Pn 10	
DI 80/220-30/2	
111274291/07w03	
Mh62133-336	
Ipl 30/85- 0,18/2 Pn 10	

Ipl 65/130- 4/2 Pn 10	
Ipl 50/130-0.37/4	
4024285	
Ksl 15-5	
2004593	
2042732	COUPLING / SAFT CONNECTION KIT
Helix V 613-1/16/E/400-50	
Cronotwin-DI 80/120-4/2	
Star-Stg 15/6	
Ipl 65/140-4/2obsolete,Replacementipl 65/130- 4/2 Pn 10	
Ipl 65/145- 5.5/2 Pn 10	
NI50/315-45-2-12(Ex.Npg65/315-37/2- 12)	
458	
Psn-X Schwimmerschalter Mit Dem Kabel Lang20m	
2040968	
Mhi 206-1/E/3-400-50-2	
495	
Aqlvgg	
348	
2006581 By Ipl 40/110-0,12/4 Pn 16 - S2-440v-60hz	
Rs25/7-3	
S40/60 Oil Pn6,1274291/9909 , Ipl 40/110-0,12/4 Pn 16 -S2-440v-60hz	
Typ : Ipl 40/110-0,12/4 Pn 16 S2-440v- 60hz	
4048414 Tmw 32/11	
Ipl 80/115- 2.2/2 Pn 10	
Mhi 804-1/E/3-400-50-2	
2799726 Sibooost Smart 3 Helix Ve 611	

O-Ri?Ng	
6019739	
Mhi 406n 3~400/1.4404/Viton Pn10	
Mecani?Cal Seal	
Coe-3helix V 1608	
4063802/0604	
Decanter Fattening Water Pump	Decanter Fattening Water Pump Dekanter-Mastwasserpumpe
110681292	
NI50/315-45-2-12	
Type:Smr455m, Nr:22/0213/09 - Old Code, Trm4-55m - New Code	
4186440	
Yonos Stg 30/1-7,5	
341	
II 65/150- 0.75/4	
6042686 / 2012w19	
111321399	
Pumpe Wilo-Multivert Mvi 16/6-1/16/E/3-400-50-2	
Top-S-25/7	
Sentrat Pump	SENTRAT PUMP SENTRAT-PUMPE
4024289	
Pumpe, Grauguss, Dn 25, Pn10 Pb 400	
69mb7gx546u	
Mhi830-1	
6064734	
NI80/250-37-2-12(Ex.N65/250v-37/2-12)	
Yonos Pico 15/1-6 /130mm/	
NI65/250-37-2-12(Ex.Np65/250v-37/2-12)	
495.1	
Pumpe, Grauguss, Dn 20, Pn6 Mvi 104	

Yonos Maxo 40/05/-4
Type: Rs15/6-3p No: 4521257
Mvi2/4/8/16-6quot;Ep120;Set
Hwj-202-Em
120910792/9603
4149741
Lrs 500/10
Ipn40/160
Mvi 805/ Pn16 3~
Ip E 50 130
S40/10
Verotwin-Dpl 40/220-1,5/4-L1-S1, 230/400v
Helix V 1011-1/16/E/400-50
Ipl 40/90- 0.37/2 Pn 10
2158887
Helix V 220-1/25/E/K/400-50 Art. Nr.4161728
Ipn50/160
4106358
4149100
2029313 COUPLING / SAFT CONNECTION KIT
Wilo-Wao65 Schwimmerschalter Mit Dem Kabel Lang20m
4195486
Fa08.23w+t13-2/16k-C0
656747050
S30/10
461
II-E 50/220-15/2-R1-L1 Art. ? 2124685/1202
Mvi5204-11/2-T-3-E
Kf72w182s3/G

NI50/315-45-2-12(Ex.Np65/315a-37/2-05)	
Ipe 65 115 1.5	
2027227	COUPLING / SAFT CONNECTION KIT
2065874 Sts 40/10 A	
Pico 25 / 1-6	
Wilo-MS1 Schwimmerschalter Mit Dem Kabel Lang20m	
NI125/200-75-2-12	
NI65/250-30-2-12(Ex.Np50/250v-30/2-12)	
Cronotwin-DI-E 125/220-7,5/4	
2158826	
Pumpe Wilo-Multivert Mvi 5202-3/16/E/3-400-50-2	
4067795	
Impeller Bronz 1 (338 Mm)	
Mvi802 - 1/16/E	
Ks9	
2799752 Sibost Smart 2 Helix Ve 1605	
I?Mpeller Nut	
P80	
2109772/13w22	
Pump Shaft Aisi420	
S40/60 Oil Pn6/10 Nicht Mehr Im Lieferprogramm, Alternative Typ : Ipl 40/110-0,12/4 Pn 16 S2-440v-60hz	
2120660	
II 50/170-5,5/2	Pumpe
6064709	
489	
Wilo-Wa65 Schwimmerschalter Mit Dem Kabel Lang20m	

Decentral Line Pump	DECENTRAL LINE PUMP DEZENTRALE LINE PUMPE
Ipn 40/160-0,55/4, Art.120 909 499/0310	
BI100/270 11/4-E1 -	
Coupli?Ng Key	
Impeller Key	
NI50/250-15-2-12(Ex.Np40/250v-15/2-12)	
2096384	60X90X10
II 50/110- 1.5/2	
Yonos Maxo-D 65/0,5-12	
Yonos Maxo 40/05-8	
Prov0269	
Ipl80/140-1,1/4	
Ipn50/140-2.2/2	
Stratos 30/1-12 Pn 10	
Twi 6 1827 B Wilo	P:15KW Q:17 M3/H QMAX:23 M3/H H:211 M HMAX:290 M
NI50/250-15-2-12(Ex.Np40/250v-15/2-05)	
2097522	
Mvie 806-1/16/E/3-2	
2799716 Sibost Smart 2 Helix Ve 611	