

Witzenmann

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Witzenmann Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Witzenmann Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
06901.0400.0020.20	do: 14 mm , BDRD-NI-14-20,2-1TF, P.R. : 20,2 BAR, N id: 92056, AR: 131491-PT:31 BAR
1217540	
1217542	
1217550	
1217552	
1217555	
1217556	
1217579	
1217595	
331390	
331394	
331398.	
331462	
331464	
331466	
331468	
331470	
331472	
331474	

Ürün	Açıklama
87526	
87528	
ARF 10,0065,080,2	
DN 40	
DN200/PN25	
ICP-N1/TPA-1.4404 PN16	
LBR25.0150.102.0	
LFR 25.0250.070.0	
LRR 63.0200.053.0	
LRR16.0250.052.0	
LRR25.0250.051.0	
NA50S	
RS 331	
RS 331 S12 , DN65	
RS 331L12 DN	
RS331 S12 , DN50	
RS331L12-016	
RS3631L12-050	
S235JR	
S235JR (23.0400.150)	
S235JR (43.0300.150)	
S235JR(43.0400.150)	
W.HOSE DN125/PN16,L=13M, RS331S12	
WRN 25.0400.062.0	
Type AFN 02.0125.081.0	HYDRA Axial - Expansion joint with welded flanges Drawing no.: 6224913

Ürün	Açıklama
	DN 125, PN 2.5 Bellows material 1.4541 Length: 215mm Round flange (left) acc. to EN 1092-1 Type 01 PN 6 Seal face A from 1.0460 Round flange (right) acc. to EN 1092-1 Type 01 PN 6 Seal face A from 1.0460 Test scope and marking acc. WITZENMANN standard test: - Tightness test Documentation: - Inspection certificate acc. to EN10204 3.1 - Materials certification
ZN_202206011112116_1926	
ZN_2022060111168_17222	
ZN_20220601154946_16641	
ZN_20220603105142_19631	
ZN_2022060310584_12294	
ZN_20230724155147_7958	
RS331L12	3/8"
S-VHN6-G	3/8" 280bar
700 mm	Operating temperature: 20 degrees C Operating pressure: 16 bar, dynamic Design pressure: 16 bar Medium: water (assumed) Hydra corrugated hose, normal corrugated RS 331L12 DN 8 1.4404 - RG 1.4301 Connection on both sides: NA22S, DN 8, - Union nut G 3/8" with Whitworth pipe thread ISO 228/1 - Flat sealing collar socket Length: 700 mm Stamping: HH Hydra [MM/YY] Fauf DN8 RS331L12 1.4404 Testing in accordance with APZ 3.1 D Testing with nitrogen, test pressure: 24 bar
750 mm	Operating temperature: 20 degrees C Operating pressure: 16 bar, dynamic Design pressure: 16 bar Medium: water (assumed)

Ürün	Açıklama
	Hydra corrugated hose, normal corrugated RS 331L12 DN 8 1.4404 - RG 1.4301 Connection on both sides: NA22S, DN 8, - Union nut G 3/8" with Whitworth pipe thread ISO 228/1 - Flat sealing collar socket Length: 750 mm Stamping: HH Hydra [MM/YY] Fauf DN8 RS331L12 1.4404 Testing in accordance with APZ 3.1 D Testing with nitrogen, test pressure: 24 bar
800 mm	Operating temperature: 20 degrees C Operating pressure: 16 bar, dynamic Design pressure: 16 bar Medium: water (assumed) Hydra corrugated hose, normal corrugated RS 331L12 DN 8 1.4404 - RG 1.4301 Connection on both sides: NA22S, DN 8, - Union nut G 3/8" with Whitworth pipe thread ISO 228/1 - Flat sealing collar socket Length: 800 mm Stamping: HH Hydra [MM/YY] Fauf DN8 RS331L12 1.4404 Testing in accordance with APZ 3.1 D Testing with nitrogen, test pressure: 24 bar
850 mm	Operating temperature: 20 degrees C Operating pressure: 16 bar, dynamic Design pressure: 16 bar Medium: water (assumed) Hydra corrugated hose, normal corrugated RS 331L12 DN 8 1.4404 - RG 1.4301 Connection on both sides: NA22S, DN 8, - Union nut G 3/8" with Whitworth pipe thread ISO 228/1 - Flat sealing collar socket Length: 850 mm Stamping: HH Hydra [MM/YY] Fauf DN8 RS331L12 1.4404 Testing in accordance with APZ 3.1 D Testing with nitrogen, test pressure: 24 bar
Hydra – Hose Coupling – 32x20x20	DIN EN ISO 288/1 – X10CrNiTi 18-10 (1.4541) – – Art. Number: MA22S
Hydra – Hose – 13,7x800 – Art. Number: RS331S12	
SPC x Hose coupling-32x20x20-DIN EN	

Ürün	Açıklama
ISO 228/1-X10CrNiTi18-10 x Hydra x MA22S	
SPC x Hose-13.7x800 x Hydra x RS331S12	
HYDRA Metal bellows	bellows type BAO 14.6 x 21 x 1 x 0.1 13W 1.4571 Drawing no.: 6310751
Alternative	HYDRA Metal bellows bellows type BAO 14.6 x 21 x 1 x 0.1 13W 1.4571 Drawing no.: 6310839
Arz 25.0500.150.1	
Dn 100 Wfk	
Dn100/Pn25,L=17 M, Rs331s12	
Dn 125 Wfk	
Dn 125 Wfn	
Arz 25.0250.150.1	
Dn 20	
Dn 100 Wfn	
Elaflex-Erv-T-Dn50	
Dn150x1000 Pn25	
Dn100x1000 Pn25	
06900.0400.0005	
Dn 150 Wfk	
Dn400-16\"-Aod3	
Elaflex-Erv-T-Dn150	
90049524	
Dn 300 Wfk	
Dn80/Pn25, L=13 M, Rs331s12	
Rs331l12dn80nl1200	
79972	

Ürün	Açıklama
Lbr25.0100.050.0	
Dn 80 Wfk	
Dn200x1000 Pn25	
Dn 200 Wfn	
Elaflex-Erv-T-Dn80	
Dn 150 Wfn	
Dn 65 Wfn	
Dn 250 Wfn	
Dn 80 Wfn	
1850040-50.077	
Dn50/Pn25,L=10 M, Rs331s12	
Dn 32	
Dn 65 Wfk	
Dn 250 Wfk	
Dn200/Pn25,L=13 M,W/Clamp Rings, O2 Hose	
Dn32/Pn25,L=7,6 M, Rs331s12	
Dn 300 Wfn	
Dn 50 Wfn	
Dn 200 Wfk	
Dn 50 Wfk	
Arz 16.0200.150.1	
Dn 25.	