

## Yamatake



Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Yamatake** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Yamatake T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Avp302-Lsd2d-Xxxxx</a>	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) with HART communication protocol ATEX Intrinsicly safe Air piping connection : 1/4 NPT Electrical connection : M20x1.5 Finish : standard (Baked Acrylic) Direct action Supply pressure classification : 150<Ps≤300kPa Scale unit : bar
<a href="#">APM-D3E1</a>	PROXIMITY SENSOR
<a href="#">FL2B-4J6-E</a>	
<a href="#">DIGITAL INDICATING CONTROLLER</a>	CP-UM-1586E SDC31
<a href="#">FL7M-3J6HD-L5</a>	PROXIMITY SENSOR
<a href="#">SL1-E</a>	LIMIT SWITCH
<a href="#">SL1-BK</a>	LIMIT SWITCH
<a href="#">C26TC0UA5200</a>	DIGITAL INDICATING CONTROLLER
<a href="#">83104848-001 + PTM-24F17-01</a>	24V 11MF 50/60 HZ LOT 6A3E 250/300RPM
<a href="#">0548U</a>	
<a href="#">0540U</a>	
<a href="#">1LS10-J</a>	Limit Switch
<a href="#">SL1-P</a>	Mikro-Schalter
<a href="#">MODEL:HGC MODEL:HGC303</a>	Part No : R-95348-41-085
<a href="#">EN60947-5-1</a>	
<a href="#">LJS-E7312</a>	LIMIT SWITCH
	Range 0-10 KG/cm2 Max WP 35 kgf/cm2 Cal RNG 4mA-0-----

<a href="#">STG940-E1L-00000-W-E9</a>	-20mA -10 kgf/cm Supply 11-42 VDC Design Pressure 0-8 kg/cm2 Working Temperature 175 �C
<a href="#">Y226</a>	
<a href="#">FL2B-4J6</a>	PROXIMITY SENSOR
<a href="#">HPJ-R22</a>	HPJ-R22 10.8-26.4VDC PNP OUTPUT
<a href="#">R4075341101</a>	
<a href="#">R4075341041</a>	
<a href="#">LDV-5402</a>	
<a href="#">STEAM VALVE WITH POSITIONER</a>	VALVE PROD. NO: R-08344-41-030 TAG NO: TCV9031 RANGE: 0,8-2,4 KGF/CM2 SUPPLY: 2,8 KGF/CM2 MODEL: AGVB SIZE: 2.1/2B POSITIONER MODEL: HEP 17-12BLRY3NNSD-A1-X INPUT: 4/20mA DC DATE: JUL 98 FLANGE PH2-VC8 2-1/2 10K-150 S
<a href="#">SL1.A</a>	
<a href="#">SL1-E</a>	
<a href="#">SL1-D</a>	
<a href="#">APM-D3D1F</a>	PROXIMITY SENSOR
<a href="#">BALL FLOAT TYPE MC94J</a>	SC24MC2640 LOW WATER LEVEL FO CUT-OFF DEVICE
<a href="#">FE8B-TLC5-913</a>	sensor
<a href="#">AVP300-PSD3A-1DYN-X</a>	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) without travel transmission P: Water-proof Air piping connection : 1/4NPT Electrical connection : 1/2 NPT S: Finish standard D: Direct Action - Air pressure increases with Control signal increase 3: Supply pressure classification : 300<Ps≤400kPa A :Scale unit : kPa 1: Model KZ03 Pressure Regulator with Filter (Mounted on Positioner) D: Material of Bracket / Bolt : SUS304 / SUS304 YN: Brackets for actuator : HA2,3, HL2,3 X: Option: None
<a href="#">LOVS-5204S</a>	
<a href="#">MC94J</a>	float switch
<a href="#">SI1-D</a>	LIMIT SWITCH
<a href="#">Ms052501y</a>	
<a href="#">Fl2s-4j6sd-Cn03</a>	SENSOR Please look at the attachement
<a href="#">Fl7m-3w6hwt-Cn03</a>	
<a href="#">Vcx-7001</a>	
<a href="#">En60947 - 5 - 1</a>	
<a href="#">SI1-A</a>	Limit Switch

<a href="#">Avp300-Fsd5b-1xxx-X</a>	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) without travel transmission. FM Explosionproof and Flameproof Air piping connection : 1/4 NPT Electrical connection : 1/2 NPT Direct action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter
<a href="#">Hpj-T21</a>	PHOTOELECTRIC SENSOR
<a href="#">072 4p SI I-M</a>	Switch
<a href="#">FI7m 10j6w Cn03</a>	
<a href="#">SI1-Dkl</a>	
<a href="#">0736p Dc-12 5a-24v</a>	SL1-HFXC2
<a href="#">Sta923-E1g-00000-7-E9</a>	
<a href="#">Lds-5200k</a>	
<a href="#">FI7m-7j6hw-Cn03</a>	
<a href="#">Kk-0002-E-8000212</a>	
<a href="#">FI7m-15y6w-910</a>	
<a href="#">Fe7c-Twc6wr</a>	
<a href="#">FI2r-4j6sd-L2</a>	PROXIMITY SENSOR
<a href="#">Mtg18a-200pd2lseaahx-Xx-K</a>	
<a href="#">1ls1-Jgec</a>	
<a href="#">Mgg18d-200p21ls5aaa-Xx-Y</a>	FLOWTUBE METER 8IN 3000 PLUS
<a href="#">Mtg18a-100pd2csdaahx-Xx-X</a>	
<a href="#">FI7m-15w6w-Cn03b</a>	
<a href="#">FI7m-2j6hd</a>	
<a href="#">SI1-Akl</a>	
<a href="#">Avp300-Fsd5b-1xxx-W</a>	Smart Valve Positioner 300 Series Analog Signal(4 to 20mA.DC.) without travel transmission. FM Explosionproof and Flameproof Air piping connection : 1/4 NPT Electrical connection : 1/2 NPT Direct action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter Reversing Relay for double acting actuator
<a href="#">SI1-Hkl</a>	
<a href="#">FI2-20b65</a>	
<a href="#">FI7m-7j6hd-L5</a>	
<a href="#">FI7m-1p5a6-Cn03 / Npn M8 Keine</a>	

<a href="#">N¼herungsschalter M12 Einsatzmaterial</a>	
<a href="#">Avp200-Esd5b-15xx-Mu</a>	Smart Valve Positioner 200 Series Analog Signal(4 to 20mA.DC.) without travel transmission TIIS Flameproof with cable gland Air piping connection : Rc1/4 Electrical connection : G1/2 Direct Action Supply air : 450<Ps≤700kPa Scale unit : kgf/cm2 Model KZ03 Pressure Regulator with Filter (Mounted on Positioner) cable length : 5m With terminal box for remote cable assembly (Standard) Stainless mounting kit of a positioner side and pressure regulator with filter
<a href="#">FI2-B-4j6-E</a>	
<a href="#">FI7m-10k6we-910</a>	
<a href="#">Fe8v-Ta6-903-Cn08</a>	
<a href="#">Mgg18d-005p21ls5aaa-Xx-Y</a>	ELECTRODE
<a href="#">Mgg14c-Cb4h-Xbxx-Yah</a>	FLOW METER MAGNEW 3000 PLUS
<a href="#">Fe7c-Twc6we</a>	
<a href="#">Fe8v-Ta6;</a>	
<a href="#">FI7m-10j6w-Cn03</a>	
<a href="#">FI7m-3j6hw-Cn03</a>	
<a href="#">SI1-Ek</a>	LIMIT SWITCH