

Ytc

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Ytc** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ytc T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
YT-2500LSI2301S	Smart positioner YT-2500 Acting: Simple Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G1/4" Cable gland thread : G½" Communication: None Option: Feedback signal Temp¼rate: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
repair kit 310	
YT-310	Seri:31212729
YT-2500RSI5221S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : Namur Air connection type : NPT1/4" Cable gland thread : ½" NPT Communication: HArtt Option: Feedback signal Temp¼rate: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : Diam 1 Connection type : PT1/4" Dome cover Option:

YT-1000RDN521S10	Without Temprature: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2.8 kg / 4.2 kg Dim : 27 x 20 x 20 cm
YT-1000RDN521S13	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Limit switch (Internal) Temprature: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-1000RSN532S15	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal: 4-20 mA Proof: None Lever : Namur Orifice type: None Connection type: NPT1/4" Dome cover Option: Feedback signal + Limit switch (Internal) Temperature: -20 to 70°C Material: Aluminum
YT-310N1	Volume booster YT-310 N1 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temprature: -20 .. 70°C Material : Aluminium Net weight / Brut : 2.3 kg / 2.5 kg Dim : 18 x 14 x 14 cm Origine : South Korea Code HTS : 848110999
YT-1000RDN521S11	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Feedback signal Temprature: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-2501LSI2321S1	Smart positioner YT-2501 - Linear Acting: Single Input signal : 4-20 mA Ex-proof : ATEX -Ex ia IIC T5/T6 Gb Lever : 20 ~70 mm Air connection type : NPT1/4" Cable gland thread : ½" G Communication: HART Option: Feedback signal Feedback module : SPTM Temprature: -30 à 85°C Material : Aluminium No Included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
G1/4//YT-2500LSI2321S	
YT-2500LSI2321S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Temprature: - 30 à 85°C Material : Aluminium
YT-3303RSN1201S	Smart positioner YT-3300 Acting: Double Input signal : 4-20 mA Ex-proof : without Lever: M6 X 34 L Connection type : N1/4" Cable gland thread : ½" G Communication: HART Option: Without Temprature: -30 à 85°C Material : Aluminium Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
YT-3400RDC5103S	Smart positioner YT-3400 Acting: Double Input signal : 4 ~20 mA Ex-proof : Exd IIC T6 Lever : Namur Connection type : Rc 1/4" Cable gland thread : ½" Communication: without Option: Feedback signal & limit switch (Electronic version) Temprature: -30 à 85°C

YT-2500RDI2121S	Smart positioner YT-2500 Acting: Double Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : M6 X 63 L Connection type : Rc 1/4" Cable gland thread : 1/2" G Communication: Hart Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium
YT-310N2	Volume booster YT-310 N2 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temprature: -20 ..120°C Matreial : Aluminium
YT-1000RDI521S00	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : Ex dmb IIB T5 (kcs) Lever : Namur Orifice type : type 2 Connection type : PT1/4" Dome cover : None Flat indicator Option : None Temprature: -20 à 70°C Material : Aluminium Bracket included
YT-300N1-1/4 NPTF	
YT-320N1-1/2 NPTF	
YT-405SN2	Lock-up valve YT-400- Acting: Simple Agreement: Ex Air connection: NPT 1/4" Air signal: NPT 1/4" Maximum pressure: 10 B Pressure signal: 1.4~7B max Temperature: -20 ~ 120°C Material: Aluminum Net weight / Brut: 1.3 kg / 1.5 kg Dimensions: 11 x 10 x 10 cm
YT-405DN2	Lock up valve - YT 405 Acting: Double Connection: NPT1/4" Temperature: -40 to +120°C Material: Stainless steel 316 Poids Net/Brut: 1.5kg/1.7kg Colisage: 10.5 x 9.5 x 9.5 cm
YT-1000RDM532S00	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal: 4-20 mA Ex-proof: Ex dmb IIB T5 Lever : Namur Orifice type: None Connection type: NPT1/4" Dome cover: None Option: None Temperature: -20 to 70°C Material: Aluminum Origin: South Korea Code HTS: 8481109990 Net weight / Brut: 3.6 kg / 4.5 kg Dimensions: 30 x 20 x 30 cm
L1 - YT-200BN210	Air filter regulator YT-200 Adjustable Range: 0 to 0.84 M Pa - Agreement: ATEX II 2 G & D Maxi supply: 17 B Connection type: NPT1/4" Gauge: 0 to 1 M Pa Air filter: 5 µ Temperature: -20 to 70°C Drain: Manual Material: Aluminum Net weight / Gross:
YT-3300	Smart positioner YT-3300 Acting: Double Input signal : 4-20 mA Ex-proof : without Lever: M6 X 34 L Connection type : N1/4" Cable gland thread : 1/2" G Communication: HART Option: Without Temprature: -30 à 85°C Material : Aluminium Bracket mouting included
YT-2500	Smart positioner YT-2500 Acting: Double Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : M6 X 63 L Connection type : Rc 1/4" Cable gland thread : 1/2" G Communication: Hart Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium Bracket mouting included
Yt-400sn1	
Yt-205an110	
Yt-1000rdn521s10	

Yt-2500Isi1321s	
Yt-200an01	
Yt-310n1	
Yt-3300ldn4201s	
Yt-1000ldi111s0	
Yt-520s21	
Model: Yt-2500, Lsn2221 S	
Yt-200bn010	
Yt-200bn210	
Yt-320n1,Pro. ˆ:12fa2,Max Air: 1mpa,Npt 1/2	
Yt-300 Not Complete	
Yt-520d22	
YT-320N1	Volume booster YT-320 N1 Connection: NPT 1/2" Connection signal: NPT1/4" Maximum pressure: 10 B Pressure signal: 7 B maxi Temperature: -20 to 70°C Material: aluminum Net weight / Brut: 0.8 kg / 1 kg Dimensions: 12 x 11 x 11 cm
Yt-1000rdm522s10	
Yt-1000ldm231s0	
E / P Switch Positioner For Model : Yt 1000 Rdn 52110	
Yt-1000 Ldm231so S/N:K0513997	
Repair Kit For Yt-310	
Yt-1000rdn521s13	
Yt-300p1	
Yt-300 Volume-Enhancing, Repair And Maintenance Kit	
Yt-200	
Yt-2500Isi1322s	
E / P Positioner For Model : Yt 1000 Rdn 52110	
Yt-850m411	
	Volume booster YT-300 N1 Connection: NPT1/4" Maximum pressure: 10 B Pressure signal: 7 B maxi Temperature: -20 to

YT-300N1	70°C Material: Aluminum Net weight / Brut: 0.5kg / 0.7kg Dimensions: 10.5 x 9.5 x 9.5 cm
Yt-1000 Rdn13114 Ra - , By Yt-1000 Rdn131s14	
Yt-1000lsm111s3	
Yt-200 Repair Kit For Air Filter Regulator	
Yt-310n	
Yt-320-N2	
Yt-2500lsn120 4s	
Yt-1000rdn531s13	
Electro Pneumatik Rotary Positioner Yt-1000 Rdm	S/N 12051781 1 set will be use with 4 " butterfly valve and 1 set will be use with 3" Butterfly valve Please see attached Photo
Yt-3450	