Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Zae Antriebssysteme

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Zae Antriebssysteme Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zae Antriebssysteme Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Typ: Sw156-0004/35-Oox-3:1-3500	ZAE servo bevel gearbox in engine version Type: 0004 Operating situation: 3 Mounting side: 5 Variants: OOX Translation: 3: 1 Drive speed: 3500 rpm Square servo mounting flange: □ 200 mm Bolt circle servo mounting: ø 215 mm Centering diameter servo mounting: ø 180 mm Servo coupling for shaft end: ø 38x80 mm Oil filling: Klübersynth GH6-080 Primer: 2-component epoxy base RAL9110, white Painting: RAL 9005, deep black, satin gloss suitable for mounting a Siemens motor Type 1 PH 6101 X = identical in construction with customers Article no .: 35057617 Product number: 8483 40 25 Your item no .: 35057617
W199 0003/44	
Typ: M080F-1300/65-HOX-53.0:1-1500-155-32x60	Worm gear for motor mounting Gear arrangement : 1300/65 Variants : HOX Actual ratio : 53.0:1 Drive speed : 1500 rpm Oil filling : Klübersynth GH6-460 Primer : 2-component epoxy base RAL9110, white Paintwork : without H = Hollow shaft with clamping set HSD50-22 on page 6 X = Gearbox suitable for motor attachment with: Flange square : 155 mm Bolt circle diameter: 165 mm with 4x diam. 11mm Centering diameter : 130 mm for motor shaft end : diam. 32 x 60 mm lg. without key

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Motor coupling with clamping set HSD36-22 F flange on side 5 and 6 Gear adjusted for low backlash (backlash at operating temperature 5'-14') A notice: Design as supplied under 506976/0002.
MW 156 0004/35	No: 469491 İ : 3:1 Oil: GH6-032
SW 156 0004/35 578525 / 007	
n. Zg. 20-0693-M/3	special transmissions dimension sheet 20-0693-M/3 with grease filling BP Energrease LS0 Actual ratio: 38:1 Paint: RAL 9018 Weight approx. 8 kg
35050284	Typ: Sw156-0004/35 No: 578525 / 007 i 4:1 Oil Klübersynth GH 6-80
587495/40	
S100B-1300/11-OOX-40.0:1-300	Gear arrangement: 1300/11 Variants: OOX Actual gear ratio: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without key Oil filling: Klübersynth GH6- 460 Primer: 2-component epoxy base RAL9110, white Paintwork: without
Typ: S100B-1300/11-OOX-40.0:1-300	Worm gear Gearbox arrangement: 1300/11 Variants: OOX Actual translation: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without keyway Oil filling: Klübersynth GH6-460 Primer: 2-component epoxy base RAL9110, white Paint finish: none

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	X= as delivered with serial number 594473 Country of origin: Germany Weight approx. 50 kg Packaging dimensions: 65 x 45 x 50 cm
WN534.040-019 ID3102007	coupling suitable for ZAE transmission Type M040B-1300/31-OOX-53:1-3000
Typ: W199-0003/11-OVO-3:1-1500	bevel gear Design type: 0003 Operational status: 1 Mounting side: 1 Variants: OVO Translation: 3:1 Drive speed: 1500 rpm Oil filling: Klübersynth GH6-100 Primer: 2-component epoxy base RAL9110, white Paint finish: none
Typ: S100B-1300/11-OOX-40.0:1-300	Worm gear Gearbox arrangement: 1300/11 Variants: OOX Actual translation: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without keyway Oil filling: Klübersynth GH6-460 Primer: 2-component epoxy base RAL9110, white Paint finish: none
S050B-1300/55-OOX-15.0:1-3000	ZAE servo gearbox Gearbox arrangement: 1300/55 Variants: OOX Actual translation: 14.5:1 Drive speed: 3000 rpm Square servo mounting flange: □ 095 mm Hole circle servo attachment: ø 100 mm Centering diameter for servo mounting: ø 080 mm Servo coupling for shaft end: ø 19x40 mm Oil filling: Klübersynth GH6-220 Primer: 2-component epoxy base RAL9110, white Paint finish: none X = Servo motor connection for motor 1FK7044 with drain plug

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
E063b-2000/55	ZAE KIVZE63B 2000/55 No 554685/0002
1tz9003-0ea42-2fa4-Z	3-Phasen-Motor 2.2kw , 2910 rpm (Motor)
M080 B 1315/42	No: 554686 i N=270 1/min (Redüktör)
Typ – Mw 156 0002 / 44	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.