

Zae Antriebssysteme



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bilzilere ulaŐabilirsiniz.
Zae Antriebssysteme Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Zae Antriebssysteme Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Typ: Sw156-0004/35-Oox-3:1-3500	ZAE servo bevel gearbox in engine version Type: 0004 Operating situation: 3 Mounting side: 5 Variants: OOX Translation: 3: 1 Drive speed: 3500 rpm Square servo mounting flange: □ 200 mm Bolt circle servo mounting: ø 215 mm Centering diameter servo mounting: ø 180 mm Servo coupling for shaft end: ø 38x80 mm Oil filling: Klbersynth GH6-080 Primer: 2-component epoxy base RAL9110, white Painting: RAL 9005, deep black, satin gloss suitable for mounting a Siemens motor Type 1 PH 6101 X = identical in construction with customers Article no. : 35057617 Product number: 8483 40 25 Your item no. : 35057617
W199 0003/44	Worm gear for motor mounting Gear arrangement : 1300/65 Variants : HOX Actual ratio : 53.0:1 Drive speed : 1500 rpm Oil filling : Klbersynth GH6-460 Primer : 2-component epoxy base RAL9110, white Paintwork : without H = Hollow shaft with clamping set HSD50-22 on page 6 X = Gearbox suitable for motor attachment with: Flange square : 155 mm Bolt circle diameter: 165 mm with 4x diam. 11mm Centering diameter : 130 mm for motor shaft end : diam. 32 x 60 mm lg. without key Motor coupling with clamping set HSD36-22 F flange on side 5 and 6 Gear adjusted for low backlash (backlash at operating temperature 5'-14') A notice: Design as supplied under 506976/0002.
MW 156 0004/35	No: 469491 İ : 3:1 Oil: GH6-032
SW 156 0004/35 578525 / 007	
n. Zg. 20-0693-M/3	special transmissions dimension sheet 20-0693-M/3 with grease filling BP Energrease LS0 Actual ratio: 38:1 Paint: RAL 9018 Weight approx. 8 kg
35050284	Typ: Sw156-0004/35 No: 578525 / 007 i 4:1 Oil Klbersynth GH 6-80
587495/40	

S100B-1300/11-OOX-40.0:1-300	Gear arrangement: 1300/11 Variants: OOX Actual gear ratio: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without key Oil filling: Kl¼bersynth GH6- 460 Primer: 2-component epoxy base RAL9110, white Paintwork: without
Typ: S100B-1300/11-OOX-40.0:1-300	Worm gear Gearbox arrangement: 1300/11 Variants: OOX Actual translation: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without keyway Oil filling: Kl¼bersynth GH6-460 Primer: 2-component epoxy base RAL9110, white Paint finish: none X= as delivered with serial number 594473 Country of origin: Germany Weight approx. 50 kg Packaging dimensions: 65 x 45 x 50 cm
WN534.040-019 ID3102007	coupling suitable for ZAE transmission Type M040B-1300/31-OOX-53:1-3000
Typ: W199-0003/11-OVO-3:1-1500	bevel gear Design type: 0003 Operational status: 1 Mounting side: 1 Variants: OVO Translation: 3:1 Drive speed: 1500 rpm Oil filling: Kl¼bersynth GH6-100 Primer: 2-component epoxy base RAL9110, white Paint finish: none
Typ: S100B-1300/11-OOX-40.0:1-300	Worm gear Gearbox arrangement: 1300/11 Variants: OOX Actual translation: 40.0:1 Drive speed: 300 rpm Square: □ 150 mm Centering: ø 80h7 mm Bolt circle: ø 100 mm Servo coupling for motor shaft: ø 20h7 x 36 mm without keyway Oil filling: Kl¼bersynth GH6-460 Primer: 2-component epoxy base RAL9110, white Paint finish: none
S050B-1300/55-OOX-15.0:1-3000	ZAE servo gearbox Gearbox arrangement: 1300/55 Variants: OOX Actual translation: 14.5:1 Drive speed: 3000 rpm Square servo mounting flange: □ 095 mm Hole circle servo attachment: ø 100 mm Centering diameter for servo mounting: ø 080 mm Servo coupling for shaft end: ø 19x40 mm Oil filling: Kl¼bersynth GH6-220 Primer: 2-component epoxy base RAL9110, white Paint finish: none X = Servo motor connection for motor 1FK7044 with drain plug
E063b-2000/55	ZAE KIVZE63B 2000/55 No 554685/0002
1tz9003-0ea42-2fa4-Z	3-Phasen-Motor 2.2kw , 2910 rpm (Motor)
M080 B 1315/42	No: 554686 i N=270 1/min (Red¼kt¼r)
Typ - Mw 156 0002 / 44	