Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Zeppelin

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Zeppelin Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zeppelin Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
20003181	
20003183	
201214946	
20374466	
APN 500/96 GS	
F805	
F811	
F812	
20499684	Filter cartridge 2.5m² Ø160x1000 PES-Al Outer diameter: 185mm Length: 1000mm Filter material: polyester fleece with aluminum coating Shape: conical Addition: Electrically conductive and food-approved
20356629	Filter cartridge 2.4m² Ø143x1000 PES/Al Outer diameter: 153mm Length: 1000mm Filter material: spunbonded polyester, aluminized

Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

	Filter attachment: bayonet flange Shape: conical Electrically Conductive: Yes Food suitability: Yes
20356636	Filter cartridge 2.4m² Ø143x1000 PES/PTFE Outer diameter: 153mm Length: 1000mm Filter material: Polyester spun fleece with ePTFE membrane Filter attachment: bayonet flange Shape: conical Electrically Conductive: Yes Food suitability: Yes
20356608	Filter cartridge 1.0m² Ø127x600 Baj. PES AL Outer diameter: 135mm Length: 600mm Filter material: polyester fleece with aluminum coating Filter attachment: bayonet Shape: conical Electrically Conductive: Yes Food suitability: Yes
20499693	
Rotary feeder APN500/96 GS	Rotary Valve APN 500/96.0 GS Discharge Rotary Valve for middle pressure applications ********** As spare for serial-no. 60113, order 3000007616 (year 2013) ********** Serial number / TAG number XXXXX / none General data product: Petcoke, carbon dust bulk density: 350 - 600 kg/m³ capacity: approx. 4,3 - 43 t/h rotor speed: approx. 1,7 - 28,7 RPM system pressure inlet: atmospheric system pressure outlet: max. + 0,7 bar g product temperature: max. +80°C ambient temperature: -10 - +40°C 950 Installation site: PLEASE SPECIFY ? Turkey? Export control? Altitude: PLEASE SPECIFY >mNN
Membrane D194,H23,NR/SBR-PA	