Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Zimmer Group

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Zimmer Group Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zimmer Group Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Rbps2000-A	Serie 101240
Lcp-2505ak-08	
ZIMM TYP-MSZ-50-S İ=28-1 1800 MİN MSZ-50-S-2E NR=	837114
MKS2501A	
MKS2005AK	Clamping element pneumatic Holding force: 600.0 N Holding force PLUS: 1300.0 N theoretical holding force PLUS: 1600.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MK3502K-03	Pneumatic clamping element Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) Scraper: No. Other: clearance height RoHS Compliant: Yes
MK3502K	JD157AJ
M14X1.5S-104	
M20X1.5M-110	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MKS3505AK	Clamping element pneumatic Holding force: 1250.0 N Holding force PLUS: 2200.0 N Theoretical holding force PLUS: 2750.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MBPS 2001 GS1A Zimmer	Clamp
MKS2505AR	Clamping element pneumatic
MK3001A	Clamping element / unit pneumatic Holding force: 1750 N Nominal operating pressure: 6.0 bar Minimum operating pressure: 2.0 bar Maximum operating pressure: 6.5 bar Condition: NO (normally open) Open without pressure Cylinder volume per cycle: 12 cm^3 Closing time: 0.010 s Opening time: 0.030 s Positioning accuracy +/-: 0.020 mm Minimum operating temperature: -10 °C Maximum operating temperature: 70 °C
MK 2501 A	Clamp MK 2501 A Linear
M14x1.5S 401	
M20X1.5M 110	
Klemme MKS 4501 A M5 Zimmer	Linear
ROTASCLEEN TG13	seri: 5773m1 ELERO JUNIOR 1S FİLE AKTUATÖR MOTOR
GPP5008N-AL-A	2-jaw parallel gripper pneumatic Nominal operating pressure: 6 bar Stroke per jaw: 8.0 mm Gripping force when opening: 560.0 N Gripping force when closing: 520.0 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MKS2505KB	Clamping element pneumatic RoHS Compliant: Yes Holding force: 750 N Holding force PLUS connection: 1950 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC)
RBPS2000-A	Pneumatic clamping and braking element RoHS Compliant: Yes Holding force: 10000 N Operating pressure min .: 4.0 bar State: passive (NC) Shaft Ø: 20.00 mm Scraper: Yes Sensor connection: query groove
HM1030NC	
mk3505ak AB00204218AG	
GK 20 N-B	Gripper GK 20 N-B Zimmer handling element
MK2502K	
M14X1.5S-104	
M20X1.5m-110	
MKS2001A	BJ-00414805
MGH8375	
MK5501A	
HK1501A	
SF74-180N-C	
DB314586AH	
MKR2500A	
BH777	
GP406N-C	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Stroke per jaw: 6.0 mm Gripping force when opening: 325.0 N Gripping force when closing: 300.0 N Nominal gripping force: 300.0 N
MK3502K-03	
TKPWS 5505 AS1DA	JH/102700
GPP5035NC-00-A	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar Stroke per jaw: 35.0 mm Gripping force when closing: 8000.0 N Min. spring secured gripping force: 1900 N Nominal gripping force: 8000.0 N
SF155-180N-C	handling element flat swivel unit pneumatic Nominal working pressure: 6 bar Pan Angle: 180° Torque: 62.0 Nm
GK35N-B	
Gripper GP 406NC-C Zimmer	Your item no. GP406NC-C Nominal operating pressure: 6 bar, Stroke per jaw: 6.0 mm, Gripping force when closing: 400 N, Gripping force secured by spring min.: 100 N, Gripping force: 300N - 950N
MK1501A	Clamping element pneumatic Holding force: 650 N Nominal operating pressure: 6.0 bar Minimum operating pressure: 2.0 bar Maximum operating pressure: 6.5 bar Condition: NO (normally open) Open without pressure Cylinder volume per cycle: 5 cm^3 Closing time: 0.010 s Opening time: 0.015 s Positioning accuracy +/-: 0.020 mm Minimum operating temperature: -10 °C Maximum operating temperature: 70 °C
M20x1,5M-110	
M14x1.5S-104	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MBPS2004BS1	
EB5025ST	
GPP5025N-24-A	
Mk3502k-03	Jh00192046 ag
1943293	
M27X3S-109	Damper
4482832 - PP WINDER	SCHNEIDER MAGNETIC SWITCH MFS204 SKHC 211044
MK3505AK	
Brake element RBPS2500A	Clamping elements RoHS Compliant: Yes REACH compliant: Yes PLUS connection possible: No Min. operating pressure: 4.0 bar Min. operating pressure: 4.0 bar Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm^3 Shaft Ø: 25.00 mm Sensor connection: query groove Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm^3 Sensor connection: query groove Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
MGP806N	
MKS2502K	
E050-08-147	Self-closing Silento Doppio RoHS Compliant: Yes REACH compliant: Yes Stroke: 50.0 mm, medium: fluid Type: self-closing Mass to be braked: 50.0 kg Direction of action: closing on both sides, without freewheel Freewheel length: 0.0 mm SEZ color housing: gray RAL7035 SEZ locking lever color: natural Total length max.: 237.0 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	SEZ hole spacing: 224.0 mm SEZ Ø holes: 4.2 mm SEZ width: 12.2mm SEZ height: 17.8mm SEZ locking lever design: Type S SEZ connection drilling: Cross drilling with countersink SEZ spring force F1: 17.0 N SEZ spring force F2: 28.0 N
S000-00-024	Aktivator Universal
LS16-25	
PHE16X15LMDD-A	PowerStop Industrial shock absorbers RoHS Compliant: Yes REACH compliant: Yes Series: High Energy Head: without head, short piston rod Protection: without protection Fixed stop: Yes Number of lock nuts: 1 Stroke max.: 20 mm Adjustability: No
GPD5013N-00-A	3-jaw centric gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Stroke per jaw: 13.0 mm Gripping force when opening: 3910.0 N Gripping force when closing: 3770.0 N
TPC-AS59X58M	Structural damper BasicStop
GS65-B	O-ring assembly gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Spreading stroke per jaw adjustable min.: 3.0 mm Spreading stroke per jaw adjustable max.: 6.0 mm Wiping stroke: 5.0 mm
GD308NC-C	
GPP5025N-24-A	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
KWH3512ES1A-A	
HK2001G	RoHS compliant: Yes REACH compliant: Yes Holding force: 1200 N State: N (bistable) Remains in the current position Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Maximum operating temperature: 70 °C clamping element
UBPS 5503 AS1L/02	
HK2001A	
MK2001A	RoHS compliant: Yes REACH compliant: Yes Holding force: 1000 N Nominal operating pressure: 6.0 bar Min. operating pressure: 2.0 bar Max. operating pressure: 6.5 bar State: NO (normally open) Open without pressure Cylinder volume per cycle: 8 cm^3 Closing time: 0.010 s Opening time: 0.020 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Maximum operating temperature: 70 °C
MK3505AK	
MGP803N	
MGP803NC	
HK4501A	
MKR3000A	
MFS01-S-KHC-P1-PNP	
Gripper GK 20 N-B	
RBPS2000-A	
GVAG2VK3RU	GVAG-2VK3RU Level probe Probe (2 electrodes) Size: G 1" Temp.: max.120C°

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Pressure: max.10 bar Housing: 1.4305 Electrodes: 1.4571 Coating: PVDF Sealing rings: FPM Electrical connection: 4-pin device plug DIN 43650 A (protection class IP65) Contact assignment: contacts 1,2+3 are used, Reference terminal contact on housing = contact 3 Teflon sockets: electrodes/housing Special feature: uncast, protection class of the unit similar to IP40, Product label without mention of protection class Lengths in mm: 40; 40 Material: electrode VA/K
120.073.01.009.1 JZ, NO.FT-101	PRINTING HEAD BEARING FOR LEFT-RIGHT SIDES
120.512.03.01.001.1	BRURSHING ROLLER 120.512.03.01.001.1 CONSTRUCT. WIDTH 3245 MM ARTICLE NO54015
7364 1" A-33867	NIPPLE "NITO"
12.503.30.3.4.BF17	LENZE REDUKTOR TYPE
GH7665	
GH76100	
MGH8350	
MGH83100	
MKS2501A	
HK3001A	
MKRS5000A-06	BJ-00407680
WER3000FSI19-09-A	BC-00654493
Mk3502k-03	
SF50-180D4-C	
SF50-180D4-C	
HK1501A	
MKS3502K	RoHS compliant: Yes REACH compliant: Yes Holding force: 1250 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Holding force PLUS connection: 2200 N Nominal operating pressure: 6.0 bar Operating pressure min.: 5.5 bar State: NC (normally closed) Pressure-free closed Cylinder volume per cycle: 12 cm^3 Closing time: 0.030 s Opening time: 0.020 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
GK20N-B	2-jaw angle gripper pneumatic
HKR3000A	
MKS3005AK	
GPW5008NC-00-A	
DVR63I6	6x air transmitters 6x current transmitters RoHS compliant: Yes REACH compliant: Yes Series: DVR Type: rotary distributor Connection flange according to EN ISO 9409-1: TK63 Pneumatic energy transfer: 6 connections Electrical energy transfer: 6-pole Max. current: 6 A Voltage max.: 250 V Maximum acceleration: 22 m/s^2 Maximum speed: 120 rpm Maximum speed: 720 $°/s^2$ Concentricity +/-: 0.03 mm Axial runout +/-: 0.03 mm Continuous torque: 2 Nm Loosening torque: 3.0 Nm Operating pressure max.: 10 bar Operating temperature min.: 5 °C Operating temperature max.: 80 °C Mass moment of inertia: 10.5 $kgcm^2$ Mr: 300 Nm My: 300 Nm Fa: 1500 N Recommended handling weight: 50 kg
DVR40I4	RoHS compliant: Yes REACH compliant: Yes Series: DVR Type: rotary distributor

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Connection flange according to EN ISO 9409-1: TK40 Pneumatic energy transfer: 4 connections Electrical energy transfer: 4-pole Max. current: 3 A Voltage max.: 24 V Maximum acceleration: 22 m/s² Maximum speed: 120 rpm Maximum speed: 720 °/s² Concentricity +/-: 0.02 mm Axial runout +/-: 0.02 mm Continuous torque: 1 Nm Loosening torque: 1.5 Nm Operating pressure max.: 10 bar Operating temperature min.: 5 °C Operating temperature max.: 80 °C Mass moment of inertia: 0.7 kgcm² Mr: 60 Nm My: 60 Nm Fa: 800 N Recommended handling weight: 15 kg
MKR1600A-A	clamping element (round) RoHS compliant: Yes REACH compliant: Yes Holding force: 650 N Nominal operating pressure: 6.0 bar Operating pressure min.: 2.0 bar State: NO (normally open) Open without pressure Shaft diameter: 16.00 mm holding torque: 5 Nm Cylinder volume per cycle: 6 cm³ Closing time: 0.010 s Opening time: 0.015 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
KB6.5	clamping block RoHS compliant: Yes REACH compliant: Yes Suitable for sensor diameter: 6.5 mm
GEP2006IL-03-B	2-jaw parallel gripper RoHS compliant: Yes REACH compliant: Yes stroke per jaw: 6 mm Robot adaptation: via adapter plate(s)
RBPS2000-A - clamping and braking element	clamping and braking element RoHS compliant: Yes REACH compliant: Yes

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Holding force: 10000 N Operating pressure min.: 4.0 bar State: NC (normally closed) Pressure-free closed Shaft diameter: 20.00 mm holding torque: 60 Nm Scraper: Yes Cylinder volume per cycle: 130 cm^3 Closing time: 0.090 s Opening time: 0.350 s Sensor connection: query slot Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
MFS02-S-KHC-P1-PNP	magnetic field sensor RoHS compliant: Yes REACH compliant: Yes Cable length: 0.30 m Installation type: Cable outlet axial Connection: Cable with plug Cylinder design: C-slot Switching output: PNP
NJ4-E2SK-01	inductive D4 -Inductive proximity switch Ø4 -Cable 0.3m - Connector M8 RoHS compliant: Yes REACH compliant: Yes Cable length: 0.30 m Sensor diameter: 4 mm Installation type: flush Connection: Cable with plug Switching output: PNP
LBPS2501AS2-A	Successor type of LBPS2501AS2 1:1 *compatible* RoHS compliant: Yes REACH compliant: Yes Holding force: 750 N Operating pressure min.: 5.5 bar State: NC (normally closed) Pressure-free closed Cylinder volume per cycle: 5 cm^3 Closing time: 0.015 s Opening time: 0.045 s Sensor connection: query groove (both sides) Connection type: top mirroring Positioning accuracy +/-: 0.050 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
KB8-28	RoHS compliant: Yes

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	REACH compliant: Yes Suitable for sensor diameter: 8.0 mm
GEH6040IL-31-B	2-jaw parallel gripper RoHS compliant: Yes REACH compliant: Yes stroke per jaw: 40 mm Stroke per jaw, adjustable: 40 mm Nominal gripping force: 180 N Gripping force min.: 10 N Cable routing: external Control: IO-Link
GS65-B - O-ring assembly gripper	O-ring assembly gripper RoHS compliant: Yes REACH compliant: Yes Spreading stroke per jaw adjustable min.: 3.0 mm Spreading stroke per jaw adjustable max.: 6.0 mm Stripping stroke: 5.0 mm
UBPS4502DS1LA	clamping and braking element RoHS compliant: Yes REACH compliant: Yes Holding force: 5200 N Operating pressure min.: 5.5 bar State: NC (normally closed) Pressure-free closed Scraper: Yes Cylinder volume per cycle: 50 cm^3 Closing time: 0.030 s Opening time: 0.310 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
MKS1501A	RoHS compliant: Yes REACH compliant: Yes Holding force: 400 N Holding force PLUS connection: 1300 N Nominal operating pressure: 6.0 bar Operating pressure min.: 5.5 bar State: NC (normally closed) Pressure-free closed Cylinder volume per cycle: 5 cm^3 Closing time: 0.015 s Opening time: 0.010 s Positioning accuracy +/-: 0.020 mm
KB5	RoHS compliant: Yes REACH compliant: Yes Suitable for sensor diameter: 5.0 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
3843CA2877 TPS080 clamping element	
WB5025F	quick-change jaw system
WB5025L	quick-change jaw system
GPD5025SO-00-A	3-jaw centric gripper RoHS compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar stroke per jaw: 14.0 mm Gripping force when opening: 22850.0 N Spring-secured gripping force min.: 6030 N
GEH6060IL-03-B	2-jaw parallel gripper RoHS compliant: Yes REACH compliant: Yes stroke per jaw: 60 mm Stroke per jaw, adjustable: 60 mm Nominal gripping force: 1000 N Gripping force min.: 100 N Cable routing: external Self-locking: mechanical Control: IO-Link
GEH6060IL-31-B	2-jaw parallel gripper RoHS compliant: Yes REACH compliant: Yes stroke per jaw: 60 mm Stroke per jaw, adjustable: 60 mm Nominal gripping force: 180 N Gripping force min.: 10 N Cable routing: external Control: IO-Link
HK2505KR	clamping element RoHS compliant: Yes REACH compliant: Yes Holding force: 1200 N State: N (bistable) Remains in the current position Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
AR160P	RoHS compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Connection flange according to EN ISO 9409-1: TK160 Recommended handling weight: 60 kg

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
3843CB1432 SF74D6DFE6-C-02 swivelling unit	
3843CB1431 GP110 parallel gripper	
SF50-90N-C	flat swivel unit RoHS compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Series: SF-C Type: Flat swivel unit Drive type: PNEU Swivel angle: 90 ° Torque: 2.4 Nm Swivel angle adjustable +/-: 3.0 ° Repeatability +/-: 0.01 ° through hole Ø: 9 mm Bearing load axial: 490.0 N Bearing load radial: 24.0 Nm Operating pressure min.: 3 bar Operating pressure max.: 8 bar Operating temperature min.: 5 °C Operating temperature max.: 80 °C Cylinder volume per cycle: 14.0 cm^3
UBPS5505AS1LA	RoHS compliant: Yes REACH compliant: Yes Holding force: 7700 N Holding force PLUS connection: 9200 N Nominal operating pressure: 6.0 bar Operating pressure min.: 5.5 bar State: NC (normally closed) Pressure-free closed Scraper: Yes Cylinder volume per cycle: 130 cm^3 Closing time: 0.030 s Opening time: 0.400 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating temperature max.: 70 °C
GZ1020-01	
MBPS2504BS1	
SWM1035	
SWM1045	
SWM1054	
SWM1063	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MKR300A BJ777AC	
Rbps 2000-A	
MK2002K	RoHS compliant: Yes REACH compliant: Yes Holding force: 1000 N Nominal operating pressure: 6.0 bar Min. operating pressure: 2.0 bar Max. operating pressure: 6.5 bar State: NO (normally open) Open without pressure Cylinder volume per cycle: 8 cm^3 Closing time: 0.010 s Opening time: 0.020 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Maximum operating temperature: 70 °C
HK3501A	
HK3501G	
MK2501A-	164216 pneumatic clamping element
MK3502K	clamping element pneumatic RoHS compliant: Yes REACH compliant: Yes Holding force: 2000 N Nominal operating pressure: 6.0 bar Min. operating pressure: 2.0 bar Max. operating pressure: 6.5 bar State: NO (normally open) Open without pressure Cylinder volume per cycle: 12 cm^3 Closing time: 0.010 s Opening time: 0.040 s Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Maximum operating temperature: 70 °C
GPP5025NC-00-A	2-jaw parallel gripper pneumatic
MK 3502-03	
MFS02-S-KHC-P2-PNP	
MK 2002 K (JH/103361)	
HK3501B	clamping element

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	manually RoHS compliant: Yes REACH compliant: Yes Holding force: 2000 N State: N (bistable) Remains in the current position Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Maximum operating temperature: 70 °C
GPD5030S-00-A	3-jaw centric gripper pneumatic
GPP5010N-00-A	2-jaw parallel gripper pneumatic RoHS compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Stroke per jaw: 10.0 mm Gripping force when opening: 945.0 N Gripping force when closing: 885.0 N
HM1078NC	Magnetic gripper pneumatic Maximum holding force: 220 N Maximum operating temperature: 80 °C
HM1097NC	Magnetic gripper pneumatic Maximum holding force: 450 N Maximum operating temperature: 80 °C
6140-B GRIPPER	
MK3505AK-	Clamping element pneumatic Holding force: 2000 N Nominal operating pressure: 6.0 bar Minimum operating pressure: 2.0 bar Maximum operating pressure: 6.5 bar Condition: NO (normally open) Open without pressure Cylinder volume per cycle: 12 cm^3 Closing time: 0.010 s Opening time: 0.040 s Positioning accuracy +/-: 0.020 mm Minimum operating temperature: -10 °C Maximum operating temperature: 70 °C
Mk2502k	Clamping element pneumatic Holding force: 1200.0 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) RoHS Compliant: Yes
Mk3505ak	clamping element pneumatic Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Min. Operating pressure: 2.0 bar State: active (NO) RoHS Compliant: Yes Reach compliant: Yes
Mks2505kb	clamping element Pneumatic DE 84 79 90 70 Holding force: 750.0 N Holding force PLUS: 1950,0 N theoretical holding force PLUS: 2400.0 N Nominal operating pressure: 6,0bar operating pressure: 5.5 bar RoHs; yes CE: Yes

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.